





GRAPHICS TABLET™

OPERATION AND REFERENCE MANUAL



<http://www.turbo-2.com/apple/>

NOTICE

Apple Computer Inc. reserves the right to make improvements in the product described in this manual at any time and without notice.

DISCLAIMER OF ALL WARRANTIES AND LIABILITY

APPLE COMPUTER INC. MAKES NO WARRANTIES, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THIS MANUAL OR WITH RESPECT TO THE SOFTWARE DESCRIBED IN THIS MANUAL, ITS QUALITY, PERFORMANCE, MERCHANTABILITY, OR FITNESS FOR ANY PARTICULAR PURPOSE. APPLE COMPUTER INC. SOFTWARE IS SOLD OR LICENSED "AS IS". THE ENTIRE RISK AS TO ITS QUALITY AND PERFORMANCE IS WITH THE BUYER. SHOULD THE PROGRAMS PROVE DEFECTIVE FOLLOWING THEIR PURCHASE, THE BUYER (AND NOT APPLE COMPUTER INC., ITS DISTRIBUTOR, OR ITS RETAILER) ASSUMES THE ENTIRE COST OF ALL NECESSARY SERVICING, REPAIR, OR CORRECTION AND ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. IN NO EVENT WILL APPLE COMPUTER INC. BE LIABLE FOR DIRECT, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES RESULTING FROM ANY DEFECT IN THE SOFTWARE, EVEN IF APPLE COMPUTER INC. HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF IMPLIED WARRANTIES OR LIABILITY FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU.

This manual is copyrighted. All rights are reserved. This document may not, in whole or part, be copied, photocopied, reproduced, translated or reduced to any electronic medium or machine readable form without prior consent, in writing, from Apple Computer Inc.

©1979 by APPLE COMPUTER INC.
10260 Bandley Drive
Cupertino, California 95014
(408) 996-1010

All rights reserved.
APPLE product # 030-0076-00

GRAPHICS TABLET™

OPERATION AND REFERENCE MANUAL

TABLE OF CONTENTS

INTRODUCTION

CHAPTER 1 GETTING STARTED

4	What You Will Need
5	Unpacking
6	Plugging In
7	Installing the Interface
9	Backing Up the Diskette
9	Starting Up
10	The Menu Overlay
10	Aligning the Menu

CHAPTER 2 THE GRAPHICS TABLET SOFTWARE

14	Get Ready
14	Drawing
15	The Menu
15	Delta
17	The Color Menu
18	Some Background Information
18	A Brief Digression on High-Resolution Graphics
19	Guidelines
19	A Clear Alternative
20	Line Up
21	Draw
21	Yes, Sir, Dot's My Baby
22	The Big Frame Up
23	Little Boxes
24	Saving Pictures for Posterity
27	Browsing Through the Catalog
28	Getting Loaded
29	Getting Out
30	Room With a Viewport
33	A Brilliant Reduction

34	Opening the Window
36	Broken Windows
36	Drawing in the Window
37	Reset
38	A Softer Reset
38	Calibrate
40	mistaken Calibration
40	Long Distance...
41	...And Area Codes
42	Slide Rules
43	Prismatic Apple
44	In Conclusion

CHAPTER 3

PROGRAMMING THE GRAPHICS TABLET

46	The Programs
47	Tablet-Code Applesoft
49	The Main Loop
50	Menu Items
51	Extending the Menu
51	Example: Instant Color Menu
53	Example: Circle Mode
55	Example: Disc Mode
56	The Firmware
57	Tablet Control
60	Accepting Input
61	From Machine Language
64	Quick-Draw
65	By Any Other Name

APPENDIX A

USE AND CARE

68	Care of the Menu Overlay
68	Care of the Tablet
69	Care of the Interface
69	If It Doesn't Work

APPENDIX B

COPYING THE MASTER DISKETTE

72	With Two Disk Drives
72	With One Disk Drive

APPENDIX C

COLOR ANOMALIES

76	Unusual Color Effects...
77	...And How to Get Them

APPENDIX D

PROGRAM LISTINGS

80	Tablet-Code Applesoft
85	Variable Atlas
87	Subroutines
88	Special Locations
89	ROM Code
108	quick-Draw
118	Utilities

APPENDIX E

SCHEMATIC DIAGRAM

123	
-----	--

INTRODUCTION

Welcome to the world of the Apple Graphics Tablet. The Tablet is a device which converts the position and movements of a special pen into numbers which your Apple can use and understand. The programs, or "software", supplied with your Tablet tell the Apple how to draw pictures on its high-resolution graphics screen, using the information supplied by the Tablet. These programs turn your Apple and Tablet into an artist's sketchpad, an engineer's drawing board, or a mathematician's chalkboard. With the Tablet and the supplied programs you can draw freehand pictures on the Apple's screen, or use the Apple to draw straight lines, rectangular boxes, open frames, or tiny dots. The pictures you create can easily be saved on Apple diskettes and recalled anytime you want. You can use the Apple to calculate the areas and distances of shapes and lines you draw on the Tablet, and you can change the scale of the figures you draw.

This is the Operation and Reference Manual for the Apple Graphics Tablet. The Graphics Tablet is a "hands-on" product, and the best way to learn how to use it is to take pen in hand and start experimenting. Most of this book is based on the assumption that you have the Graphics Tablet set up in front of you, and are following and doing each example as it is presented. If you try to learn how to use the Tablet without using this manual (or even worse, read the manual without actually using the Tablet), you might pick up most of the simpler commands, but you'll never master the more powerful functions of the Tablet. So read the manual, repeat the examples, and don't be afraid to experiment.

The first chapter of this book describes how to set up your Tablet, and what you need in order to use it. Chapter 2 introduces you to the Graphics Tablet software. This is a set of programs which allow you to use the Tablet to draw pictures on the Apple's high-resolution graphics screen. You do not need to know much about the Apple in order to use the Graphics Tablet. In fact, all you really need to know is how to turn it on. Once you start using the Tablet software, it will guide you each step of the way. You do not need to know how to write programs to use the Tablet skillfully and efficiently.

If you do know how to program, you may be interested in Chapter 3. It will give you assistance in modifying the Graphics Tablet software to your liking, including adding your own features to the Tablet menu. There are also instructions on interfacing directly to the Tablet's firmware, so you can write your own special-purpose programs that will use the Tablet. Listings of the programs which operate the Tablet are supplied in Appendix B.

If you see the symbol



it means that the following paragraph contains important information about some Tablet behavior that you might not anticipate. The symbol



means that the following paragraph contains special information you should note. Read these sections carefully.

Above all, feel free to play around with the Tablet. The Apple Graphics Tablet is easy to learn, easy to use, and hard to mess up. With some simple maintenance (described in Appendix A), your Tablet will give you years of enjoyment and use. So sit down at your Apple, take pen in hand, and turn to Chapter 1. We'll let you...

Draw Your
Own
Conclusion!

CHAPTER 1 GETTING STARTED

4	What You Will Need
5	Unpacking
6	Plugging In
7	Installing the Interface
9	Backing Up the Diskette
9	Starting Up
10	The Menu Overlay
10	Aligning the Menu

WHAT YOU WILL NEED

To use the Apple Graphics Tablet with its supplied software, you will need the following:

- 1) An Apple II or Apple II Plus computer, with 48K bytes of Random Access Memory (RAM);
- 2) If you do not have an Apple II Plus, you will need an Applesoft Firmware card (part number A2B0009), or an Apple Language System (part number A2B0006) with a BASICS language diskette;
- 3) An Apple Disk II plug-in controller card with at least one Disk II disk drive;
- 4) A color or black-and-white video monitor.

In addition, you may wish to have additional Disk II disk drives and controller cards.



The Graphics Tablet was designed to work with most present and future Apple II hardware and software. However, the supplied programs which operate the Graphics Tablet are designed to work with the Apple II DOS disk operating system, versions 3.2 and up. The Graphics Tablet software will not operate under previous versions of DOS or in an Apple Pascal environment.

It is helpful (but not necessary) to have read the following manuals:

- 1) The Applesoft Tutorial (product number A2L0018)
Welcome and Chapter 1
- 2) Do's and Don't's of DOS (product number A2L0012)
Preface through Chapter 2

If you are using the Apple Language System, be sure to read:

- Apple Language System (product number A2L0024)
Chapter 3: Using BASIC

UNPACKING

Your Graphics Tablet package contains ten items:

- 1) The Graphics Tablet and its attached cable.
- 2) The Graphics Tablet's indicator pen and its attached cable.
- 3) A printed-circuit board (the Graphics Tablet Interface card)
- 4) A mylar "menu" overlay.
- 5) Two "GRAPHICS TABLET SOFTWARE" diskettes.
- 6) A piece of die-cut, double-sided foam tape.
- 7) A warranty card.
- 8) A packing list.
- 9) This manual.
- 10) A static cloth.

Save the packing material in case you wish to transport your Tablet -- or in the unlikely event that you must return your Tablet to your dealer for service. If you did not fill out your warranty with your Apple dealer before you brought your Graphics Tablet home, send it in now -- not only does this ensure that any warranty repair your Tablet may need will be done as quickly as possible, but it also puts you on the mailing list for CONTACT, the Apple users' newsletter that keeps you informed of updates and new products.

PLUGGING IN



***** Special Note *****
Before connecting or disconnecting
ANYTHING
on the Apple or
the Graphics Tablet
TURN OFF THE POWER.
This is a must.

Please pay special attention to this warning: If you try to connect or disconnect something from the inside of your Apple when the power is on, there is a good chance that you may damage its electronics.

The Graphics Tablet and its pen connect to the Interface card, which in turn plugs into one of the eight peripheral connector slots in the inside of the Apple, along the back of the main board. The cables attached to the Tablet and the pen terminate in small sockets, which fit over two sets of pins on the Interface card. The sockets are spaced and keyed so that it is very difficult to attach them incorrectly.



Handle the Interface card as you would handle a high-quality, expensive phonograph record. Grasp it only by the corners or edges, and try not to touch the delicate components or pins. Don't grasp the card by the gold "fingers" -- they are the medium through which the Apple communicates to the Tablet and their efficiency is decreased if they are dirty or scratched. The Interface is a precision instrument and should be treated with care.



First attach the Tablet's pen to the interface card. Place the Interface card on a flat surface with the components face up and the gold "fingers" nearest you. Take the connector at the end of the cable from the Tablet's pen. Notice that the four tiny round holes on the bottom of the connector are keyed to correspond to the set of four pins in the upper right corner of the Interface card. Gently slide this connector over the set of pins. There should be some space between the card and the connector. The finished connection should look like this:



Now attach the Graphics Tablet to the Interface card. Take the connector at the end of the cable from the Graphics Tablet. Gently slide the connector over the set of pins near the top middle of the Interface card. When the connector is properly attached there should be some space between it and the card. The finished connection should look like this:




INSTALLING THE INTERFACE

To install the Graphics Tablet Interface card (which you have already connected to the Tablet and its pen) into the Apple, you will simply plug the Interface card into the back of the computer, as follows:

1. Turn off the power switch at the back left corner of the Apple. This is important to prevent damage to the computer. Don't unplug the Apple, just turn it off. If you unplug your Apple, you isolate it from the common earth ground and your Apple and Tablet Interface card could be in danger from static discharges.
2. Remove the cover from the Apple. Do this by pulling up on the back edge of your Apple's lid until the corner fasteners pop apart, then slide the lid back and lift it off.
3. Before proceeding, touch your hand to the metal power supply case inside your Apple. This will remove any stray static charges from your hands, so you do not damage the static-sensitive components on the Interface card.
4. Inside the Apple, across the rear of the main green board, are eight long, narrow sockets called Peripheral Connectors, or "slots". The leftmost slot (looking from the keyboard end) is called "Slot #0" and the rightmost is called "Slot #7". The Interface card will operate in any slot except #0, but it is customary for the Tablet to use Slot #5, the third one from the right.
5. Grasp the upper corners of the card between the thumbs and forefingers of both hands. Insert the gold "fingers" of the Interface card into the chosen slot in the back of the Apple, rear edge first. Gently push the front edge of the card down until it is level and firmly seated.

6. Take the two cables which you have connected to the Interface card. On the cable attached to the pen there is a black plastic fitting. This is called a strain relief. There is a hole running lengthwise along the bottom of the strain relief, with a slit running the length of the hole. Pry the slit open with your fingernail and slide the cable from the Tablet through the slit and into the hole. The finished strain relief should look like this:



Now take the strain relief with its "tail" on top and pointing out the back of the Apple and slide it into the leftmost of the two smaller vertical notches in the back of the Apple's case. Slide it down to the bottom of the notch. It should be a tight fit. If it doesn't slide all the way down the first time, pull it out and slide it back in again. The plastic is pliable enough so that it will conform to the slot's width after about three or four insertions.



7. Snap the top back onto your Apple. Place the Tablet on a flat surface near your Apple, close enough so that the pen can easily reach all parts of the Tablet surface. Make sure that your disk drive and video monitor are connected properly.

BACKING UP THE DISKETTE

Now that your Graphics Tablet is all hooked up, it's a good time to think about an important rule of thumb. "What rule?" you might ask. The rule is this: Always keep at least one backup copy of any diskette whose information you wish to keep.

The value of a backup copy cannot be overemphasized. Right now, if you were to drop both your Graphics Tablet Software diskettes, and your pet turtle started nibbling on them, or somebody mistook them for square, black Frizbees, or some other catastrophic event occurred which would render them both unreadable, then your Graphics Tablet would be almost useless. Honest. You'd have to write all new programs yourself, or buy another Graphics Tablet Software diskette, in order to use your Tablet.

Take a look at the two Graphics Tablet Software diskettes that came with your Graphics Tablet. Notice that one of them has a small piece of silver tape over the rectangular notch on its edge. This piece of tape is called a write-protect tab. The write-protect tab tells the Apple not to store any more information on the diskette in question. The tab assures that none of the information on the diskette will be accidentally written over. Store this write-protected diskette in a safe place, and use it as your backup copy.

Fortunately, you know better than to leave your Graphics Tablet diskettes lying around where they might be damaged by heat, your pet turtle, or strong magnetic fields. However, you may want to be really careful and keep two backup copies instead of just one. Keeping more than one backup copy insures that your programs will be safe even if one of your backups is accidentally destroyed. If you don't know how to go about making copies of the Graphics Tablet Software diskette, see Appendix B in this manual for instructions.



Don't put your Graphics Tablet Software diskettes, or any other diskettes, on top of the Tablet itself! Its magnetic field will wipe out any information on the diskettes.

STARTING UP

After you've reassembled your Apple and its peripherals and everything is in order, place your Graphics Tablet Software diskette into Drive 1. Remember to use the one that does not have the silver write-protect tab over the rectangular notch on its edge. Now turn the power on and "boot" the diskette. (If you don't understand what this means, STOP! Don't kick your diskette, but read the section called BOOTING DOS in Chapter 2 of your DOS manual, or Chapter 3 in the

Language System Manual if you have an Apple Language System.) The disk drive will whirr and click for about 15 seconds, then the Graphics Tablet logo will be displayed:



To begin your encounter with the Tablet, press the **ESC** key. The screen will display the Graphics Tablet "HELLO Menu", which is a list of things you can do with your Graphics Tablet Software diskette. You'll be using the MENU ALIGNMENT program first.

THE MENU OVERLAY

Included in your Graphics Tablet package is a mylar overlay called the "Graphics Tablet Menu". You will be placing this overlay in the center of the recessed area on the Tablet. The overlay divides the surface of the Tablet into different areas, and each area has a different meaning. Part of the overlay represents the Apple's high-resolution graphics screen, and another part lets you select which functions of the Tablet you want to use.

Once you attach this overlay to the Tablet, you need to tell the Apple the exact location of the overlay on the surface of the Tablet, and the Apple will help you make sure that you've put the overlay on correctly.

ALIGNING THE MENU

Before you use the Tablet, you must first place the overlay on the Tablet and align it. There is a program on your diskette which will assist you in aligning your menu overlay properly. From the Graphics Tablet HELLO menu, press **M** to select the MENU ALIGNMENT program, and then press **RETURN**.

The alignment program tells you what slot your Interface card is plugged into and then creates an information file on your diskette. The name of this file is TAB.INFORMATION. All other programs which use the Tablet can read the vital information about your Tablet and menu from this file. After you run the MENU ALIGNMENT program once, you need not run it again, unless you remove your menu overlay from the Tablet or use your Tablet with a different pen.

The MENU ALIGNMENT program will guide you in attaching and aligning the menu overlay. All you need to do is read its instructions carefully, and do just as it requests. If the menu ever comes loose from the Tablet during the alignment process, press the **[ESC]** key to re-start the whole procedure.

You'll be using four small circles of thin double-sticky foam tape, included with your Tablet, to attach the menu to the Tablet surface. Stick a small circle of tape directly under the target circle in the upper-left corner of the menu overlay, and place the overlay in the center of the recessed area of the Tablet. Stick the overlay to the Tablet surface.

Use the Graphics Tablet's pen to point to the small circle in the upper-left hand corner of the command box labelled RESET. Hold the pen perpendicular to the surface, and carefully press straight down until the point retracts into the pen, making sure that the point of the pen does not slip out of the circle.



Now take the pen and point to the small circle at the lower-left corner of the overlay. Hold the pen straight and press down. The Apple will now determine whether the overlay is straight or crooked. If it is straight, the screen will display "ALIGNED" and you can proceed. If the overlay is crooked, the program will ask you to swing the bottom edge of the overlay a little to one side. Move the overlay just a little in the proper direction and try again. Continue until the screen displays "ALIGNED". Place circles of tape under the remaining three target circles and stick them firmly to the Tablet surface. You may want to press **ESC** to end the program and then re-RUN it to make sure you didn't accidentally move the overlay when you were taping down the corners.

Now follow the arrows displayed on the screen and press the pen down in each small circle in all four corners of the overlay. Be very careful! Make sure that you're holding the pen straight up-and-down, and that the point of the pen does not stray outside of the target. If you do it correctly, you will be rewarded with the message

CREATING TABLET INFORMATION FILE

If you get any other message, you probably slipped somewhere, or the overlay isn't centered on the Tablet surface. Try it again.

Once the overlay is aligned, the Apple will return you to the Graphics Tablet logo. Press **ESC** to get to the program menu again. Now you can start using your Graphics Tablet.

(If you want to be really sure that your menu is properly aligned, you can run the MENU ALIGNMENT program again. Leave the menu taped down and just poke the proper points with the pen. If everything goes well, then your menu is well-aligned. If not, repeat the MENU ALIGNMENT procedure.)

CHAPTER 2 THE GRAPHICS TABLET SOFTWARE

14	Get Ready
14	Drawing
15	The Menu
15	Delta
17	The Color Menu
18	Some Background Information
18	A Brief Digression on High-Resolution Graphics
19	Guidlines
19	A Clear Alternative
20	Line Up
21	Draw
21	Yes, Sir, Dot's My Baby
22	The Big Frame Up
23	Little Boxes
24	Saving Pictures for Posterity
27	Browsing Through the Catalog
28	Getting Loaded
29	Getting Out
30	Room With a Viewport
33	A Brilliant Reduction
34	Opening the Window
36	Broken Windows
36	Drawing in the Window
37	Reset
38	A Softer Reset
38	Calibrate
40	Mistaken Calibration
40	Long Distance...
41	...And Area Codes
42	Slide Rules
43	Prismatic Apple
44	In Conclusion

GET READY

To start using the Graphics Tablet, go to the Graphics Tablet logo, either by re-booting the diskette, completing the MENU ALIGNMENT program, or typing

RUN HELLO

Press **ESC**. Now press **G** to select GRAPHICS TABLET SOFTWARE and press **RETURN**. The disk will whirr and chug for a while, and the Apple will present you with a blank screen. (If you get a message informing you that the Tablet information file does not exist, press **[RETURN]** and run the MENU ALIGNMENT program.) In about three seconds, your Tablet will be ready to use.

DRAWING

Touch the point of the Tablet's pen lightly to the surface of the Tablet. Move the pen around. You should see a small "crosshairs" cursor moving around the screen as you slide the pen around. The crosshairs are a locator, and the position and motions of the crosshairs on the screen correspond to the position and motions of the pen on the Tablet. Now press down on the pen so that the point retracts, and start drawing. As you draw on the Tablet, the path you trace will show up on the screen as a thin white line.



The top and sides of the working area of the overlay (the area with the fine mesh gridwork) correspond to the top and two sides of the Apple's screen. However, the working area on the overlay is slightly taller than the screen. To compensate for this difference in height, only the upper 2/3 of the overlay's working area is "mapped onto" the screen. The rest, about 2.5 inches (6.35 cm) at the bottom of the working area, is not usually active. (For information on how to use

the full working area, see the WINDOW command.) You might want to find the lower boundary of the working area and mark it with a felt tipped pen on the overlay.

THE MENU

Along the top of the Tablet's Mylar overlay are two rows of 22 squares. Each square in the top row carries the name of a certain command or function which the Tablet software can perform. These two rows of squares are called the Tablet Menu. They let you order functions for the Tablet as you would order food in a restaurant in a foreign country: by pointing to what you want. If you could speak the proper language, you would order dinner by telling the waiter what you would like. But the Tablet's language consists of thousands of magnetic and electrical impulses traveling near the speed of light. Most people can't communicate in this fashion (those who can are mutants, and thus have gone far in the computer world), so you'll have to indicate your choices to the Tablet by pointing at the Menu.

To invoke a command or function, touch the point of the Tablet's pen anywhere inside the corresponding square and press down. Hold the pen down until you hear the Apple beep. If you don't hear a beep, then you haven't fully activated the command, and you should lift the pen and try again.

The second row of boxes, which carry no name, consequently have no function. You can use them for your own programs (see EXTENDING THE MENU in Chapter 3).

The following pages describe each command and its function. To help you locate the square for each command, the section describing that command will be headed with a drawing of the menu and a pen pointing to the proper square.

DELTA


RESET	CLEAR	WINDOW	BG COLOR	DELTA	SOFT RESET	VIEW PORT	CALI- BRATE	REDUCER	PEN COLOR	DRAW
-------	-------	--------	-------------	-------	---------------	--------------	----------------	---------	--------------	------

The DELTA function lets you adjust the precision with which the pen draws on the screen. The Apple subdivides the working area of the Tablet into 53,760 small dots, each one corresponding to one dot on the Apple's screen. As you move the pen around the surface of the Tablet, the Apple draws lines between the dots you traverse. The DELTA setting lets you control the distance the pen can move before the Apple draws a line to the new dot. The smallest possible DELTA is 1. This setting will make the Apple draw a new line each time you move the pen a vertical or horizontal distance of one dot from the

Tablet, about .039 inches or 0.997 mm) from the last dot plotted. The normal value for DELTA is 2. The largest DELTA value is 127. This will make the Tablet draw a new line only after the pen has moved a horizontal or vertical distance of 127 dots (4.98 inches, or 12.6 cm) from the last dot plotted.


Associated with the DELTA setting is the Audio Feedback feature. When this feature is turned on, the Apple's speaker will emit a click each time the Apple draws a new line. With the Audio Feedback feature enabled, you can actually hear as well as see the effects of different DELTA settings.

To look at or change the current DELTA setting, touch the pen to the DELTA command square. Press it down until you hear the Apple beep. You'll see the following:



The first few lines tell you the current DELTA setting and whether the Audio Feedback feature is ON or OFF. The Apple will ask you for the new DELTA value. If you wish to retain the current DELTA value, just press **RETURN**. If not, type a number between 1 and 127 and press **RETURN**. Next, you'll be asked whether you want the Audio Feedback ON or OFF. Again, if you wish to retain the current setting, just press **RETURN**. Otherwise, type the word ON (to produce the clicks) or OFF (to silence the clicks) and press **RETURN**. The Apple will then return you to the picture you were drawing, with the new DELTA and Audio Feedback settings in effect.

Experiment a little with different DELTA settings. Set a cup or saucer on the Tablet surface and trace its perimeter several times, using different values for DELTA each time. You'll get something which looks like this:



Turn the Audio Feedback ON and OFF, and use it at different DELTA settings. At low settings, it will buzz as you move the pen around; at higher settings, you'll be able to detect distinct clicks.

THE COLOR MENU

RESET	CLEAR	WINDOW	BG COLOR	DELTA	SOFT RESET	VIEW PORT	CALI- BRATE	REDUCER	PEN COLOR	DRAW
-------	-------	--------	-------------	-------	---------------	--------------	----------------	---------	--------------	------

The Apple's screen can display six colors: black, white, green, violet, orange, and blue (of course, if you are using a black-and-white monitor, you'll see only various shades of grey). The Apple lets you draw on the screen with all of these colors.

Touch the pen to the command box marked PEN COLOR and press down. The Apple will beep, the screen will clear and the message

CONSTRUCTING COLOR MENU

will appear at the bottom of the screen. The Apple will proceed to draw eight colored boxes, surrounded by a grey border.

Move the pen lightly across the surface of the Tablet. You'll see a small block drifting around the screen (instead of the usual crosshairs). Use the pen to position the block over the color with which you wish to draw, and press down. The color menu will vanish, and you will be looking at the screen on which you were previously drawing. Now, draw! The lines you draw will be in the color you selected. Change colors again and keep drawing. All the rules are the same. Only the colors have been changed.

If, while you're shopping around for a new PEN COLOR, you decide you really don't want to change the color you've got, just press **RETURN**. Your PEN COLOR will not be changed.

SOME BACKGROUND INFORMATION

RESET	CLEAR	WINDOW	BG COLOR	DELTA	SOFT RESET	VIEW PORT	CALI- BRATE	REDUCER	PEN COLOR	DRAW
-------	-------	--------	-------------	-------	---------------	--------------	----------------	---------	--------------	------

When you start drawing with the Graphics Tablet, you're given a black screen on which to create. You can tell the Tablet that you wish to use a different-colored background by pressing the pen in the BG COLOR (BackGround COLOR) square. The Apple will present you with a color menu (as for the PEN COLOR command). Pick the color you want to use as a background; for instance, orange. The menu will vanish and the screen will instantly be filled with orange, or whatever color you have chosen.



Using the BG COLOR command will erase everything you had on the screen, so if you want to specify a BackGround COLOR, do it before you start to draw.

Are you trying the examples? Is the BackGround COLOR command working? Is orange your favorite color? Again, if you decide not to change the BackGround COLOR, just press **RETURN** instead of selecting a color. Your BackGround COLOR (and your picture, too) will be left unchanged.

A BRIEF DIGRESSION ON HIGH-RESOLUTION GRAPHICS

by now you must have noticed that there are some funny things going on with the colors. For example, set the BackGround COLOR to green and try to DRAW blue lines across it. Or set the BackGround COLOR to violet, and draw some blue lines. Obviously there's something wrong. The color "shadows" and the "zebra stripes" which you see on a color television set, or the strange distortions, unevenness, and lack of consistency you observe on a black-and-white monitor, are the results of the Apple's method of generating colors in its high-resolution graphics display. For more information on the anomalies of the Apple's high-resolution graphics color generation scheme, see Appendix C.

GUIDELINES

To minimize the problems created by the Apple's high-resolution graphics color scheme, follow these guidelines:

- 1) Most inconsistencies of the Graphics Tablet colors occur with vertical lines. Use horizontal lines when possible.
- 2) When you're drawing with black or white on a colored background, or in color on a black or white background, draw the lines a little thicker than normal by going over them twice. This takes care of the broken lines you may get.
- 3) If you need to place two colored blocks next to each other, stack them vertically, not horizontally. This cures the colored shadows that sometimes appear between colors.

So much for the digression, on with the Tablet.

A CLEAR ALTERNATIVE

RESET	CLEAR	WINDOW	BG COLOR	DELTA	SOFT RESET	VIEW PORT	CALI- BRATE	REDUCER	PEN COLOR	DRAW
-------	-------	--------	-------------	-------	---------------	--------------	----------------	---------	--------------	------

If you're tired of the scribbles and doodles on your screen, press the pen to the CLEAR square. Zap! Your whole screen will be restored to the BackGround COLOR (see the previous section). Draw mode will be restored, and, if you haven't set one, the BackGround COLOR will be black.

If you have set a VIEWPORT (described a little further on in this chapter), then CLEAR will affect only the portion of the screen inside the VIEWPORT. The rest of the screen will remain unchanged.

LINE UP

LINES	DOTS	FRAME	BOX	CATALOG	LOAD	SAVE	SEPARATE	SLIDE	AREA	DISTANCE
-------	------	-------	-----	---------	------	------	----------	-------	------	----------

So far, you've been happily drawing somewhat rough, freehand lines on the Apple's screen. If you wanted to draw a straight line between two points, you probably tried to draw it with a straightedge (smart, but awkward) or did it freehand (sloppy). "Is there a better way to draw straight lines?!", I hear you cry. Well, guess what! Yes, there's a better way to draw straight lines. Press the pen to the box which, for some obscure reason, bears the designation LINES. Now you have entered LINES mode. You will remain in LINES mode until you tell the Apple otherwise. We'll tell you how to do that later.

Meanwhile, since you're in LINES mode, let's draw some lines. Press the pen down anywhere on the Tablet's working area and lift the pen again. See the small dot left on the screen? That will be one endpoint of your line. Now press the pen down at another point in the working area. Zap! There's now a straight line connecting the two points. Press the pen down again at another point, and the Apple will draw another line, this one connecting the new point and the second point. Now rush to your nearest toy store and buy a Connect-the-Dots coloring book. Pick out an interesting page, tape it to your Tablet, and start connecting dots. The figure will magically appear on your screen.

If you want to start a second LINES figure, simply press the pen to the LINES command box again. The next point at which you press the pen will be the beginning of a new figure.



The "straight" lines you draw with your Tablet may not seem absolutely straight to you. This is normal. Lines that are neither horizontal nor vertical are actually made up of tiny zig-zags between dots on the screen.

Once you enter LINES mode, you'll stay in LINES mode until you ask to leave. The proper way to ask to be excused is to press the pen to a box that represents another drawing mode.

DRAW

RESET	CLEAR	WINDOW	BG COLOR	DELTA	SOFT RESET	VIEW PORT	CALIBRATE	REDUCER	PEN COLOR	DRAW
-------	-------	--------	----------	-------	------------	-----------	-----------	---------	-----------	------


The mode you were in before you entered LINES mode is called DRAW mode. DRAW mode is the normal state of the Graphics Tablet and is automatically put into effect when you choose the Graphics Tablet Software from the diskette menu. This means that DRAW mode is the default mode.

Whenever you wish to leave a fancy drawing mode (LINES, BOX, FRAME or DOTS), simply press the pen to the command square called DRAW. Your picture will be left intact and you will be able to draw normally until you specify another mode.

YES, SIR, DOT'S MY BABY

LINES	DOTS	FRAME	BOX	CATALOG	LOAD	SAVE	SEPARATE	SLIDE	AREA	DISTANCE
-------	------	-------	-----	---------	------	------	----------	-------	------	----------


Once you've got a picture on the screen, you might want to edit or change small portions of it. For example, you've drawn this picture:



and you want to fix up the little "glitches" around the edge. There are a couple of ways to do this: you could set the PEN COLOR to black and DRAW the glitches out, you could erase whole portions of the screen and redraw them, or you could simply erase the whole thing and start over. Fortunately, there's an easier way. Press the pen to the square marked DOTS. You are now in DOTS mode, and will remain in DOTS mode until you specify another. While you are drawing with DOTS, the

Graphics Tablet will let you plot individual points on the screen. Each time you press the pen down in the working area you will plot one, and only one, point on the screen. When you lift the pen up again and press it down in a new place, you will plot another single dot. The dots will be of the color you specified in the most recent PEN COLOR command, or white if you have not selected any other color.

By setting the PEN COLOR to the BackGround COLOR (normally black), setting DOTS mode, centering the crosshairs on the extraneous glitches in the picture, and exorcising them one by one, you can turn a rough picture like the previous one into this:



DOTS mode is also handy for adding shading and texture to your pictures. DOTS mode is most useful when used with VIEWPORT and REDUCER, described later in this chapter.

To leave DOTS mode, press the pen in the command square for any other mode (like DRAW, LINES, BOX or FRAME).


THE BIG FRAME-UP

LINES	DOTS	FRAME	BOX	CATALOG	LOAD	SAVE	SEPARATE	SLIDE	AREA	DISTANCE

When you're in the FRAME mode you can draw open rectangular boxes on the screen by specifying two diagonally opposite corner points. To enter FRAME mode, press the pen down in the (surprise!) FRAME command box. Now press the pen down anywhere on the Tablet's working area and lift it again. A single dot will appear on your screen. Take the pen and press it down at another point on the working area. The Apple will draw an open rectangle with opposite corners at the points you specified. Pick another point and press the pen down. Notice that the FRAME mode doesn't draw a frame with the new point and previous

point (as LINE mode would draw a line between them), but instead uses the new point as a corner of a separate FRAME. Pick and press a fourth point to complete the second FRAME.

Your FRAMES can be simple, or you can use many FRAMES to make a larger, more complicated FRAME:



You can draw your FRAMES in different colors, too. The FRAMES will be drawn in the current PEN COLOR, or white if you haven't selected any other color. Beware! Colored FRAMES may come out with a side or two missing because of the nature of the Apple's high-resolution graphics screen (see Appendix C). If this happens, re-draw the FRAME, but move the corner points very slightly to one side.


To leave FRAME mode, press the pen in the square for any other mode (such as DRAW, LINES, DOTS, or BOX).

LITTLE BOXES

LINES	DOTS	FRAME	BOX	CATALOG	LOAD	SAVE	SEPARATE	SLIDE	AREA	DISTANCE

There's a white one, and a blue one,
And a green one, and an orange one,
And they're all made
On the Graphics Tablet
And they all look
Just the same.

Now FRAMES are nice, but they're kind of vapid. You might even go so far as to say they're empty. If you're looking for something a little more, well, fulfilling than an ordinary rectangular quadrilateral, then the BOX mode is for you. Press the pen down in the square marked BOX. Now press the pen down at two points on the working area, as you did for FRAME. The Tablet software will give you solid indication that the task is completed by drawing a uniform, monolithic box with corners at the two points you specified.



You will remain BOXed into this mode until you free yourself by pressing the pen down in one of the squares marked DRAW, LINES, DOTS, or FRAME. The BOXes you draw will be of the current PEN COLOR. If you have not specified a different color, your boxes will be white.

SAVING PICTURES FOR POSTERITY

LINES	DOTS	FRAME	BOX	CATALOG	LOAD	SAVE	SEPARATE	SLIDE	AREA	DISTANCE
-------	------	-------	-----	---------	------	------	----------	-------	------	----------

By now you should have generated some beautiful (well, at least interesting) artwork. It's a shame that you have to erase it, isn't it? Well, you can save the entire picture for later recovery and further work by pressing the pen in the square marked SAVE. Your picture will vanish (temporarily) and the screen will display the message

TYPE A NAME FOR THIS PICTURE.

==>

A picture name can be from 1 to 26 characters long, and may include letters, numbers, and special characters (except the comma). Unlike normal diskette file names, picture names do not need to begin with a letter; you can have picture names such as

1 FOR THE ROAD

or

<<SPACE>>

(notice the spaces before the name)

The reason for this is that before the Apple saves the screen onto the diskette, it adds the prefix "PIC." to your picture name to identify it as a bona fide Graphics Tablet Picture. Since diskette file names will always begin with the letter P (in PIC.), your picture names can begin with whatever you please.

The PIC. flag also implies that the picture file includes the Tablet WINDOW setting (see the WINDOW command). Files which do not contain this information should not carry the PIC. flag.

After you type the name of the picture, press **RETURN**. If you decide you don't really want to save the picture yet, just press **RETURN** without typing any name. Your picture will reappear, and you'll be left in DRAW mode.

If you do choose to save your picture, the Apple will then ask you:

DRIVE? ==> (DEFAULT=1)

The Apple will save your picture onto the diskette in the disk drive you indicate. The DEFAULT drive is the drive which the Apple thinks you'll want to use, drive 1 the first time and the drive specified previously each time thereafter. Type the drive number you wish to use and press **RETURN**, or just press **RETURN** to select the DEFAULT drive. (If you try to specify any drive number other than 1 or 2, the Apple will use the default drive). The drive will whirr and chug for a moment, then your freshly saved picture will reappear, in DRAW mode with PEN COLOR as it was when you left.

If there is already a picture on the selected diskette with the name you specified, the Apple will display the message

A PICTURE ALREADY EXISTS WITH THAT NAME.

CONTINUE (Y OR N)

If you wish to overwrite the current picture which has the name you specified, press **Y** **RETURN**. If you don't want to destroy the picture on the diskette, press **N** **RETURN** and repeat the SAVE operation using a different picture name (a lone **RETURN** is accepted as an **N** **RETURN** response).

If you complete the SAVE procedure, or if your attempt to SAVE a picture is foiled, and you get an error message from the Apple, you will lose any VIEWPORT you may have set (see the VIEWPORT command). If, however, you have aborted the SAVE command with an **N** **RETURN**, the VIEWPORT will remain intact.

If you receive this message:

THE PICTURE IS LOCKED, OR
THE DISK IS FULL, OR PROTECTED.

PRESS SPACE BAR TO RETRY.
PRESS <CR> TO ABORT.

then any number of things could be wrong: the diskette is full and can hold no more pictures, the diskette is write-protected, or there's another picture on the diskette with the same name and the file which holds that picture is locked. In the first case, simply use another uninitialized diskette. In the second case, remove the diskette, peel off the write protect tab and reinsert the diskette. In the third case, try another file name. Whatever the problem is, you may press the spacebar to attempt to SAVE the picture again under the same name, or press **RETURN** to cancel the attempted SAVE. Your picture will reappear, and you will be back in DRAW mode.



If you filled up the diskette by trying to SAVE a picture, only part of the picture will actually be stored on the diskette. It is best to delete the partial file from the diskette after you have SAVED the picture on another diskette (see GETTING OUT).

If you receive this message:

I/O ERROR

PRESS SPACE BAR TO RETRY
PRESS <CR> TO ABORT.

while attempting to SAVE a picture, then there are problems. Maybe you specified Drive 2 when you only have one drive, or the diskette is

uninitialized, or the data on it has been destroyed. You could have a faulty disk drive or controller card, or your drive is under the influence of a powerful magnetic field (did you put it on top of your television? Naughty, naughty). There may be no diskette in the drive, or you left the drive door open, or the diskette is crimped and is not rotating. Whatever the cause, press the spacebar to attempt the SAVE again, or press **RETURN** to get back to your picture. Investigate.

BROWSING THROUGH THE CATALOG

LINES	DOTS	FRAME	BOX	CATALOG	LOAD	SAVE	SEPARATE	SLIDE	AREA	DISTANCE

You can look at the contents of your diskette by pressing the pen in the square marked CATALOG. The Apple will ask you (as above) for the drive number. You can select the DEFAULT drive by pressing **RETURN**.

The message

PRESS SPACE BAR TO CONTINUE

will be centered at the top of the screen. The drive will whirr a bit, and the names of all files on the diskette will be presented. Don't press the spacebar yet! The file names which begin in PIC. are your Graphics Tablet pictures, and should all have the annotation B 033 to the left of them. Incidentally, the B denotes that they're BINARY files, and the 033 means that they use 33 diskette sectors, or a little over 8K bytes of memory, each. If you see any PIC. files which aren't marked B 033, then they're not complete pictures. Change their names (see GETTING OUT) so you don't mistake them for Graphics Tablet pictures in the future.

If you order a CATALOG of the Graphics Tablet Software diskette, these files will be included:

PRESS SPACE BAR TO CONTINUE

DISK VOLUME 254

000 HELLO
014 GRAPHICS TABLET LOGO
010 MENU ALIGNMENT
003 GRAPHICS TABLET SOFTWARE
010 QUICK-DRAW
003 UTILITIES
002 DOCUMENT FILE LENGTHS
040 TABLET CODE APPLESOFT
002 TAB INFORMATION

These are all component programs of the Graphics Tablet package. The only notable file is the GRAPHICS TABLET LOGO, which you'll notice has the notation B 034 to the left of it. (The 034 means that it's

slightly larger than normal Tablet pictures, which are labeled B033. This causes no problems, however.) This is the picture of the Graphics Tablet Logo frame, which you see when you boot the diskette. You can LOAD this picture and work on it, even though it's not a PIC. file (see LOAD, below, for details).

CATALOG can fall victim to the same I/O ERROR problems as noted in SAVE. See the previous section for details.

If the CATALOG listing is too long for the screen, the listing will pause after displaying 18 files. Press the spacebar to get the rest of the CATALOG.

When you've finished looking at the CATALOG, just press the spacebar. Your picture will instantly reappear on the screen, with PEN COLOR unchanged.

GETTING LOADED

LINES	DOTS	FRAME	BOX	CATALOG	LOAD	SAVE	SEPARATE	SLIDE	AREA	DISTANCE
-------	------	-------	-----	---------	------	------	----------	-------	------	----------

Once you have SAVED a picture on diskette, you can call it back to your screen to be worked on some more, or just bring it out so you can admire it for a minute. Press the pen to the square marked LOAD. The following words will appear:

PLEASE TYPE THE PICTURE NAME.
==>

If you change your mind and don't want to LOAD a new picture, press **RETURN**. Your previous picture will reappear, and you will be left in DRAW mode with the same PEN COLOR as when you left.

If you do want to LOAD another picture, type the name of the picture which you wish to see, and press **RETURN**. You don't have to type the PIC., the Apple will supply that for you. The rules for naming pictures are the same as described in the SAVE command.

You will then be asked to specify which drive the diskette with the chosen picture is in. Press **RETURN** to indicate that it's in the DEFAULT drive, or type the drive number (1 or 2) and press **RETURN**.

The disk drive will spin for a few moments, then the selected picture will appear on the screen. You will be left in DRAW mode.

LOAD is vulnerable to the same disk I/O ERROR problems as were described in the SAVE section.

You can LOAD picture files which were not created by the SAVE command, as long as they carry the notation B 034 in their CATALOG listing. One such file is the GRAPHICS TABLET LOGO file on your Graphics Tablet Software diskette. Even though this file doesn't have the PIC. flag in front of its name, it can be LOADED and worked upon like any other picture. If you LOAD this file, and SAVE it again, the new version will have the prefix PIC. attached to the name, and will have the notation B033 to its left in the CATALOG.

When the Apple sees the PIC. prefix, it infers that the file contains information about the Tablet WINDOW setting along with the picture. The absence of the PIC. flag indicates to the Apple that it should use the default WINDOW setting (see the WINDOW command). In addition, if you have a picture on the diskette whose file name does have the PIC. prefix, you can make the Apple ignore the Tablet WINDOW setting in that file by typing the PIC. prefix at the beginning of the file name when you LOAD it.



If you LOAD a picture which was SAVED on another Apple or Graphics Tablet, it's possible that the Tablet which created that picture uses a slightly different WINDOW setting than yours. The difference usually appears as a discrepancy between the motions of the pen across the working area and of the crosshairs on the screen. If the crosshairs don't correspond to the pen position, then re-LOAD the picture, but type the PIC. prefix at the beginning of the file name. This will make the Apple use the proper WINDOW setting for your Tablet.

With one exception, an attempt to LOAD a picture, whether successful or not, will remove any VIEWPORT you may have set (see the VIEWPORT command). If you have aborted the attempted LOAD with a **N** **RETURN** or a **RETURN**, this rule does not apply.

GETTING OUT

With the Graphics Tablet, you can perform three simple operations with disk files: SAVE, CATALOG, and LOAD. In order to RENAME or DELETE picture files, you'll have to leave the Graphics Tablet Software and get back to the Applesoft/DOS command level. To do this, get to DRAW mode and press **ESC**. The Apple will ask you if you indeed wish to leave.



If you answer **Y**, you will lose whatever picture you had on the screen! Any other reply will send you back to your artwork, in DRAW mode.

If you answer **Y**, then the Apple will run the HELLO program on the diskette, and you will see the Graphics Tablet Logo frame (see Chapter 1, STARTING UP).

Press **ESC** again to get to the HELLO menu. Choose **Q** to QUIT and press **RETURN**. The screen will be cleared and the Applesoft prompt character (>) will appear in the upper-left corner.

Now you can DELETE, RENAME, LOCK, UNLOCK, or VERIFY any of your picture files on the diskette, or do almost anything else in Applesoft or with DOS. (For details on how to perform these operations, see Chapters 2 and 4 of your DOS manual.) Remember to include the PIC. at the beginning of the pictures' file names! To return to the Graphics Tablet software, type

RUN HELLO

When the Graphics Tablet logo appears, press **ESC**, select **G** for Graphics Tablet Software, and press **RETURN**. You'll be working with the Tablet again, with a blank screen, a white pen, no VIEWPORT, the WINDOW at its default setting, the REDUCER off, and in DRAW mode.



DON'T try to RUN the file GRAPHICS TABLET SOFTWARE directly! It is not a program in itself, but is an EXEC file which runs several programs and sets up some parameters necessary for the well-being of the Tablet software. You should always enter the Graphics Tablet Software by selecting it from the HELLO menu.

ROOM WITH A VIEWPORT

RESET	CLEAR	WINDOW	BG COLOR	DELTA	SOFT RESET	VIEW PORT	CALIBRATE	REDUCER	PEN COLOR	DRAW
-------	-------	--------	----------	-------	------------	-----------	-----------	---------	-----------	------

Am I to spend the rest of my short life
Confined by these four corners, bright and sharp?
Shall I be limited in my designs
To draw only within this VIEWPORT small?

This cannot be! And yet, there's recompense:
The box which limits, also can protect,
And keep me from destroying what I've wrought.
Confine, protect; the VIEWPORT functions thus.

You can use the VIEWPORT command to select a rectangular area on the screen. Once you set an area for a VIEWPORT, you will be allowed to draw only within that area. This allows you to concentrate on one

area of the screen at a time, while protecting the rest of the picture from being accidentally erased or overdrawn.

The VIEWPORT appears on the screen as four small "L"-shaped corner marks, one at each corner of the VIEWPORT. Each leg of each "L" is three dots long and one dot high. The VIEWPORT itself is the area enclosed by these four corners (the corners are actually outside the VIEWPORT proper). If you change or remove a VIEWPORT, the corner marks vanish without a trace, leaving the screen under them unchanged.

To specify a VIEWPORT, press the pen to the VIEWPORT square on the Tablet menu. The prompting message

UPPER LEFT?

will appear briefly at the bottom of the screen. Position the pen at the spot where the upper-left corner of the VIEWPORT should be (imagine you're drawing a FRAME) and press down. One corner mark will appear, and another prompting message:

LOWER RIGHT?

will be displayed:



Position the pen at the opposite (lower-right) corner of your proposed VIEWPORT, and press down. The other three corners of the viewport will appear. This is how the finished VIEWPORT will look:



Unlike FRAME and BOX modes, in which you can specify the corner points in any order, VIEWPORT really does want the second corner point to be below and to the right of the first. If you give the points in reverse order, or specify an impossible VIEWPORT (one which has no height or width), then you will receive the message

PLEASE SPECIFY POINTS CORRECTLY

You will then be asked for both corner points again.

Once you've set a VIEWPORT, what do you do with it? Simple, just DRAW. After you specify the two corner points, and you see the four-cornered frame, you will be placed in DRAW mode with the PEN COLOR unchanged. Anything you DRAW outside of the VIEWPORT simply will not show up on the screen; anything you draw inside it, will. Notice that the crosshairs will appear even outside the VIEWPORT, but pressing down on the pen has no effect.

You can change to any other drawing mode (BOX, DOTS, LINES, or FRAME) and it will work normally inside the VIEWPORT. But if, while you're in one of these modes, you try to specify a point outside the VIEWPORT, you'll receive the admonition

POINT OUTSIDE VIEWPORT. RESPECIFY.

Just choose another point inside the VIEWPORT. If you want to restart the BOX, FRAME, or LINE you're drawing, press the pen to the square for the proper mode again.

If you invoke the VIEWPORT command when another VIEWPORT is already active, the Apple will remove the previous VIEWPORT before asking you to specify a new one.

At any time after you have invoked the VIEWPORT command, but before you have finished specifying a new VIEWPORT, you can tell the Apple to give you one of two special VIEWPORTs. One of these is the VIEWPORT you were using before you started to set a new one, and the other is the "default" VIEWPORT (the currently set WINDOW).

To recover the VIEWPORT you had before you started to set a new one, press **RETURN** before you finish the VIEWPORT command.

To request the default VIEWPORT, press **D** before you finish the VIEWPORT command. The default VIEWPORT is the full screen, or (if you have invoked the WINDOW command) the area within the WINDOW. When the VIEWPORT is set to the full screen, no corner marks appear.

The VIEWPORT command always leaves you in DRAW mode with the PEN COLOR unchanged.

A BRILLIANT REDUCTION

RESET	CLEAR	WINDOW	BG COLOR	DELTA	SOFT RESET	VIEW PORT	CALI- BRATE	REDUCER	PEN COLOR	DRAW
-------	-------	--------	-------------	-------	---------------	--------------	----------------	---------	--------------	------

Once you've set a VIEWPORT, you can use the REDUCER function to shrink the entire Tablet working area into the VIEWPORT on the screen. This allows you to convert large pen motions on the Tablet into small motions on the screen. This lets you make precise, small drawings. When you use the REDUCER in conjunction with the DOTS mode, you can modify very small areas of a picture, setting and resetting individual dots if necessary.

Once the REDUCER is enabled, it will stay in effect until you remove it or change the VIEWPORT. To use the REDUCER, set a VIEWPORT around the area in which you wish to work, then press the pen to the square marked REDUCER. When you hear the Apple beep, the REDUCER is active. If you receive the message

NOT POSSIBLE.

then you have specified a VIEWPORT which is too small or too disproportionately shaped for the REDUCER to function. Such an impossible reduction will leave you with the REDUCER inactive and everything else unchanged.



The screen position of the VIEWPORT determines the minimum possible size into which you can REDUCE. You can REDUCE into smaller VIEWPORTs in the upper-left corner of the screen than in the lower-right corner. Specifically, the smallest possible VIEWPORT size into which you can REDUCE ranges from two screen dots square (at the normal WINDOW setting) in the upper-left corner to 45 dots square in the lower-right.

To disable the REDUCER, press the pen to the REDUCER square again. The Apple will beep and the REDUCER will be disabled. The RESET, SOFT RESET, WINDOW, VIEWPORT, and LOAD commands also disable the REDUCER.

When the VIEWPORT is at its default setting, the REDUCER has no effect.

OPENING THE WINDOW



The WINDOW command works like a VIEWPORT with the REDUCER on, but the other way 'round. Where VIEWPORT with REDUCER lets you draw something large on the Tablet, and have it appear smaller and in a specific place on the screen, the WINDOW lets you draw something small in a specific place on the Tablet and have it appear large on the screen.

You normally set a WINDOW before you begin drawing a picture. Press the pen to CLEAR and then to WINDOW. This will appear on the screen:



Find a picture of a molehill and tape it to the Tablet's working area. Now take a pen or a pencil (not the Tablet's pen!) and draw a box around the significant part of the picture. Take the Tablet's pen and, following the highlighted instructions on your screen, press it to the upper-left corner of the box. The highlighting will shift:



Press the pen to the lower-right corner. The words will disappear and the drawing screen will return, with a large frame in the middle of the screen. This frame is proportional to and corresponds with the frame around the molehill on the Tablet, and is centered on the screen. Take the pen, set DRAW mode, and trace the molehill. You will make a mountain on your screen out of the molehill taped to the Tablet.



After it's finished, WINDOW returns you to DRAW mode, with your PEN COLOR unchanged and the VIEWPORT set to the same size as the WINDOW frame on the screen.

The reason that you aren't shown the screen and crosshairs while you set the WINDOW (as you are when you set a VIEWPORT) is that you're selecting an area on the Tablet, not the screen. The resulting area on the screen is as large as the Apple can make it, proportional in size to the WINDOW on the tablet, and centered on the screen. Since the WINDOW area on the Tablet bears little relation to the screen before it's set, the screen and crosshairs are not displayed.

At any time after you have initiated the WINDOW command and before you have completed it, you can use the Apple's keyboard to indicate that you want the default WINDOW, (the entire working area of the Tablet.)

or that you want to cancel the WINDOW sequence. Press **RETURN** at any time during the WINDOW sequence to cancel it; press **D** to select the default WINDOW.

BROKEN WINDOWS

If you receive the message

PLEASE SPECIFY POINTS CORRECTLY!

then you've not specified the two corner points in their proper upper-left, lower-right order, or you've tried to set the WINDOW to an area on the Tablet that's too small. You will be asked to specify both corners again. If you want to cancel the attempted WINDOW, press **RETURN**.

If the Apple flashes the message

PLEASE STAY WITHIN THE WORK-AREA.

then you've let the pen stray outside the working area of the Tablet's overlay. You will be prompted again to indicate the corner point. To cancel the WINDOW command, press **RETURN**.

DRAWING IN THE WINDOW

Once you've placed a WINDOW on the Tablet, you can use any of the Tablet's drawing modes (DRAW, LINES, DOTS, FRAME, or BOX) to draw, as long as you stay within that WINDOW.

You can set the VIEWPORT within the WINDOW on the screen. Once you've set it, you can even REDUCE into it, and use the entire Tablet area within the VIEWPORT. When you turn the REDUCER off, you will again be limited to your WINDOW.

Once you've set a WINDOW, the only way to remove the WINDOW frame is to set a new WINDOW or use the Tablet RESET command. No other Tablet command will remove a WINDOW. The REDUCER will allow you to temporarily override the WINDOW; when you turn off the REDUCER, you will be left with the previous WINDOW again. Experiment with using WINDOW and the REDUCER; you'll be surprised at what they can do.



When you specify a WINDOW on the Tablet, the Apple will draw the WINDOW frame on the screen on top of the current picture. The sides of the frame are two dots wide, and the top and bottom are one dot wide. If you set a new WINDOW, the Apple will remove the frame by drawing over it with the BackGround COLOR. The WINDOW command can

therefore destroy parts of your previous picture. Also, even though WINDOW sets the VIEWPORT to the portion of the screen inside the WINDOW frame, the CLEAR command will clear the entire screen, including everything outside the VIEWPORT and the WINDOW frame, and even the frame itself! (The frame will be redrawn after the CLEAR.) If you reset the VIEWPORT to a slightly smaller size than the WINDOW, the CLEAR command will work normally and erase only what is within the VIEWPORT.

The WINDOW information is stored along with the picture information when you SAVE a picture onto diskette. There is no way to avoid saving this information. When you LOAD a picture, the Apple will automatically use the WINDOW setting stored with that picture, if that picture's diskette file name begins with PIC. If it does not, the Apple will use the default WINDOW setting for your Tablet. You can force the Apple to ignore the WINDOW setting stored in a picture file in three ways:

1) Leave the Graphics Tablet Software (see GETTING OUT) and RENAME the file, removing the PIC. prefix from the file name.

-- or --

2) When you LOAD the picture, type the PIC. flag at the beginning of the picture name. (LOAD PIC.filename)

-- or --

3) Once you have LOADED the picture, press the pen to WINDOW and type **D** to get the default setting.

RESET

RESET	CLEAR	WINDOW	BG COLOR	DELTA	SOFT RESET	VIEW PORT	CALI- BRATE	REDUCER	PEN COLOR	DRAW
-------	-------	--------	-------------	-------	---------------	--------------	----------------	---------	--------------	------

The RESET command lets you "wipe the slate clean" and begin anew on a fresh picture. Namely, it:

- 1) Sets the WINDOW to the the normal 11 inch wide, 6.5 inch tall rectangle at the top of the working area.
- 2) Sets the VIEWPORT to the full screen.
- 3) Sets CALIBRATE to one unit per screen dot, and leaves the unit type undefined.
- 4) Sets the BackGround COLOR to black, and clears the screen.
- 5) Sets the PEN COLOR to white and sets DRAW mode.

- 6) Sets the value of DELTA to 2 and turns the Audio Feedback feature OFF.
- 7) Sets the default drive number for LOAD, SAVE, and CATALOG to 1.

Using the RESET command is just like restarting the Graphics Tablet software all over again.

A SOFTER RESET

RESET	CLEAR	WINDOW	BG COLOR	DELTA	SOFT RESET	VIEW PORT	CALIBRATE	REDUCER	PEN COLOR	DRAW
-------	-------	--------	----------	-------	------------	-----------	-----------	---------	-----------	------

The SOFT RESET command is a milder version of RESET. It lets you reset many of your drawing and calculating functions, while leaving your picture, WINDOW settings, and pen color intact. SOFT RESET:

- 1) Sets the VIEWPORT to the full screen, or to the currently set WINDOW. This is the same as pressing **D** while setting a VIEWPORT.
- 2) Sets the CALIBRATE unit to 1 and the unit type undefined.
- 3) Sets the DELTA value to 2 and turns the Audio Feedback feature OFF.
- 4) Sets DRAW mode.

Nothing else is changed by SOFT RESET. The PEN COLOR, BackGround COLOR, the WINDOW setting, the default drive number, and so on, all remain the same.

CALIBRATE

RESET	CLEAR	WINDOW	BG COLOR	DELTA	SOFT RESET	VIEW PORT	CALIBRATE	REDUCER	PEN COLOR	DRAW
-------	-------	--------	----------	-------	------------	-----------	-----------	---------	-----------	------

The CALIBRATE command lets you specify a distance on the Tablet surface and use it for measuring with the DISTANCE and AREA functions.


Press the pen to the CALIBRATE square on the menu. The Apple will beep and the brief question:

BEGINNING POINT?

will appear at the bottom of the screen. Select a point and press down. Another brief question:

ENDING POINT?

will flash at the bottom of the screen. Select another point, say, an inch away from the first and press down. The screen will vanish and the following frame will appear:



The Apple has converted the distance between the two points you specified into its internal "screen units". You now have the opportunity to define how long that distance actually was. If you've just arrived from Alpha Centauri, and you specified a distance of about one U.S. inch, then that's about 5 glibbets. Type

5 **RETURN**
G L I B B E T S **RETURN**

You've now defined the length you specified to be 5 Alpha Centauri glibbets. You're free to change it, of course, and give a distance of 10 chronacs, 200 malms, or even half a greton if you so desire (use decimal numbers for fractions, in this case **.5** gretons).

The CALIBRATE command won't let you specify negative distances, or distances greater than 999999999. It also won't let you use a name for your measurement which is more than 10 letters, numbers, or special characters (such as asterisks, bracketts, etc.) long.

You can tell the Apple that you'll agree to use its internal screen units for measurement by answering its questions about length and name with the **RETURN** key. Once you've specified a distance and unit name in the CALIBRATE command, they will remain as you set them until you: a) reset them with the CALIBRATE command, b) do a RESET or a SOFT RESET, or c) change the BackGround COLOR, the VIEWPORT setting, or the WINDOW setting.

MISTAKEN CALIBRATION

If you specify an endpoint for the CALIBRATE distance which is outside the current VIEWPORT, you will be asked to indicate the point again.

Once you begin to define a distance for the CALIBRATE command, you can cancel the procedure by pressing the **RETURN** key.



Don't change the REDUCER setting after you've CALIBRATED your Tablet. If you do, it will shrink your measurements just as it shrunk your Tablet movements, and all your DISTANCE and AREA calculations will be incorrect.

LONG DISTANCE...

LINES	DOTS	FRAME	BOX	CATALOG	LOAD	SAVE	SEPARATE	SLIDE	AREA	DISTANCE
-------	------	-------	-----	---------	------	------	----------	-------	------	----------

Once you've set a distance and a unit name with the CALIBRATE command, you can use those definitions to calculate the DISTANCE that you move the pen along a path on the Tablet surface.

For example, find a road map (we'll use one of Central California), unfold it, and tape it to the Tablet so that the legend (with the scale of distance) is in the working area. Use the CALIBRATE command to set the distance and unit name to the scale of distance on the map:



Now point the pen to the DISTANCE square and press down. The Apple will beep, signaling you to take the pen and trace a path on the map. Draw a path from Buttonwillow to Bakersfield, along Route 5. The path

will appear on the screen as you draw. When you lift the pen, the Apple will beep again and flash

CALCULATING...

at the bottom of the screen, and then go away and think for a moment. It will soon return, telling you that the DISTANCE you traveled from Buttonwillow to Bakersfield is about 25 miles. After a short delay, you will be returned to DRAW mode.

The path you draw, as it appears on the screen, is just like any other path in DRAW mode, and it is subject to the same DELTA effects as DRAW. Lower DELTA settings will give you more accurate DISTANCES; higher DELTA settings will give you less accurate (albeit quicker) approximations.

If you invoke the DISTANCE command and then decide you don't want to calculate a distance after all, simply press the **RETURN** key instead of drawing a path on the Tablet.

There is a limitation on the maximum DISTANCE your path can be. The longest path you can draw for DISTANCE contains 800 points. With a DELTA setting of 2, this is 1600 screen units, or about 59 actual inches on the Tablet. Of course, this will be different if you're using the WINDOW or REDUCER functions.

... AND AREA CODES

LINES	DOTS	FRAME	BOX	CATALOG	LOAD	SAVE	SEPARATE	SLIDE	AREA	DISTANCE
-------	------	-------	-----	---------	------	------	----------	-------	------	----------

The AREA command is a counterpart to the DISTANCE command. But instead of letting you find the DISTANCE between Buttonwillow and Bakersfield, CA, it will let you figure the AREA of Manhattan. Quickly remove the map of Central California and switch to one of the New York City area. Use the CALIBRATE command with the scale of distance on the new map.

Now place the pen on the AREA square and press down. The Apple will respond with a beep. Trace the perimeter of Manhattan. As soon as you lift the pen, the Apple will beep again and flash

CALCULATING...

and sit and think for a few moments. Soon it will return with the area of the island, expressed in the units you set in the CALIBRATE command. It will hold this value on the screen for about five seconds, and then return you to DRAW mode.

Now CLEAR the screen and try it again. This time, don't go completely around the island, but stop about half an inch away from your starting point. The Apple will obligingly close the curve for you, connecting the ending point directly to the beginning, before it calculates the AREA.

AREA is subject to the same limitations as DISTANCE: you can only draw a path 800 points long, or about 59 Tablet inches with a DELTA setting of 2. As in DISTANCE, a larger DELTA setting will give you less accurate results. And if you had the REDUCER on when you CALIBRATED, don't turn it off when you are going to calculate an AREA. A press of the **RETURN** key will abort the AREA command, just as it will for the DISTANCE command.

Now CLEAR the screen and find the AREA of Manhattan again. This time, go around the island twice. Notice that even though the AREA looks the same on the screen, the number that the Apple will return is about twice the actual AREA of the figure. This is normal: if you go around three times, the Apple will give you a number three times too large, and so on.

If, while drawing around an AREA, you move the pen outside the VIEWPORT, the Apple will act as if you had lifted the pen at that point, close the curve, and figure the AREA.

SLIDE RULES

LINES	DOTS	FRAME	BOX	CATALOG	LOAD	SAVE	SEPARATE	SLIDE	AREA	DISTANCE
-------	------	-------	-----	---------	------	------	----------	-------	------	----------

Once you've got a picture on the screen, you don't have to rest at that. No, you can mobilize your pictures, give them some motivation, see some action! Press the pen to the SLIDE square. The request

BEGINNING POINT?

will appear briefly at the bottom of the screen. Use the pen to select any point on your picture, and press down. A second request

ENDING POINT?

will appear. Select another point on the screen, some distance removed from the first. Watch your picture travel across the screen, both vertically and horizontally, until the first point you selected (on the picture) is in the vicinity of the second point (on the screen).

If you decide that a SLIDE isn't what you want right now, press **RETURN** to cancel the operation. You'll be returned to your picture, in DRAW mode.

The SLIDE operation is performed in four directions, with what mathematicians call "toroidal wrap-around". This ponderous phrase means that the picture thinks it's not on a flat screen, but wrapped around a doughnut: the left side is joined to the right side, and the top is joined to the bottom, so that everything that you SLIDE off one edge of the screen will reappear on the opposite edge. When your SLIDE is complete, you will be returned to DRAW mode.

SLIDE moves the entire screen: there is no way to move only a portion of the screen. Because of the way the Apple places colors on the screen (see A SHORT DIGRESSION...), the SLIDE command can move the picture the exact vertical distance you indicate, but can only come within 14 dots of the horizontal location you specify.

SLIDE will remove the VIEWPORT and WINDOW borders before it moves the picture, but will replace them in their former locations (not SLID over) after the SLIDE is complete.

PRISMATIC APPLE

LINES	DOTS	FRAME	BOX	CATALOG	LOAD	SAVE	SEPARATE	SLIDE	AREA	DISTANCE
-------	------	-------	-----	---------	------	------	----------	-------	------	----------

The SEPARATE function "strips" your picture, until only one color is left. Press the pen to the SEPARATE square. You will be presented with a color menu, just like in PEN or BackGround COLOR. REMEMBER: The SEPARATE command will destroy parts of your picture. If you want to preserve a picture, be sure to SAVE it before you do a SEPARATE. If you've already started a SEPARATE command, just press **RETURN** to cancel it and return you to DRAW mode.

If you do want to SEPARATE out your picture, select a color from the color menu with the pen and press down. The menu will vanish and your picture will reappear. Quicker than you can pronounce "refraction", your picture will be stripped of all colors except the one you selected. You will be left in DRAW mode, with your BackGround COLOR set to black and your PEN COLOR set to the SEPARATE color you specified.

There is no way to undo a SEPARATION. The SEPARATE command will remove any VIEWPORT or WINDOW before it performs its function, and restore them when it's finished. SEPARATE works only on the entire screen: there is no way to SEPARATE only a portion of the screen.

You cannot SEPARATE out the color black. If you did, you'd be left with a blank screen! The Apple will deny your attempt to separate out either of the blacks with the message

NO SEPARATION ON BLACKS.

IN CONCLUSION

Congratulations! If you've come this far, and practiced with your Tablet along the way, then you've mastered the basic functions of the Apple Graphics Tablet. With a little practice, you can be drawing and manipulating pictures with skill and ease. If you're interested in doing more with your Tablet, and you're accustomed to programming in Applesoft BASIC, then you might be interested in looking into Chapter 3. It describes the internal operation of the Graphics Tablet software, and the operating subroutines in the Graphics Tablet itself. You'll find dozens of new applications for your Tablet. Go ahead, keep drawing, and have fun!

CHAPTER 3 PROGRAMMING THE GRAPHICS TABLET

46	The Programs
47	Tablet-Code Applesoft
49	The Main Loop
50	Menu Items
51	Extending the Menu
51	Example: Instant Color Menu
53	Example: Circle Mode
55	Example: Disc Mode
56	The Firmware
57	Tablet Control
60	Accepting Input
61	From Machine Language
64	Quick-Draw
65	By Any Other Name

THE PROGRAMS

There are four main programs which comprise the Graphics Tablet software. Three of these programs are supplied on your GRAPHICS TABLET SOFTWARE diskette, and the fourth is stored in ROM (Read-Only Memory) on the Tablet Interface card. These programs are:

- 1) **TABLET-CODE APPLESOFT:** This is a large applications program, written in the Applesoft II BASIC programming language. This is the program which performs all the commands and functions of the Tablet as described in Chapter 2.
- 2) **QUICK-DRAW:** This is a machine language subroutine which is used by the TABLET-CODE APPLESOFT program. This subroutine allows an Applesoft program to draw lines on the Apple's high-resolution graphics screen as fast as the Tablet can supply the points. This machine-language subroutine is hidden inside an Applesoft program.
- 3) **Tablet Firmware:** This is a set of subroutines permanently stored in ROM on the Tablet's Interface card. These are base-level subroutines for the basic operation of the Tablet. They can be used from any Apple programming language.
- 4) **UTILITIES:** This is a package of machine-language subroutines which perform many of the screen manipulation functions of the TABLET-CODE program. This package includes the subroutines which perform the SEPARATE and SLIDE operations. It also includes the shape table used by the Applesoft DRAW command to draw the corner marks for the VIEWPORT. These subroutines are stored in a binary file on the diskette and load at location \$6000 (decimal 24576) in memory. The length of this file is \$330 (816 decimal) bytes.

In addition, there are two other Applesoft programs which are used as part of the Graphics Tablet software package, but don't take part in the actual operation of the Tablet. They are:

- 1) **HELLO:** This is the program which is executed when you boot the diskette. It is also executed whenever you exit the TABLET-CODE or MENU ALIGNMENT programs. It allows you to select which program you wish to run, and lets you quit if you want to.
- 2) **MENU ALIGNMENT:** This is another Applesoft program that sets up an information file on the diskette, called TAB.INFORMATION. This file contains information about what slot the Interface card is in and where the overlay is located on the Tablet.

TABLET-CODE APPLESOFT

This is the main operating program for the Graphics Tablet. It is written in Applesoft, and takes up 12K bytes of the Apple's memory. It resides between locations \$1000 and \$3FFF (decimal 4096 and 16383) of memory. It requires that your Apple have the Applesoft language in ROM or on a Language System Language card. It will not run with cassette or diskette versions of Applesoft.

A source listing of this program appears in Appendix D, along with an atlas of subroutines, variables, and special locations. Here is a brief map to the program:

<u>Lines</u>	<u>Function</u>
10-160	Initialization. This section reads the Tablet information file, sets up all pertinent Tablet parameters, and initializes and clears Page 2 of the Apple's high-resolution graphics screen. It also places the program and its variables in the proper locations in the Apple's memory, and loads the UTILITIES subroutines.
170-180	This is the main DRAW mode loop. These two lines take input from the Tablet pen and send it to the QUICK-DRAW subroutine to draw on the screen. The only way out of this loop is to press a key or press the pen outside the Tablet's working area (i.e., on the menu).
190-194	These lines are executed when you press a key during DRAW mode. If you press any key other than ESC , nothing happens. If you press ESC , you will be asked whether you wish to quit or not. Pressing any key other than Y will return you to DRAW mode. Otherwise, the HELLO program will be run.
200-290	These lines sense when you press the pen to the menu. Line 280 is the main menu vector table.
300-310	The CLEAR command.
330-410	The LOAD command.
420-520	The SAVE command.
530-540	A subroutine to input the disk drive number during LOAD, SAVE, and CATALOG.
550-560	The SOFT RESET command.
570-610	The CATALOG command.

620-640	The BackGround COLOR command.
650	The PEN COLOR command.
660	This line lets you reenter LINES, DOTS, BOX, or FRAME mode after a menu selection.
670-870	This subroutine draws the color menu for BackGround COLOR, PEN COLOR, and SEPARATE, and lets you select a color with the pen.
880	Color box low-resolution draw.
890-1120	The WINDOW command.
1130-1140	This subroutine resets the Tablet WINDOW information after a color menu selection.
1150-1290	The VIEWPORT command.
1300	This subroutine causes a 1.15 second delay. It is used to pause while the Apple is displaying a message on the screen.
1310-1320	This subroutine waits until either a key is pressed on the keyboard or the pen is pressed down, and then returns.
1330-1340	This subroutine draws or undraws the four corner marks for a VIEWPORT.
1350-1360	This subroutine draws a single VIEWPORT corner mark.
1380-1390	The REDUCER command.
1400-1440	Turns on the REDUCER.
1460-1560	The DELTA command.
1580-1660	LINES mode.
1680-1720	DOTS mode.
1740-1820	FRAME mode.
1840-1930	BOX mode.
1940-1950	This subroutine is called whenever you specify a point outside of the VIEWPORT for any of the four modes mentioned above.
1970-1980	The AREA command. This section is the drawing loop.

1990-2030	The calculation section for AREA.
2070-2080	The DISTANCE command. This section is the drawing loop.
2090-2120	The calculation section for DISTANCE.
2160-2290	The CALIBRATE command.
2300	A subroutine to blank out the four lines at the bottom of Page 2 of Text mode.
2310	A subroutine to display "BEGINNING POINT?" at the bottom of Page 2 of Text mode and wait for the pen to be pressed down.
2320	A subroutine to display "ENDING POINT?" at the bottom of Page 2 of Text mode and wait for the pen to be pressed down.
2330-2480	The SLIDE command.
2490-2580	The SEPARATE command.
2590-2600	This subroutine resets the Tablet firmware.
2610-2730	Error handling subroutines.

THE MAIN LOOP

The main programming loop of the TABLET-CODE program occurs in lines 170 through 290. Lines 170 and 180 are the main loop for the DRAW mode. The DRAWING is done by the CALL EP% in line 170. This activates the QUICK-DRAW subroutine, which reads the Tablet and draws on the screen. As it draws on the screen, it also places the coordinates for each point plotted into the two arrays called X% and Y%. It uses the variable N% as an index into these arrays, and uses the value of the variable D% as its DELTA value (see the section on the QUICK-DRAW subroutine). The QUICK-DRAW subroutine returns to the Applesoft program when one of four events occur:

- 1) A key on the keyboard was pressed.
- 2) The pen was pressed down outside the working area of the Tablet.
- 3) The pen was lifted after being pressed down.
- 4) One of the arrays X% or Y% was filled up.

When QUICK-DRAW terminates, the termination condition code (a number from 0 to 3) is stored in location 700, and the Applesoft program

places this value into the variable CD. Depending upon the termination condition, the program either reinitializes the DRAW mode, or branches to line 190 (to handle a keypress) or line 200 (to get a menu selection).

If the pen was pressed outside the working area, then lines 220 through 240 sense the pen's position again in relation to the menu. Two numbers are returned: X holds a number from 0 to 21 which corresponds to one of 22 horizontal positions across the menu, and Y holds a number (0 or 1) which corresponds to one of two menu rows.

The ON Y+1 GOTO 280,290 statement in line 250 selects between the top and bottom menu rows. The ON X+1 GOTO 140... in line 280 selects among the 22 menu items in the top row.

MENU ITEMS

Each menu item corresponds to a block of code (not a subroutine) in the program. After the code for each item performs its function, it executes either a GOTO 170 (to reinstate DRAW mode) or a GOTO 660 (to reenter the current mode). A list of the variables which are used in the program and a description of their function appears in Appendix B. Subroutines which are called by parts of the program also appear in that Appendix.

The four other modes (LINES, DOTS, BOX, and FRAME) are actually independent menu items which operate differently from DRAW mode. For an example, look at the code for the FRAME mode, in lines 1740 through 1820. Line 1740 resets the Tablet to accept points from the current WINDOW area, with a sparkling crosshairs cursor displayed. It also sets the variable CM (for Current Mode) to 3, for FRAME mode. Line 1750 loops until the pen is pressed onto the Tablet surface, and returns the coordinates of the point in X and Y. These coordinates can be used directly to plot onto the high-resolution screen.

Line 1760 checks to see if the point is inside the current VIEWPORT. If it is not, the subroutine at line 1940 is called. This subroutine checks that the point is in the menu area. If it is, it sets the variable RT to 1; if not, it sets RT to 0 and displays the message

POINT OUTSIDE VIEWPORT. RESPECIFY.

Back in line 1760, if a menu item was selected, the code causes a jump to line 220 (menu selection). If the point was outside the viewport, the mode is restarted by a GOTO 1750.

If the point was inside the VIEWPORT, then line 1780 plots the point on the screen and saves its coordinates in the variables TX and TY. Lines 1790 through 1810 go through the whole get-a-point procedure again, and get another point in X and Y. Finally, line 1820 actually draws the FRAME, and jumps back to line 1750 to get another two points.

EXTENDING THE MENU

If you can write programs for the Apple, then you can tailor the TABLET-CODE APPLESOFT program to your own liking. You can add extra functions and remove or modify existing functions. You can define your own menu selections, or you can even start from scratch and write your own programs to use the Graphics Tablet to do just about anything.



The TABLET-CODE APPLESOFT program uses almost all of the memory space allotted for it. If you wish to add a function to the code, you must delete some of the program to make room for it. If the program grows any larger, it will not work.

EXAMPLE: INSTANT COLOR MENU

If you're tired of having to wait for the Apple to redraw the color menu when all you want to do is change the PEN COLOR from white to black, here's a modification you can make to get instant changes in PEN COLOR. To do it, you'll have to sacrifice one of the Tablet's other functions. Since this will mean changing your TABLET-CODE program, it's important that you not work on the original backup diskette.

Type

NEW

LOAD TABLET-CODE APPLESOFT

to load the unmodified program. To make room for your new code, delete a function you don't use much (some good candidates for oblivion are SLIDE, SEPARATE, AREA, DISTANCE, and CALIBRATE — they are special-purpose functions and their removal won't affect the rest of the program). Let's delete the SLIDE function. Type

DEL 2330,2480

Now you've got about 250 more bytes to use for your program. To replace the SLIDE command with a null command, enter the line

2330 GOSUB 1130: GOTO 170

to reset the Tablet and return to DRAW mode if you try to select the now-defunct SLIDE function.

What we'll do is let you choose a new PEN COLOR simply by poking one of the first eight squares in the second row of the menu. Label these squares on your menu with a pencil or pen:



Now for the programming part. In lines 250 through 280, the variables X and Y hold the coordinates of the menu box which was just selected. Y is set to 0 for the top row and 1 for the bottom, and X holds a number between 0 and 21 corresponding to the 22 boxes in each row. So, if you poke the pen to one of the eight boxes of the new color menu, Y will be set to 1 and X will be a number from 0 to 7, depending upon which of the 8 squares you poked. It just so happens that the eight colors in Applesoft's high-resolution graphics mode are numbered 0 through 7, and they are in the exact same order as the color names you wrote on the second row of the menu! Isn't that lucky? But, first we've got to handle Y. In line 250, if Y is equal to 1, the program goes to line 290, the null function. Let's replace that line with

```
290 IF X<0 OR X>7 THEN GOSUB 1130: GOTO 170
```

Now the null function is executed only if the pen was pressed in the second row and not in the first eight boxes. If the pen was pressed in one of the first eight boxes, the next line will be executed. So let's make the next line:

```
295 PC=X: HCOLOR=PC: GOSUB 1130: GOTO 660
```

This line sets the Pen Color to the value of X (remember, 0 through 7?) and sets the high-resolution COLOR to that value. Then it resets the Tablet and goes to line 660, which reenters the current mode.

And that's it! Now before you RUN it save this version onto a copy of the GRAPHICS TABLET SOFTWARE diskette. You might want to add a REM statement at the beginning, describing the change and date. When you SAVE the program, you must save it under the name TABLET-CODE APPLESOFT or you won't be able to use it. Since the version of TABLET-CODE APPLESOFT that is on your diskette is LOCKED, you will have to UNLOCK it before you can save the new version.

To use your newly modified program, type

```
RUN HELLO
```

press **ESC**, select **G**, and press **RETURN**. When the program is running, you can instantly change colors in midstream, from any mode, by pressing the pen to the box for that color.

EXAMPLE: CIRCLE MODE

Here's another change which is a little more extensive than the previous one. Here are two extra modes, counterparts to BOX and FRAME, which draw open and filled circles rather than rectangles. You'll specify the location and size of a circle by poking two points on the Tablet: the first one will be the center of the circle and the second will be on the perimeter. Since this will require some extra room, (if you haven't done it already) delete a function such as SLIDE. In fact, you can delete both SLIDE and SEPARATE and use their menu squares to set CIRCLE and DISC mode. On a copy (not either of your original copies) of the GRAPHICS TABLET SOFTWARE diskette, type

```
LOAD TABLET-CODE APPLESOFT
DEL 2330,2580
```

Now they're gone. Since CIRCLE and DISC need two points, just like BOX and FRAME, we can follow the example of those modes. Type

```
2330 REM ** CIRCLE MODE **
2340 GOSUB 1130: PRINT D$;"IN#";SL: CM=5
2350 RT=2: INPUT X,Y,Z: IF Z<>2 THEN POKE -16368,0: GOTO 2350
2360 IF X<X3 OR X>X4 OR Y<Y3 OR Y>Y4 THEN GOSUB 1940: IF
      RT=1 THEN 220
2370 IF RT=0 THEN 2350
2380 HPLOT X,Y: TX=X: TY=Y
2390 RT=2: INPUT X,Y,Z: IF Z<>2 THEN POKE -16368,0: GOTO 2390
2400 IF X<X3 OR X>X4 OR Y<Y3 OR Y>Y4 THEN GOSUB 1940: IF RT=1 THEN 220
2410 IF RT=0 THEN 2390
```

At this point, the coordinates of the center of the circle are in TX and TY, and the coordinates of a point on the perimeter are in X and Y. Let's find the radius of the circle now:

```
2420 R=SQR((X-TX)^2+(Y-TY)^2)
```


With a little trigonometry, we know that the horizontal and vertical distance from the center of a circle to any point on the perimeter is given by the simple formulae

```
2440 DX=R*SIN(TH): DY=R*COS(TH): X=TX: Y=TY
```

where R is the radius (derived in line 2420) and TH is an angle from 0 to 2π . Furthermore, we know that this formula gives us not one, but eight points on the circle:

X+DX,Y+DY	X+DX,Y-DY	X-DX,Y+DY	X-DX,Y-DY
X+DY,Y+DX	X+DY,Y-DX	X-DY,Y+DX	X-DY,Y-DX

as TH ranges from 0 to $\pi/4$ where X,Y is the center of the circle. So, let's add a loop and the lines to plot the points on the perimeter.

```
2430 FOR TH=0 TO .7854 STEP 1/R
2450 HPOINT X+DX,Y+DY: HPOINT X+DX,Y-DY: HPOINT X-DX,Y+DY:
      HPOINT X-DX,Y-DY
2460 HPOINT X+DY,Y+DX: HPOINT X+DY,Y-DX: HPOINT X-DY,Y+DX:
      HPOINT X-DY,Y-DX
2470 NEXT TH: GOTO 2350
```

Now to finish it all up, change the lines

```
660 ON CM+1 GOTO 170,1580,1680,1740,1840,2330
1380 RD=RD+1: IF RD>1 THEN RD=0: GOSUB 1130: GOTO 660
1390 GOSUB 1400: GOTO 660
```

These changes let you go back to CIRCLE mode automatically after making a menu selection.

Now UNLOCK the old version of TABLET-CODE APPLESOFT that is on your diskette, (the one on which you're putting your own versions) and then SAVE this new version on your diskette. RUN HELLO and start using the GRAPHICS TABLET SOFTWARE. When you want to draw an open circle, press the pen to the square marked SLIDE. Indicate one point for the center of the circle, and another for a point on the perimeter. The circle will be drawn to specification, and you'll remain in CIRCLE mode until you choose another.

Be forewarned that if you make a CIRCLE which is too large for the screen, then you'll get an error. Just press **ESC** to get back to DRAW mode. If you don't like this "feature", the following lines will fix the problem:

```
2425 ON ERR GOTO 2480
2470 NEXT TH: ON ERR GOTO 2650
2475 GOTO 2340
2480 PRINT D$;"PR#0": GOSUB 2300: PRINT D$;"PR#";SL: PRINT "M2":
      VTAB 23: HTAB 12: POKE 41, PEEK(41)+4: PRINT "CIRCLE OFF SCREEN.
      RESPECIFY."
2485 GOSUB 1300: PRINT D$;"PR#";SL: PRINT "N,H2": ONERR GOTO 2650
2490 GOTO 2340
```

Note that you can still make circles which go out of the VIEWPORT. There's no easy way to prevent this.

EXAMPLE: DISC MODE

The DISC mode is just the same as CIRCLE mode, except that instead of plotting individual points on the perimeter, you'll have to draw lines across the diameter to fill in the circle. Because they have so much code in common, you can make DISC use much of the code from CIRCLE. Here are the changes to CIRCLE to make it do DISCs, too:

```
2340 CM=5: GOTO 2348
2342 REM ** DISC MODE **
2344 CM=6
2348 GOSUB 1130: PRINT D$;"IN#";SL
```

```
2445 IF CM=6 THEN 2464
2462 GOTO 2470
2464 HPOINT X+DX,Y+DY TO X-DX,Y-DY: HPOINT X+DX,Y-DY TO X-DX,Y+DY
2466 HPOINT X+DY,Y+DX TO X-DY,Y-DX: HPOINT X+DY,Y-DX TO X-DY,Y+DX
```

To change the menu vector table so that the SLIDE square will activate CIRCLE and the SEPARATE square will activate DISC, change line 280 to read:

```
280 ON X+1 GOTO 140,300,890,620,1460,550,1150,2160,1380,650,290,1580,
      1680,1740,1840,570,330,420,2342,2330,1970,2070
```

and make this other change:

```
660 ON CM+1 GOTO 170,1580,1680,1740,1840,2330,2342
```

This next line lets you reenter both CIRCLE and DISC modes after you make a menu selection (such as PEN COLOR). Finally, if you added the error handling subroutine described above, then change it so:

```
2390 ON CM-4 GOTO 2330,2342
```

Now again SAVE your modified program under the name TABLET-CODE APPLESOFT on the diskette you're using for your experimentation.

THE FIRMWARE

On the Graphics Tablet Interface card is a 2K byte ROM (Read-Only Memory). This ROM contains all the subroutines which read and interpret the signals from the Graphics Tablet. These subroutines can be used easily from any BASIC program.

The Graphics Tablet Firmware performs many functions. Its main purpose is to read the position of the Tablet's pen on the surface of the Tablet, and return that position in a numerical form to a BASIC program. But, it also does much more:

- It lets you supply horizontal and vertical offset information. It will use this offset information in calculating the pen position. This lets you place the origin (where the X and Y coordinates are both 0) anywhere on the Tablet surface. The offsets can be integers from -32767 to +32767.
- It allows you to give a scaling divisor, from 1 to 32767. You can tell the Tablet firmware to divide all coordinates by this number before it passes them to your BASIC program. This lets you calibrate the Tablet units (200 to the inch) to your own scale.
- It allows you to select among ten different modes on the Apple's screen. Text, low-, and high-resolution graphics (on either Page 1 or Page 2) can be selected, and you can mix text with graphics.
- It automatically displays a flashing cursor on the Apple's screen, given the proper scaling and offset information. Cursors are available or may be suppressed in all screen modes.
- You can tell the Tablet to suppress all output from your Apple.
- You can read not only the position of the pen, but also whether it is within readable distance, whether the pen is up or pressed down, detect pen-down and pen-up movements, and read the keyboard to see if a key has been pressed.

Your programs can communicate to the Firmware subroutines by using the BASIC commands `PR# s` and `IN# s`, where `s` is the number of the peripheral connector slot in the Apple which holds the Tablet Interface card. (The `PR#` command indicates that all subsequent output is to be directed to the Firmware subroutines in a certain slot, and the `IN#` command indicates that all subsequent input is to be taken from the Firmware subroutines in the given slot.) When your program wants to stop talking to the Firmware subroutines, it can issue a `PR#0` or `IN#0` command to direct output or accept input from the normal screen and keyboard.

To avoid alienating DOS (the Disk Operating System), you'll have to issue the `PR#` and `IN#` commands in the form of DOS commands. See the section on Selecting I/O Devices in your DOS manual.

TABLET CONTROL

To send control information to the Tablet, just execute a `PR# s` command from BASIC and PRINT a string of Tablet Control commands. The Control commands will not be displayed on the Apple's screen; they will be used by the Tablet alone.

There are seventeen Tablet Control commands. These commands take the form of a letter or a word, sometimes followed by a number. Commands are executed in a sequential order as given to the tablet by the user.

Commas are used as delimiters between commands and must not begin or end the command string. Spaces are ignored. A null string issued to the tablet is invalid. Only the first alphabetic character of a command is meaningful; the other alphabetic characters are ignored and may be omitted.

Following is a list of Tablet Control commands. The letter "n" that follows some of these commands represents an integer. The Tablet Control commands are:

TEXT n	Sets the Apple's screen to show text mode. n determines which page of Text to display and can be either 1 or 2.
HGR n	Sets the Apple's screen to show full-screen high-resolution graphics mode. n determines which page of graphics to display and can be either 1 or 2.
LGR n	Sets the Apple's screen to show full-screen low-resolution graphics mode. n determines which page of Graphics to display and can be either 1 or 2.
MIXHGR n	Sets the Apple's screen to show high-resolution graphics mode, mixed with four lines of text at the bottom. n determines which page of text and graphics to display and can be either 1 or 2.
GR n	Sets the Apple's screen to show low-resolution graphics mode, mixed with four lines of text at the bottom. n determines which page of text and graphics to display and can be either 1 or 2.

SCALE n Sets the Tablet scaling divisor to n. All coordinates generated by the Graphics Tablet will be divided by n before they are given to your program. The range for n is 1 to 32767. If you give the Tablet a negative scaling divisor, it will ignore the minus sign and use the positive number. A scale factor of 0 is undefined and will not work.

XOFF n Sets the Tablet horizontal (X) offset to n. If the R command is enabled, all horizontal coordinates will have n added to them before they are given to your BASIC program. The offset value, n, may range from -32767 to +32767.

YOFF n Sets the Tablet vertical (Y) offset to n. If the R command is enabled, all vertical coordinates will have n added to them before they are given to your BASIC program (see R command below). The offset value, n, may range from -32767 to +32767.

F Ignore scaling divisor. None of the coordinates generated by the Tablet will be scaled or offset. The cursor, however, will not ignore scale and offset information.

R Use scaling divisor. All coordinates generated by the Tablet will be divided by the scaling divisor before they are given to your BASIC program. Then offset values will be added.

AFTER If the R command is used, the offsets will be added after the scaling operation. This command is turned off (the BEFORE command is reinstated) with any subsequent command which sets a screen mode, including the DEFAULT command.

BEFORE If the R command is used, the offsets will be added before the scaling operation.

NOPRINT Disables all on-screen printing. After a NOPRINT command is sent to the Tablet, no new output generated by the Apple will be displayed on the screen. NOPRINT mode is turned off by any other Tablet Control command string or by a BASIC PR#0 command.

CURSOROFF Turns off the sparkling cursor. The cursor will remain off until any other Tablet Control command is sent which sets a screen mode (the DEFAULT command also turns the cursor on).

P Sets Stream mode. If the pen is within the proximity of the Tablet, the Tablet Firmware will send coordinates each time it is polled, regardless of the pen position or status. This command is turned off (the Q command

is reinstated) with any subsequent command which sets a screen mode, including the DEFAULT command.

Q

Resets Stream mode. The Tablet firmware will send coordinates only when it is polled, and the pen is pressed down.

DEFAULT

Sets the standard (default) Tablet mode:

- HGR 2 screen mode
- SCALE=16
- XOFF=1536
- YOFF=1536
- F (no scaling or offsets)
- BEFORE
- Q (stream mode off)
- Cursor on
- Printing on

For example, if the Tablet Interface card is in slot number 5 and you want the Tablet to set low-resolution graphics mode, with four lines of Text at the bottom, use a scaling divisor of 16, and use the offsets stored in the variables X0 and Y0, and apply them before the scaling, you would use this Tablet Control command:

```
PR#5: PRINT "GR 1, SCALE=16, XOFF=";X0;"", YOFF=";Y0;"", BEFORE":PR#0
```

Of course, you could shorten it by eliminating extraneous spaces and using only the first letter of each Control command name:

```
PR#5: PRINT "G1,S16,X";X0;"",Y";Y0;"",B":PR#0
```

Since you are using Apple DOS, you must use DOS's PR# command in order to use both DOS and the Tablet. If you've got the slot number of the interface card in the variable SL, then the same Tablet Control command would read:

```
PRINT D$;"PR#";SL:PRINT "G1,S16,X";X0;"",Y";Y0;"",B":PRINT D$;"PR#0"
```

It's important not to add a semicolon (;) or comma (,) at the end of the Tablet Control PRINT string. The Tablet will execute the command only when it receives a RETURN character. A semicolon or a comma after the string will suppress the RETURN; therefore, the Tablet will never carry out your commands because it won't hear the end of them.

Any illegal construct in a Control command, including numbers out of range, will cause the screen to return to text mode and the message


*** TABLET SYNTAX ERROR

to appear on the screen.

ACCEPTING INPUT


Once you've told the Tablet what kinds of numbers you expect to be getting from it, you can use the BASIC statements `IN#` and `INPUT` to get the pen coordinates and status information from the Tablet.

The Tablet sends its coordinate and status information in this format:



The X- and Y-position coordinates must be integers from -9999 to +9999. The user is responsible for adjusting the X and Y offsets and the scale value so that values returned by the tablet fall within this range. It is possible to exceed this range, in which case an Applesoft error will be generated. These coordinates indicate the position of the pen on the Tablet. If the R command is in effect, these coordinates indicate the position of the pen plus the offset and divided by the scaler.

The sign and status digits indicate the status of the pen and keyboard. If the sign is negative, then a key has been pressed. The two digits have separate meanings:



So let's write a program to read the Tablet and print out the coordinates, without scaling or offsets, on the Text screen. Let's assume that the slot number of the Interface card is stored in the variable `SL`.

```
100 PR#SL: PRINT "T1, F, C, P": PR#0: REM INITIALIZE TABLET
110 IN#SL: INPUT X,Y,Z: IN#0: REM READ TABLET
120 PRINT "THE X-POSITION IS ";X;"", "THE Y-POSITION IS ";Y;"."
130 IF Z<0 THEN PRINT "THE KEYBOARD HAS BEEN PRESSED."
140 IF ABS(Z)>=10 THEN PRINT "THE PEN IS OFF-SCALE."
150 Z=ABS(Z): IF Z>=10 THEN Z=Z-10: REM GET ONES DIGIT
160 IF Z=0 THEN PRINT "PEN IS DOWN."
170 IF Z=1 THEN PRINT "PEN WAS JUST LIFTED."
180 IF Z=2 THEN PRINT "PEN WAS JUST PRESSED DOWN."
190 PRINT
200 POKE -16368,0: GOTO 110:REM CLEAR KEYBOARD STROBE, REPEAT
```

This program will work in either Applesoft BASIC or Apple Integer BASIC.

Line 100 sets the Tablet Control parameters. Line 110 gets input from the tablet, and the remaining lines interpret the values and print an explication. Line 200 clears the keyboard strobe (if a key was pressed) and loops back to get another set of values.

This program works in Stream mode, that is, it is continually getting input from the Tablet regardless of the position of the pen. If you change the Tablet Control command string to read

```
100 PR#SL: PRINT "T1, F, C, Q": PR#0
```

then the coordinates will be returned only when the pen is pressed down.

Let's write a subroutine in BASIC which is to return the X and Y coordinates of the next pen press, or return with the variable `KY` set to 1 if the user presses the `RETURN` key on the keyboard. Let's assume that the Tablet has been initialized in the main program (see previous example, line 100).

```
200 REM ** SUBROUTINE TO GET A PEN PRESS OR KEYPRESS **
210 KY=0: REM FLAG FOR KEYPRESS
220 IN#SL: INPUT X,Y,Z: IN#0
230 IF Z=2 THEN RETURN: REM PEN DOWN
240 IF Z>0 THEN 280: REM NO KEYPRESS
250 K=PEEK(-16384): REM GET KEYPRESS
260 IF K<>13 THEN 280: REM IS IT A RETURN?
270 KY=1: RETURN: REM YES, IT IS.
280 POKE -16368, 0: GOTO 220: REM NO, KEEP LOOKING.
```

FROM MACHINE LANGUAGE

You can perform the same Tablet operations from within a machine language program that you can from a BASIC program. Even though machine language programs are a little more difficult to write, they will run faster and use less memory than their BASIC counterparts.

Your machine language programs will invoke the various functions of the Graphics Tablet firmware by performing JSR (Jump to SubRoutine) operations to subroutines inside the Tablet's ROM, rather than using the `PR#` and `IN#` statements in BASIC. Your programs will pass information to the Tablet by storing it in fixed locations in memory, and will receive information from the Tablet by storing it in other fixed locations, instead of using `PRINT` and `INPUT` statements as a BASIC program would.

Since the Tablet firmware operates in the same manner regardless of whether it is being driven by a BASIC or a machine language program, this section will explain only the specifics of machine language operation of the Tablet. For a description of the modes and parameters which the Tablet firmware recognizes, please see the previous section.

The Tablet firmware is absolutely located in the Apple's memory at locations \$C800 through \$CFFF. This is a 2K memory space which is shared by all peripherals, and can be used by any one peripheral card at any time. In order to let the Graphics Tablet card take possession of this common ROM space, you must reference two special memory locations. First, you must reference location \$CFFF. This will turn off all interface cards which may be using the common ROM space. Then you must make at least one reference to any address in the range \$Cn00 through \$CnFF, where n is the number (from 0 to 7) of the peripheral connector slot which holds the Graphics Tablet interface card. Once this is done, the Tablet's ROM will be placed into its proper memory range and you can reference its subroutines normally.

After you activate the ROM, you should store the slot number of the Graphics Tablet (in the format \$Cn) in location \$07F8. This lets other Apple programs know that the Tablet is active and in use.

Subroutine POINT (location \$Cn02) lets you read a single point from the Tablet. The coordinates of the point, along with the pen status information, will be stored as a 15-character long ASCII string, beginning at location \$0200 and ending with a RETURN code at location \$020E. The format of this string is described in the previous section called ACCEPTING INPUT.

The subroutine DEFAULT (location \$CE90) sets all the Graphics Tablet parameters and modes to their default values. It operates the same as the Tablet control command DEFAULT.

The subroutine MREAD (location \$CBB9) allows you to read the pen position and status quickly, and get the result in binary (rather than ASCII, as POINT does). It returns the X and Y coordinates in the following locations:

XFFL	\$0281	Lower byte of X-coordinate
XFFH	\$0282	Upper byte of X-coordinate
YFFL	\$0283	Lower byte of Y-coordinate
YFFH	\$0284	Upper byte of Y-coordinate
TEM	\$0280	Pen status

The X and Y coordinates are numbers from -32767 to +32767. Notice that this is a greater range than the coordinates passed by POINT. The numbers are in two's complement form, and the high bit of the upper byte of each coordinate determines the sign of that coordinate. The pen status byte is interpreted much the same as it is for POINT: the lower 4 bits represent the pen status and the upper bit represents the keyboard status.

The SCALE subroutine (location \$CB70) is normally called immediately after MREAD. It performs a scaling and offset operation on the X and Y coordinates generated by MREAD and places the results in these four locations:

TEMXL	\$0285	Lower byte of scaled X-coordinate
TEMXH	\$0286	Upper byte of scaled X-coordinate
TEMYL	\$0287	Lower byte of scaled Y-coordinate
TEMYH	\$0288	Upper byte of scaled Y-coordinate

These values are also in two's complement form and range from -32767 to +32767.

The CURSOROUT subroutine (location \$C8F0) is normally called immediately after an MREAD. CURSOROUT calls SCALE and uses the scaled results to place a cursor on the Apple's screen. The cursor is placed by an exclusive-OR operation, so another call to CURSOROUT using the same coordinates will remove the cursor and leave the screen unchanged.



The CURSOROUT subroutine places the cursor on the screen which the Tablet was told to display. It is not necessarily the screen which the Apple is currently displaying. If you manually change the screen setting after calling DEFAULT or setting the Tablet PAGE parameter (see below), then the Apple may be displaying a video mode which is different from the one in which the Tablet is displaying a cursor.

You can pass parameters to the Tablet firmware by storing the proper values in special memory locations. Here are the locations used by the Tablet firmware.

The MSLOT parameter (location \$07F8) contains the number of the slot (in the format \$Cn) into which the Graphics Tablet Interface card is plugged.

The PAGE parameter (location \$03B8+MSLOT) holds the code for the current video mode:

\$20	high-resolution page 1	\$40	high-resolution page 2
\$01	low-resolution page 1	\$02	low-resolution page 2
\$21	Mixed high-resolution page 1	\$42	Mixed high-resolution page 2
\$05	Mixed low-resolution page 1	\$0A	Mixed low-resolution page 2
\$04	Text page 1	\$08	Text page 2

\$00 No cursor

If you set the high bit of the PAGE byte, then the scale and offset factors will be applied.

The MPAGE parameter (location \$0438+MSLOT) holds some of the same information as the PAGE parameter. The lower six bits of MPAGE are derived from the lower six bits of PAGE exclusive-ORed with the constant \$25. The upper two bits represent the A, B, P, and Q parameters:

Bit 7 ON: Stream mode on Bit 7 OFF: Stream mode off
 Bit 6 ON: Offset after scale Bit 6 OFF: Offset before scale

The scale and offset parameters are stored in the following locations:

SCALL	\$04B8+MSLOT	Lower byte of scaling divisor
SCALH	\$0538+MSLOT	Upper byte of scaling divisor
OFFXL	\$05B8+MSLOT	Lower byte of X-offset
OFFXH	\$0638+MSLOT	Upper byte of X-offset
OFFYL	\$06B8+MSLOT	Lower byte of Y-offset
OFFYH	\$0738+MSLOT	Upper byte of Y-offset

The scaling divisor is a binary integer from 0 to 32767. The offsets are two's complement binary numbers from -32767 to +32767.

QUICK DRAW

The QUICK-DRAW program is a machine language subroutine which acts as an intermediary between the Tablet Firmware and an Applesoft program. Since an Applesoft program using HPLLOT cannot draw on the High-Resolution screen fast enough to keep up with the movements of the pen across the Tablet, the QUICK-DRAW subroutine talks directly to the Tablet and plots the points on the high-resolution screen. QUICK-DRAW also makes the points plotted available to the Applesoft program.

QUICK-DRAW must run on an Apple with at least 16K bytes of memory, the Applesoft II BASIC programming language in ROM or the Language System, and a Graphics Tablet Interface card. The Graphics Tablet Firmware must be activated by an IN# command before QUICK-DRAW can be called.

The QUICK-DRAW subroutines are hidden inside an Applesoft program. When you RUN QUICK-DRAW, the Applesoft program will store the subroutines in the memory range \$C00-\$FFF (decimal 3072-4095). The entry point for the subroutines will be placed in memory locations \$2F0 and \$2F1 (decimal 752 and 753). Your Applesoft program, which you will RUN right after you RUN QUICK-DRAW, can PEEK at these locations and get the entry point by executing this line:

```
100 EP%=PEEK(752)+256*PEEK(753)
```

The QUICK-DRAW subroutine deals directly with four Applesoft variables. When you CALL the QUICK-DRAW subroutines, it takes the coordinates of the points it receives from the Tablet and places them in the two Applesoft arrays X% and Y%. It uses the Applesoft variable

N% as an index into these arrays. The subroutine also uses the contents of the variable D% as a DELTA value. It is the QUICK-DRAW subroutine which controls the DELTA and Audio Feedback features of the Tablet software.

You must dimension the arrays X% and Y% prior to calling QUICK-DRAW. Also, you must assign a non-zero value to D%. The D% value is used as described in the DELTA function in Chapter 2; if the value of D% is negative, then the Audio Feedback feature will be turned off.

The QUICK-DRAW subroutine will return control to the Applesoft program under any of four conditions:

- 1) A key on the keyboard was pressed before the pen was pressed down.
- 2) The pen was moved to a place on the Tablet which does not correspond to a position in the current VIEWPORT.
- 3) The pen was lifted after being pressed down inside the VIEWPORT.
- 4) There is no more room in the arrays X% and Y% to store coordinate values.

When one of these conditions arises, the code for that termination condition will be stored in location \$2BC (decimal 700) and control will be returned to the Applesoft program.

You can define a VIEWPORT for the QUICK-DRAW subroutines by storing:

- the coordinate of the left edge in locations 3089 and 3090;
- the coordinate of the right edge plus one in locations 3091 and 3092;
- the coordinate of the top edge in location 3093; and
- the coordinate of the bottom edge plus one in location 3094.

See lines 1100 and 1120 of the TABLET-CODE APPLESOFT program for an example of how to pass VIEWPORT coordinates to the QUICK-DRAW subroutine.

BY ANY OTHER NAME

You can change the names of the variables which QUICK-DRAW will use by executing a special CALL to QUICK-DRAW. Normally, QUICK-DRAW uses these variable names:

D% for the DELTA value	N% for the index to the arrays
X% for the X-coordinate array	Y% for the Y-coordinate array

You can change these four variable names to be whatever you like. However, they must always be of the integer variable type (denoted by the percent sign (%)) following the name). To rename the variables, use this format:

```
220 CALL EP%,DELTA%,NUMBER%,XVAL%,YVAL%
```

Since Applesoft only recognizes the first two letters of a variable name, this will make QUICK-DRAW use the variable DE% for its DELTA, NU% for N%, XV% for X%, and YV% for Y%. If you want to change only one of the names, just leave the others out, but keep the proper number of commas:

```
230 CALL EP%,,IN%,,
```

will make QUICK-DRAW use the variable IN% instead of N%. You must keep the variable names in the order D%,N%,X%,Y%.

APPENDIX A USE AND CARE

68	Care of the Menu Overlay
68	Care of the Tablet
69	Care of the Interface
69	If It Doesn't Work

CARE OF THE MENU OVERLAY

You can write on the clear plastic menu overlay with most anything: soft (Number 2) pencils, felt-tip pens, permanent markers, crayons, and the like. However, ball-point pens tend not to write well on the overlay, and colored or hard lead pencils also have problems.

You can wipe the overlay clean of most marks or doodles you have drawn using a soft cloth and a mild soap-and-water solution. Most marks from felt-tip or "permanent" markers can be removed easily. Some markers, however, will leave truly permanent scars on the overlay; it's a good idea to test any marker on an inconspicuous corner of the overlay before you use it to draw all over your Tablet. To be safe, use felt-tip markers designed for use on acetate or mylar (or for use with overhead projectors). These will give you visible, non-smearing colors, but the marks will wipe off without a trace.

If you are getting inexplicable "glitches" on your screen you probably have a static problem. The solution is simple: Wipe the overlay with the static cloth that came with your Graphics Tablet. A treatment with the cloth should remove any excess static from the overlay.

CARE OF THE TABLET

Your Graphics Tablet is constructed of a solid wood base, protected below by a sheet metal baseplate and above by a molded, snap-on plastic cover. If the top cover gets dirty, it can be cleaned with a soft cloth and a mild soap-and-water solution. Don't use any abrasives or strong detergents on the surface or case of the Tablet: they may scratch or damage the plastic. If possible, keep the Tablet covered when you aren't using it.

DON'T leave anything which has a strong magnetic field on or near the Tablet. This will disrupt its natural magnetic orientation and make it malfunction. Keep your diskettes off the Tablet! Its magnetic field may alter or erase the information on them. Don't place disk drives, televisions, electric motors, magnets, or large, heavy metallic objects on top of the Tablet.

Keep the Tablet in a cool, dry place. Don't leave it in direct sunlight or in a car trunk or some other hot, stuffy place. Too much heat will warp its cover.

Be careful with the Tablet when you're moving it from place to place. Don't drop it or jar it. Even though it's pretty solid, it can be seriously damaged by a bad fall.



CARE OF THE INTERFACE

The Interface card is really the most delicate part of the Graphics Tablet. When inserting, removing, or transporting it, be very careful not to bend any of its pins or components. To be safe, always carry it in the box in which it was shipped, nestled in protective foam. Keep it away from strong electrical or magnetic fields, and don't even think of touching it if there's a lot of static electricity in the area.

If you've been inserting and removing the Interface card into the Apple a lot, then it's possible that the metal "fingers" have gotten dirty and are not making good contact with the Apple. In this case, the easiest way to clean the fingers is to just use an ordinary pencil eraser and rub all of the gunk off. If you want to be thorough, use cotton swabs and rubbing alcohol to clean the fingers on the card.

IF IT DOESN'T WORK

If you've exposed your Tablet to bad magnetic influences or it's been bumped and jarred a lot, it may develop "dead spots" on its surface, spots where the pen won't draw. These aren't permanent, they're just a loss of magnetic orientation in certain spots of the Tablet. Take the Tablet to your Apple service center. The service center should have the proper equipment to reorient your errant Tablet and make it work again.



APPENDIX B BACKING UP YOUR DISKETTES

72 With Two Disk Drives
72 With One Disk Drive

WITH TWO DISK DRIVES

If your Apple has two disk drives, you can easily make a copy of either GRAPHICS TABLET SOFTWARE diskette by using the diskette copying program on your Apple SYSTEM MASTER diskette. You will need three diskettes:

- 1) One of the GRAPHICS TABLET SOFTWARE diskettes, enclosed with your Tablet;
- 2) The SYSTEM MASTER diskette, enclosed with your Disk II; and
- 3) A blank, uninitialized diskette. If you like, you can use a preinitialized diskette, but all information on that diskette will be destroyed.

Boot your system using the SYSTEM MASTER diskette (see your DOS manual, or, if you have an Autostart ROM, see your Autostart ROM manual) and type

RUN COPY

After the disk drive stops whirring, place the GRAPHICS TABLET SOFTWARE backup diskette in one drive, and place the blank diskette in the other. The GRAPHICS TABLET SOFTWARE diskette will be the "Original", and the blank diskette will be the "Duplicate". Follow the instructions in the section on using the COPY program in your DOS manual.

Once you've copied the diskette, label the duplicate so you'll know what it is. Then put the original away in a safe place. If you ever lose or destroy the duplicate, then before you start to use the original, make another copy of it. It's also a good idea to periodically make duplicate copies of the diskettes which hold your pictures.

WITH ONE DISK DRIVE

If your Apple has only one disk drive, then you'll have to copy all the programs which comprise the GRAPHICS TABLET SOFTWARE package one by one, loading each program from the original diskette and saving it to the duplicate. It's a lengthy procedure, but well worth your trouble.

Boot your system using the GRAPHICS TABLET SOFTWARE diskette. Press **ESC** to get to the HELLO menu, select **Q** to QUIT, and press **RETURN**. Now remove the diskette and write-protect it by sticking a write-protect tab (a thin but sturdy strip of tape will do) over the

square notch on the left side of the diskette. This is important! It will prevent you from accidentally destroying anything on the original diskette. Now insert a blank, uninitialized diskette in the drive. You can use a preinitialized diskette, but all information on it will be destroyed. Type

INIT HELLO

and press **RETURN**. You're now initializing the diskette with the HELLO program from the GRAPHICS TABLET SOFTWARE diskette. This takes about a minute.

Now switch to the GRAPHICS TABLET SOFTWARE diskette and type
LOAD MENU ALIGNMENT

Now switch to the duplicate diskette and type
SAVE MENU ALIGNMENT

Now switch to the GRAPHICS TABLET SOFTWARE diskette and type
LOAD TABLET-CODE APPLESOFT

Now switch to the duplicate diskette and type
SAVE TABLET-CODE APPLESOFT

Now switch to the GRAPHICS TABLET SOFTWARE diskette and type
LOAD QUICK-DRAW

Now switch to the duplicate diskette and type
SAVE QUICK-DRAW

Now switch to the GRAPHICS TABLET SOFTWARE diskette and type
BLOAD UTILITIES
BLOAD GRAPHICS TABLET LOGO

Now switch to the duplicate diskette and type
BSAVE UTILITIES, A\$6000, L\$330
BSAVE GRAPHICS TABLET LOGO, A\$2000, L\$2000

Now enter this program:

NEW

```
10 D$=CHR$(4)
20 PRINT D$;"OPEN GRAPHICS TABLET SOFTWARE"
30 PRINT D$;"WRITE GRAPHICS TABLET SOFTWARE"
40 PRINT "RUN QUICK DRAW"
50 PRINT "RUN TABLET-CODE APPLESOFT"
60 PRINT D$;"CLOSE GRAPHICS TABLET SOFTWARE"
70 END
```


RUN

This short program creates an EXEC file called GRAPHICS TABLET SOFTWARE, whose function is to set up the Apple to RUN the programs which make the Graphics Tablet work. You need to have this file on every duplicate diskette you make; if you're going to be making many duplicate copies, you might want to SAVE this short program so you don't have to retype it every time you need it.

To SAVE this program, type

SAVE FILEMAKER

Then, whenever you're making a duplicate, put in this diskette and type

LOAD FILEMAKER

put in the duplicate diskette, and type

RUN

That's all there is. Once you've copied the diskette, label the duplicate so you'll know what it is and put it away in a safe place. If you ever lose or destroy the original, then before you start to use the duplicate, make another copy of it.

APPENDIX C

COLOR ANOMALIES

- 76 Unusual Color Effects...
- 77 ...And How to Get Them

UNUSUAL COLOR EFFECTS...

You may have already noticed that a few strange things happen when you try to use certain combinations of colors with the Graphics Tablet. Don't worry: these are normal, predictable phenomena which are caused not by the Tablet, but by the Apple itself.

The Graphics Tablet displays its pictures using the Apple's high-resolution graphics mode. In this mode, there are 53,760 individual dots on the screen, and six colors (black, white, orange, blue, green, and violet). The Apple should therefore need several hundred thousand individual "bits" of information to form a picture. But the Apple uses only 65,536 bits of information (organized into 8,192 eight-bit "bytes") to form the picture! The reason the Apple can display such complex pictures using so little memory is the same reason that sometimes the colors don't appear normal: not all colors can be used in all places on the screen, and each dot is limited in the number of colors it can be.

This specialization of function causes some combinations of colors to work differently than you might expect. There are three different effects which are caused by the limitation in the color scheme. They occur in all drawing modes, but only where one color borders another and the borderline is not horizontal. For example, the color problems could occur on the two vertical sides of a FRAME but not on the top or bottom. Here are the three effects:

- 1) **DASHED LINES.** When you draw black or white lines on a colored field (or vice versa), non-horizontal lines will tend to become dashed and incomplete, and vertical lines may not appear at all.
- 2) **ZEBRA STRIPES.** When you draw colored lines on a colored field, non-horizontal lines don't appear their normal colors, but instead are sometimes black-and-white striped. Vertical lines will appear either completely black or completely white.
- 3) **COLOR FLIP.** When you draw with one color (or black or white) across a colored field, sometimes a seven-dot wide area around a non-horizontal line will change color. This will result in a colored "shadow" appearing around the line.

These effects occur in various combinations, depending upon the colors you use.

...AND HOW TO GET THEM

The table on the next page illustrates seven different combinations of the effects mentioned above, and what color combinations produce which effects. To use the table, find the pen color you're using along the left side of the table. Then look on the top edge of the table and find the color of the area on the screen across which you want to draw. Where the row for the pen color and the column for the field color intersect, there's a number. Find the number in the legend to the table and read about the effect you'll get.

About BLACK1, WHITE1, BLACK2, and WHITE2: Due to the vagaries of the Apple's color generation scheme, there are two instances each of the colors black and white. When you look at the Tablet color menu (see the section on PEN COLOR in Chapter 2), you'll see that there are two black squares and two white squares along with the four colored squares. The black and white in the top row are BLACK1 and WHITE1; the ones in the bottom row are BLACK2 and WHITE2. The reason for the duplication is that the 1's cause fewer problems when used with green and violet than do the 2's, and similarly the 2's go better with blue and orange than do the 1's. When this book refers to black or white, it means BLACK1 or WHITE1.

PEN COLOR

	BLACK1	GREEN	VIOLET	WHITE1	BLACK2	ORANGE	BLUE	WHITE2
BLACK1	0	2	2	1	0	2	2	1
GREEN	2	0	3	2	4	5	6	4
VIOLET	2	3	0	2	4	6	5	4
WHITE1	1	2	2	0	1	2	2	0
BLACK2	0	2	2	1	0	2	2	1
ORANGE	4	5	6	4	0	0	3	2
BLUE	4	6	5	4	2	3	0	2
WHITE2	1	2	2	0	1	2	2	0

FIELD COLOR

Color Effects Table

LEGEND:

- 0: No effect.
- 1: Colors appear as expected; no anomalies.
- 2: DASHED LINES on non-horizontal lines; vertical lines may disappear.
- 3: ZEBRA STRIPING on non-horizontal lines; vertical lines appear solid black or white.
- 4: DASHED LINES with a COLOR FLIP.
- 5: Pure COLOR FLIP: non-horizontal lines appear "chunky" and wider than normal.
- 6: ZEBRA STRIPING with a COLOR FLIP.

APPENDIX D PROGRAM LISTINGS

80	Tablet-Code Applesoft
85	Variable Atlas
87	Subroutines
88	Special Locations
89	ROM Code
108	Quick-Draw
118	Utilities

TABLET-CODE APPLESOFT

```

10 REM * TABLET SOFTWARE. COPYRIGHT APPLE 1979. B. EHLERS *
20 LOPEM 25392
30 D$ = CHR$(4): PRINT D$;"CLOSE GRAPHICS TABLET SOFTWARE"
40 ONERR GOTO 2610
50 D$ = CHR$(4): PRINT D$;"OPEN TAB INFORMATION.D1": PRINT D$;"READ TAB
    INFORMATION": INPUT SL: INPUT XL: INPUT YL: INPUT XH: INPUT YH
60 PRINT: PRINT D$;"CLOSE TAB INFORMATION"
70 ONERR GOTO 2650
80 EP% = PEEK(1753) * 256 + PEEK(1752): M% = 800
90 DIM Y$(M%): X$(M%)
100 PRINT D$;"LOAD UTILITIES.A$4000.D1"
110 XA = XH - XL: YA = YH - YL: LT = INT((XA + YA) / 2): PI = INT(LT / 11)
120 SO = INT(XA / 11 + 5)
130 MD = INT(PI / 2): XM = XL: YM = 2 * MD + YL
140 HGR2: PC = 3: DC = 0: HCOLOR = PC: W = 1: DF = 1
150 X1 = XM * 2: Y1 = YM * 2: X2 = (INT((XH * 2 - X1) / 280 + 5) * 280) / 2
    Z = INT(X2 * 192 / 280): X5 = X1 - X2: Y5 = Y1 - Y2
160 DX = -2: SM = S2: GOSUB 1070: RD = 0
170 CM = 0: N% = 1: CALL EP%: CD = PEEK(700): ON CD + 1 GOTO 190,200,170,1
    70
180 GOTO 170
190 PRINT: PRINT D$;"PR#0": PRINT D$;"D#0": GET A$: IF ASC(A$) < 32
    7 THEN 200
192 TEXT: HOME: VTAB 12: HTAB 13: INPUT "QUIT? (Y OR N) ": A$: IF A$ = "
    Y" THEN HOME: VTAB 12: HTAB 10: PRINT "LOADING HELLO PROGRAM": POKE
    104,8: POKE 103,1: PRINT D$;"RUN HELLO.D1": STOP
194 GOSUB 1130: GOTO 170
200 IF PEEK(640) < 2 THEN 170
210 POKE 640,0
220 XF = XL * 2: YF = YL * 2: SF = SO: GOSUB 2590: REM SENSE
    MENU
230 PRINT: PRINT D$;"IN#": SL
240 INPUT X,Y,Z: IF Y > 1 THEN GOSUB 1130: GOTO 170
250 IF Y < 1 AND Y > 0 THEN PRINT D$;"PR#0": PRINT CHR$(7): PRINT
    : PRINT D$;"PR#": SL: PRINT "N": ON Y + 1 GOTO 280,290
260 GOTO 200
270 TEXT: PR# 0: PRINT "ERROR": STOP
280 ON X + 1 GOTO 140,300,590,620,1460,550,1150,2160,1360,650,290,1580,16
    80,1740,1340,570,330,420,2490,2330,1970,2070
290 GOSUB 1130: GOTO 170
300 IF XT = X3 AND YT = Y3 AND X4 = X8 AND Y4 = Y8 THEN HCOLOR = BC: HPL0T
    0,0: CALL 62454: GOTO 520
310 HCOLOR = BC: HPL0T X3,Y3: FOR T1 = Y3 TO Y4: HPL0T X3,T1 TO X4,T1: NEXT
    HCOLOR = PC: GOSUB 1130: GOTO 170
330 TEXT: PRINT D$;"PR#0": HOME: VTAB 7: HTAB 6: PRINT "PLEASE TYPE THE
    PICTURE NAME": PRINT: HTAB 7: PRINT D$;"IN#0": INPUT "=> ": B$: IF
    B$ = "" THEN GOSUB 1130: GOTO 170
340 VTAB 9: HTAB 37: CALL = 668: HTAB 1: GOSUB 530
345 B$ = "PIC " + B$: ONERR GOTO 400
350 PRINT D$;"LOAD " + B$ + ".A$4000.V0.D": C$
360 S2 = PEEK(16632) * 256 + PEEK(16633): IF S2 < 0 THEN 130
370 X1 = PEEK(16504) * 256 + PEEK(16505): X2 = PEEK(16506) * 256 + PEEK
    (16507): Y1 = PEEK(16508) * 256 + PEEK(16509): Y2 = PEEK(16510) *
    256 + PEEK(16511)
380 ONERR GOTO 2650
390 HOME: GOTO 520
400 B$ = RIGHT$(B$, (LEN(B$) - 4)): ONERR GOTO 2650
410 PRINT D$;"LOAD " + B$ + ".A$4000.V0.D": C$: GOTO 150
420 TEXT: PRINT D$;"PR#0": HOME: VTAB 7: HTAB 3: PRINT "PLEASE TYPE A N
    A ME FOR THIS PICTURE": PRINT: HTAB 7: PRINT D$;"IN#0": INPUT "=> "
    : B$: IF B$ = "" THEN GOSUB 1130: GOTO 170
430 VTAB 9: HTAB 37: CALL = 868: HTAB 1: GOSUB 530
440 GOSUB 1230: HCOLOR = BC: GOSUB 1040: H = INT(X1 / 256): POKE 16504,H:
    POKE 16505,X1 - H * 256: H = INT(X2 / 256): POKE 16506,H: POKE 1650
    7,X2 - H * 256: H = INT(Y1 / 256): POKE 16508,H: POKE 16509,Y1 - H *
    256
450 H = INT(Y2 / 256): POKE 16510,H: POKE 16511,Y2 - H * 256: H = INT(S
    2 / 256): POKE 16632,H: POKE 16633,S2 - H * 256

```

```

460 B$ = "PIC " + B$: ONERR GOTO 490
470 HCOLOR = PC: PRINT D$;"VERIFY ": B$ + ".D": C$: ONERR GOTO 2630
480 VTAB 21: HTAB 1: PRINT "A PICTURE ALREADY EXISTS WITH THAT NAME": PRINT
    : HTAB 12: INPUT "CONTINUE (Y OR N) ": E$: IF E$ < 32 THEN 510
490 ONERR GOTO 2650
500 PRINT D$;"BSAVE " + B$ + ".A$4000.L$1FFB.V0.D": C$
510 HOME: PRINT D$;"PR#": SL: PRINT "H2.N"
520 GOSUB 1090: PRINT D$;"IN#": SL: GOTO 170
530 VTAB 10: CALL = 958: PRINT: HTAB 16: PRINT "DRIVE # ? (DEFAULT="
    DF,")": HTAB 25: INPUT " ": C$: IF C$ < 32 THEN 1 AND C$ < 32 THEN
    C$ = STR$(DF)
540 DF = VAL(C$): VTAB 11: HTAB 24: CALL = 958: PRINT C$: RETURN
550 REM *** SOFT RESET COMMAND ***
560 GOSUB 1330: GOSUB 1090: DX = -2: GOTO 170
570 TEXT: PRINT D$;"PR#0": HOME: PRINT D$;"IN#0": GOSUB 530
580 HOME: HTAB 7: PRINT "PRESS SPACE BAR TO CONTINUE": POKE 34,2
590 PRINT D$;"CATALOG " + C$
600 POKE = 16368,0: GET A$: IF A$ < 32 THEN 600
610 GOSUB 1130: GOTO 170
620 REM *** BACKGROUND AND PEN COLOR ***
630 T1 = PC: GOSUB 670: IF PC = 8 THEN PC = T1: GOSUB 1130: GOTO 660
640 BC = PC: PC = T1: HCOLOR = BC: HPL0T 0,0: CALL 62454: GOTO 520
650 T3 = PC: GOSUB 670: GOSUB 1130: IF PC = 8 THEN PC = T3
660 ON CM + 1 GOTO 170,1580,1680,1740,1840
670 XF = XM * 2: YF = YM * 2: SF = INT((XH - XM) / 140)
680 PRINT D$;"PR#0": TEXT: HOME: PRINT D$;"PR#": SL: PRINT "G1.R,X",XF,"
    Y",YF,"S",SF: GR: HOME: VTAB 22: HTAB 9: PRINT "CONSTRUCTING COLD
    R MENU"
690 COLOR = 5: FOR Z2 = 0 TO 39: HLIN 0,39 AT Z2: NEXT
700 XB = 9: YB = 17: X9 = 2: Y9 = 2: C9 = 0: GOSUB 880: X9 = 11: Y9 = 2: C9 = 12:
    GOSUB 880: X9 = 20: Y9 = 2: C9 = 3: GOSUB 880: X9 = 29: Y9 = 2: C9 = 15: GOSUB
    880
710 X9 = 2: Y9 = 21: C9 = 0: GOSUB 880: X9 = 11: Y9 = 21: C9 = 9: GOSUB 880: X9 =
    20: Y9 = 21: C9 = 5: GOSUB 880: X9 = 29: Y9 = 21: C9 = 15: GOSUB 880
720 HOME: VTAB 22: HTAB 7: PRINT "USE THE PEN TO PICK A COLOR": PRINT:
    PRINT D$;"PR#": SL: PRINT "N"
730 PRINT D$;"IN#": SL: INPUT X,Y,Z: IF Z < 0 THEN PRINT D$;"IN#0": GET A
    : X = 0: Y = 0: PRINT: IF ASC(A$) = 13 THEN PC = 8: RETURN
740 IF Z < 2 THEN 730
750 X = INT(X / 7): Y = INT(Y / 4)
760 IF Y < 2 OR Y > 37 OR Y = 19 OR Y = 20 OR X < 2 OR X > 37 THEN 730
770 PRINT D$;"PR#0": PRINT CHR$(7): IF Y < 1 AND Y < 19 THEN ON INT(
    (X - 2) / 9) + 1 GOTO 790,800,810,820
780 ON INT((X - 2) / 9) + 1 GOTO 830,840,850,860
790 PC = 0: B$ = "BLACK1": GOTO 870
800 PC = 1: B$ = "GREEN": GOTO 870
810 PC = 2: B$ = "VIOLET": GOTO 870
820 PC = 3: B$ = "WHITE1": GOTO 870
830 PC = 4: B$ = "BLACK2": GOTO 870
840 PC = 5: B$ = "ORANGE": GOTO 870
850 PC = 6: B$ = "BLUE": GOTO 870
860 PC = 7: B$ = "WHITE2"
870 HOME: VTAB 22: HTAB (40 - LEN(B$)) / 2: PRINT B$: FOR Z2 = 1 TO 50
    0: NEXT HCOLOR = PC: HOME: RETURN
880 COLOR = C9: FOR Z2 = 1 TO XB: VLIN Y9,Y9 + YB - 1 AT X9: X9 = X9 + 1: NEXT
    : RETURN: REM COLOR BOX LO-RES DRAW
890 REM *** WINDOW COMMAND ***
900 PRINT: PRINT D$;"PR#": SL: PRINT "T1.F.C": PRINT D$;"PR#0"
910 TEXT: HOME: VTAB 9: HTAB 15: PRINT "PRESS PEN AT": PRINT: HTAB 8: INVERSE
920 PRINT D$;"PR#": SL: PRINT "N.C": PRINT D$;"IN#": SL: INPUT X,Y,Z: IF Z <
    0 THEN PRINT D$;"IN#0": GET A$: IF ASC(A$) = 68 THEN GOSUB 1330: HCOLOR =
930 IF Z < 0 THEN IF ASC(A$) = 13 THEN GOSUB 1130: GOTO 170
940 IF Z < 2 THEN 920
950 PRINT D$;"PR#0": IF X < XM + 2 OR Y < YM + 2 THEN VTAB 22: HTAB 4: PRINT
    CHR$(7): "PLEASE STAY WITHIN THE WORK-AREA": FOR Z2 = 1 TO 500: NEXT
    Z2: VTAB 22: CALL = 868: GOTO 920
960 VTAB 11: CALL = 868: HTAB 8: PRINT "UPPER-LEFT AND ": INVERSE: PRINT
    "LOWER-RIGHT": NORMAL
970 PRINT D$;"PR#": SL: PRINT "N.C": INPUT TX,TY,Z: IF Z < 0 THEN PRINT D
    : "IN#0": GET A$: IF ASC(A$) = 68 THEN GOSUB 1330: HCOLOR = BC: GOSUB
    1040: X1 = X5: X2 = X6: Y1 = Y5: Y2 = Y6: GOSUB 1070: GOTO 170
980 IF Z < 0 THEN IF ASC(A$) = 13 THEN GOSUB 1130: GOTO 170
990 IF Z < 2 THEN 970

```



```

1000 PRINT PRINT D$;"PR#0": IF TX > XH * 2 OR TY > YH * 2 THEN VTAB 22
      HTAB 4: PRINT CHR$ (7); "PLEASE STAY WITHIN THE WORK AREA." FOR ZZ
      = 1 TO 500: NEXT ZZ: VTAB 22: CALL - 868: GOTO 970
1010 IF TX < X OR TY < Y THEN VTAB 22: HTAB 5: PRINT CHR$ (7); "PLEASE S
      PECIFY POINTS CORRECTLY!": FOR ZZ = 1 TO 500: NEXT ZZ: GOTO 910
1020 X1 = X: X2 = TX - X1 + 1: Y1 = Y: Y2 = TY - Y1 + 1
1030 GOSUB 1330: HCOLOR= 30: GOSUB 1040: GOSUB 1070: GOTO 170
1040 XT = INT (GF): XB = 279 - XT: YT = INT (HF): YB = 191 - YT IF XT > =
      2 THEN HPLLOT XT - 1, YT TO XT - 1, YB: HPLLOT XT - 2, YT TO XT - 2, YB: HPLLOT
      XB + 1, YT TO XB + 1, YB: HPLLOT XB + 2, YT TO XB + 2, YB
1050 IF YT > = 1 THEN HPLLOT XT, YT - 1 TO XB, YT - 1: HPLLOT XT, YB + 1 TO
      XB, YB + 1
1060 RETURN
1070 T1 = X2 / .280: T2 = Y2 / .192: IF T1 < T2 THEN S2 = T2: IF INT (T2) <
      T2 THEN S2 = INT (T2) + 1
1080 IF T1 > = T2 THEN S2 = T1: IF INT (T1) < T1 THEN S2 = INT (T1) +
      1
1090 RD = 0: GOSUB 1130: HCOLOR= 0: IF BC = 0 OR BC = 4 THEN HCOLOR= 3
1100 GOSUB 1040: HCOLOR= PC: B1 = INT (XT / 256): B2 = XT - B1 * 256: B3 =
      INT ((XB + 1) / 256): B4 = (XB + 1) - B3 * 256: B5 = YT: B6 = YB + 1: X3
      = INT (XT): X4 = INT (XB): Y3 = INT (YT): Y4 = INT (YB)
1110 GOSUB 1330: HCOLOR= PC: WH = 1: W# = "": ONERR GOTO 2630
1120 BX = 3069: POKE BX, B2: POKE BX + 1, B1: POKE BX + 2, B4: POKE BX + 3, B3
      : POKE BX + 4, B5: POKE BX + 5, B6: RETURN
1130 IF RD > 0 THEN GOSUB 1400: RETURN
1140 GF = (280 - X2 / S2) / 2: HF = (192 - Y2 / S2) / 2: XF = INT (X1 - GF +
      S2): YF = INT (Y1 - HF * S2): SF = S2: GOSUB 2590: RETURN
1150 REM *** VIEWPORT COMMAND ***
1160 HCOLOR= 3: IF BC = 3 OR BC = 7 THEN HCOLOR= 0
1170 GOSUB 1330: XF = INT (X1 - GF + S2): YF = INT (Y1 - HF * S2): SF = S2
      : GOSUB 2590
1180 GOSUB 1290: GOSUB 1310
1190 IF Z < 0 THEN PRINT D$;"IN#0": PRINT : GET A$: IF ASC (A$) = 13 THEN
      GOSUB 1130: GOSUB 1330: HCOLOR= PC: GOTO 170
1200 IF Z < 0 THEN IF ASC (A$) = 68 THEN GOSUB 1090: GOTO 170
1205 IF Z < 0 THEN GOTO 1180
1210 IF XT > X OR XB < X OR YT > Y OR YB < Y THEN 1180
1220 T1 = X - 1: T2 = Y - 1: H = 0: XB = T1: YB = T2: GOSUB 1350
1230 GOSUB 1280: GOSUB 1310: IF Z < 0 THEN GOSUB 1350: GOTO 1190
1240 IF XT > X OR XB < X OR YT > Y OR YB < Y THEN 1230
1250 IF X < T1 OR Y < T2 THEN GOSUB 1350: PRINT D$;"PR#0": TEXT : HOME :
      VTAB 12: HTAB 5: PRINT "PLEASE SPECIFY POINTS CORRECTLY": GOSUB 1300
      : GOTO 1180
1260 WH = 1: W# = "": GOSUB 2590: RD = 0
1270 X3 = T1 + 1: Y3 = T2 + 1: X4 = X: Y4 = Y: H = 0: GOSUB 1350: GOSUB 1330: B
      1 = INT (X3 / 256): B2 = X3 - B1 * 256: B3 = INT ((X4 + 1) / 256): B4 =
      (X4 + 1) - B3 * 256: B5 = Y3: B6 = Y4 + 1: GOSUB 1120: HCOLOR= PC: GOTO
      170
1280 PRINT PRINT D$;"PR#0": GOSUB 2300: PRINT D$;"PR#": SL: PRINT "M2": VTAB
      23: HTAB 15: POKE 41, PEEK (41) + 4: PRINT CHR$ (7); "LOWER-RIGHT?": FOR
      T3 = 1 TO 500: NEXT PRINT D$;"PR#": SL: PRINT "N,H2": RETURN
1290 PRINT PRINT D$;"PR#0": GOSUB 2300: PRINT D$;"PR#": SL: PRINT "M2": VTAB
      23: HTAB 15: POKE 41, PEEK (41) + 4: PRINT CHR$ (7); "UPPER-LEFT?": FOR
      T3 = 1 TO 500: NEXT PRINT D$;"PR#": SL: PRINT "N,H2": RETURN
1300 FOR H = 1 TO 1000: NEXT H: RETURN
1310 PRINT D$;"IN#": SL: INPUT "X,Y,Z": IF Z = 2 OR Z < 0 THEN RETURN
1320 GOTO 1310
1330 POKE 233, 99: POKE 232, 32: HCOLOR= 0: IF BC = 0 OR BC = 4 THEN HCOLOR=
      3
1340 H = 0: XB = X3 - 1: YB = Y3 - 1: GOSUB 1350: H = 16: XB = X4 + 1: YB = Y3 -
      1: GOSUB 1350: H = 32: XB = X4 + 1: YB = Y4 + 1: GOSUB 1350: H = 48: XB =
      X3 - 1: YB = Y4 + 1: GOSUB 1350: RETURN
1350 IF XB > = 0 AND XB < 280 AND YB > = 0 AND YB < 192 THEN ROT= H: SCALE=
      1: XDRAW 1 AT XB, YB
1360 RETURN
1380 RD = RD + 1: IF RD > 1 THEN RD = 0: GOSUB 1130: ON CM + 1 GOTO 170, 15
      80, 1680, 1740, 1840
1390 GOSUB 1400: ON CM + 1 GOTO 170, 1580, 1680, 1740, 1840
1400 IF X4 = X3 OR Y4 = Y3 THEN 1440
1410 T1 = ((XH * 2) - (XM * 2)) / (X4 - X3): T2 = ((YH * 2) - (YM * 2)) / (
      Y4 - Y3): SF = INT (T1): IF T2 < T1 THEN SF = INT (T2)
1420 XF = INT ((XM * 2) - (SF * X3)): YF = INT ((YM * 2) - (SF * Y3)): IF
      ABS (XF) > 27000 OR ABS (YF) > 27000 THEN GOTO 1440

```

```

1430 GOSUB 2590: RETURN
1440 PRINT D$;"PR#0": GOSUB 2300: PRINT : PRINT D$;"PR#": SL: PRINT "M2,C"
      : VTAB 23: HTAB 14: POKE 41, PEEK (41) + 4: PRINT "NOT POSSIBLE." : RD =
      0: GOSUB 1300: GOSUB 1130: RETURN
1450 PRINT : PRINT D$;"PR#": SL: PRINT "T1,C": PRINT D$;"PR#0": PRINT D$;"
      IN#0": TEXT
1470 HOME : PRINT : HTAB 9: PRINT "FAST-DRAW DELTA SETTING": VTAB 5: HTAB
      7: PRINT "CURRENT DELTA SETTING IS ": ABS (DX): " ": PRINT : A$ = "ON"
      : IF DX < 0 THEN A$ = "OFF"
1480 HTAB 10: PRINT "AUDIO FEEDBACK IS ": A$
1490 VTAB 18: CALL - 958: HTAB 11: INPUT "NEW DELTA EQUALS ": A$: IF A$ =
      "" THEN 1530
1500 IF VAL (A$) < 1 OR VAL (A$) > 127 THEN 1490
1510 IF DX < 1 THEN DX = - VAL (A$): GOTO 1530
1520 DX = VAL (A$)
1530 VTAB 20: CALL - 958: HTAB 9: INPUT "TURN AUDIO FEEDBACK ": A$: IF A$
      = "" THEN 1560
1540 IF LEFT$ (A$, 2) < > "ON" AND LEFT$ (A$, 3) < > "OFF" THEN 1530
1550 DX = ABS (DX): IF LEFT$ (A$, 3) = "OFF" THEN DX = - DX
1560 GOSUB 1130: GOTO 170
1580 GOSUB 1130: PRINT D$;"IN#": SL: CM = 1
1590 RT = 2: INPUT X,Y,Z: IF Z < > 2 THEN POKE - 16368, 0: GOTO 1590
1600 IF X < X3 OR X > X4 OR Y < Y3 OR Y > Y4 THEN GOSUB 1940: IF RT = 1 THEN
      220
1610 IF RT = 0 THEN 1590
1620 HPLLOT X,Y
1630 RT = 2: INPUT X,Y,Z: IF Z < > 2 THEN POKE - 16368, 0: GOTO 1630
1640 IF X < X3 OR X > X4 OR Y < Y3 OR Y > Y4 THEN GOSUB 1940: IF RT = 1 THEN
      220
1650 IF RT = 0 THEN 1630
1660 HPLLOT TO X,Y: GOTO 1630
1680 GOSUB 1130: PRINT D$;"IN#": SL: CM = 2
1690 RT = 2: INPUT X,Y,Z: IF Z < > 2 THEN POKE - 16368, 0: GOTO 1690
1700 IF X < X3 OR X > X4 OR Y < Y3 OR Y > Y4 THEN GOSUB 1940: IF RT = 1 THEN
      220
1710 IF RT = 0 THEN 1690
1720 HPLLOT X,Y: GOTO 1690
1740 GOSUB 1130: PRINT D$;"IN#": SL: CM = 3
1750 RT = 2: INPUT X,Y,Z: IF Z < > 2 THEN POKE - 16368, 0: GOTO 1750
1760 IF X < X3 OR X > X4 OR Y < Y3 OR Y > Y4 THEN GOSUB 1940: IF RT = 1 THEN
      220
1770 IF RT = 0 THEN 1750
1780 HPLLOT X,Y: TX = X: TY = Y
1790 RT = 2: INPUT X,Y,Z: IF Z < > 2 THEN POKE - 16368, 0: GOTO 1790
1800 IF X < X3 OR X > X4 OR Y < Y3 OR Y > Y4 THEN GOSUB 1940: IF RT = 1 THEN
      220
1810 IF RT = 0 THEN 1790
1820 HPLLOT X,Y TO TX,Y TO TX, TY TO X, TY TO X,Y: GOTO 1750
1840 GOSUB 1130: PRINT D$;"IN#": SL: CM = 4
1850 RT = 2: INPUT X,Y,Z: IF Z < > 2 THEN POKE - 16368, 0: GOTO 1850
1860 IF X < X3 OR X > X4 OR Y < Y3 OR Y > Y4 THEN GOSUB 1940: IF RT = 1 THEN
      220
1870 IF RT = 0 THEN 1850
1880 HPLLOT X,Y: TX = X: TY = Y
1890 RT = 2: INPUT X,Y,Z: IF Z < > 2 THEN POKE - 16368, 0: GOTO 1890
1900 IF X < X3 OR X > X4 OR Y < Y3 OR Y > Y4 THEN GOSUB 1940: IF RT = 1 THEN
      220
1910 IF RT = 0 THEN 1890
1920 IF Y < TY THEN FOR H = Y TO TY: HPLLOT X,H TO TX,H: NEXT : GOTO 1850
1930 FOR H = TY TO Y: HPLLOT X,H TO TX,H: NEXT : GOTO 1850
1940 IF (Y * SF + YF - YL * 2) / 50 < 2 THEN RT = 1: RETURN
1950 PRINT D$;"PR#0": GOSUB 2300: PRINT D$;"PR#": SL: PRINT "M2": VTAB 23:
      HTAB 3: POKE 41, PEEK (41) + 4: PRINT "POINT OUTSIDE VIEWPORT. RESP
      ECIFY " : GOSUB 1300: PRINT D$;"PR#": SL: PRINT "N,H2": RT = 0: RETURN
1970 GOSUB 1130: NX = 1: CALL EP%: CD = PEEK (700): ON CD + 1 GOTO 190, 197
      5, 1980, 1980
1975 IF NX = 1 THEN 1970
1980 HPLLOT XX(1), YX(1) TO XX(NX - 1), YX(NX - 1): GOSUB 1990: GOSUB 1130: GOTO
      170
1990 PRINT D$;"PR#0": GOSUB 2300: PRINT D$;"PR#": SL: PRINT "M2": VTAB 23:
      HTAB 14: POKE 41, PEEK (41) + 4: PRINT CHR$ (7); "CALCULATING. " : IF
      NX = 2 THEN AR = 0: GOTO 2020

```



```

2000 AR = 0: FOR T1 = 2 TO NX - 1: DX = X%(T1) - X%(T1 - 1): DY = Y%(T1) - Y%(T1 - 1): AR = AR + DX * DY: NEXT T1
2010 AR = AR + (X%(1) - X%(NX - 1)) * (Y%(1) + Y%(NX - 1)) / 2: AR = ABS (AR) / WM * 2: IF AR < 99999999 THEN AR = (INT (AR * 100)) / 100
2020 GOSUB 2300: VTAB 23: B$ = "AREA IS ": POKE 41, PEEK (41) + 4: GOSUB 2030: GOSUB 1300: GOSUB 1300: RETURN
2030 B$ = B$ + STR$ (AR) + " SQUARE " + WM + " ": HTAB 21 = INT (LEN (B$) / 2): PRINT B$: RETURN
2040 GOSUB 1130: NX = 1: CALL EFN: CD = PEEK (700): ON CD + 1 GOTO 170, 2075, 2080, 2090
2075 IF NX = 1 THEN 2070
2080 GOSUB 2090: GOSUB 1130: GOTO 170
2090 PRINT D$: "PR#0": GOSUB 2300: PRINT D$: "PR#": SL: PRINT "M2": VTAB 23: HTAB 14: POKE 41, PEEK (41) + 4: PRINT CHR$ (7): "CALCULATING...": IF NX = 2 THEN DT = 0: GOTO 2110
2100 DT = 0: FOR T1 = 2 TO NX - 1: DX = X%(T1) - X%(T1 - 1): DY = Y%(T1) - Y%(T1 - 1): DT = DT + SQR (DX * DX + DY * DY): NEXT T1: DT = DT / WM: IF DT < 99999999 THEN DT = (INT (DT * 100)) / 100
2110 GOSUB 2300: VTAB 23: B$ = "THE DISTANCE IS ": POKE 41, PEEK (41) + 4: GOSUB 2120: GOSUB 1300: GOSUB 1300: RETURN
2120 B$ = B$ + STR$ (DT) + " " + WM + " ": HTAB 21 = INT (LEN (B$) / 2): PRINT B$: RETURN
2130 GOSUB 1130
2170 GOSUB 2310
2180 PRINT D$: "IN#": SL: INPUT X, Y, Z: IF Z < 0 THEN PRINT D$: "IN#0": GET A$: IF ASC (A$) = 13 THEN GOSUB 1130: GOTO 170
2190 IF Z < 0 THEN PRINT: GOTO 2180
2200 IF X3 < X OR X4 < X OR Y3 < Y OR Y4 < Y THEN 2170
2210 GOSUB 2320
2220 PRINT D$: "IN#": SL: INPUT TX, TY, Z: IF Z < 0 THEN PRINT D$: "IN#0": GET A$: IF ASC (A$) = 13 THEN GOSUB 1130: GOTO 170
2230 IF Z < 0 THEN PRINT: GOTO 2220
2240 IF TX < X3 OR TX > X4 OR TY < Y3 OR TY > Y4 THEN 2210
2250 PRINT D$: "PR#": SL: PRINT "T1, C": TEXT: HOME: T1 = TX - X + 1: T2 = Y - Y + 1: DX = SQR (T1 * T1 + T2 * T2): VTAB 10: HTAB 6: PRINT "DISTANCE IS ": INT (DX): " SCREEN UNITS. ": PRINT D$: "IN#0"
2260 VTAB 18: CALL - 959: HTAB 8: INPUT "YOUR NUMBER OF UNITS -> ": A$: IF A$ = "" THEN W = DX: GOTO 2280
2265 IF VAL (A$) > 999999999 THEN 2260
2270 W = VAL (A$): IF W = 0 THEN 2260
2280 VTAB 20: CALL - 959: HTAB 8: INPUT "TYPE OF UNITS -> ": W$: IF LEN (W$) > 10 THEN 2280
2290 WM = DX / W: GOSUB 1130: GOTO 170
2300 FOR T4 = 21 TO 24: VTAB T4: HTAB 1: POKE 41, PEEK (41) + 4: PRINT " ": NEXT T4: PRINT: RETURN
2310 PRINT D$: "PR#0": GOSUB 2300: PRINT D$: "PR#": SL: PRINT "M2": VTAB 23: HTAB 13: POKE 41, PEEK (41) + 4: PRINT CHR$ (7): "BEGINNING POINT": FOR T3 = 1 TO 500: NEXT: PRINT D$: "PR#": SL: PRINT "N, H2": RETURN
2320 PRINT D$: "PR#0": GOSUB 2300: PRINT D$: "PR#": SL: PRINT "M2": VTAB 23: HTAB 14: POKE 41, PEEK (41) + 4: PRINT CHR$ (7): "ENDING POINT": FOR T3 = 1 TO 500: NEXT: PRINT D$: "PR#": SL: PRINT "N, H2": RETURN
2330 REM *** CHRIS' SLIDE ***
2340 GOSUB 1330: HCOLOR = BC: GOSUB 1040
2350 GOSUB 1130: GOSUB 2310
2360 PRINT D$: "IN#": SL: INPUT X, Y, Z: IF Z < 0 THEN PRINT D$: "IN#0": GET A$: IF ASC (A$) = 13 THEN 2470
2370 IF Z < 0 THEN PRINT: GOTO 2360
2380 IF X < 0 OR X > 279 OR Y < 0 OR Y > 191 THEN 2350
2390 GOSUB 2320
2400 PRINT D$: "IN#": SL: INPUT TX, TY, Z: IF Z < 0 THEN PRINT D$: "IN#0": GET A$: IF ASC (A$) = 13 THEN 2470
2410 IF Z < 0 THEN PRINT: GOTO 2400
2420 IF TX < 0 OR TX > 279 OR TY < 0 OR TY > 191 OR (TX = X AND TY = Y) THEN 2390
2430 IF TY > Y THEN FOR ZZ = 1 TO TY - Y: CALL 25218: NEXT: GOTO 2450
2440 IF Y > TY THEN FOR ZZ = 1 TO Y - TY: CALL 25175: NEXT
2450 IF TX > X THEN FOR ZZ = 1 TO INT ((TX - X) / 14): CALL 25308: NEXT: GOTO 2470
2460 IF X > TX THEN FOR ZZ = 1 TO INT ((X - TX) / 14): CALL 25261: NEXT
2470 HCOLOR = 0: IF BC = 0 OR BC = 4 THEN HCOLOR = 3
2480 GOSUB 1040: GOSUB 1330: HCOLOR = PC: GOSUB 1130: GOTO 170
2490 REM *** DAVE'S SEPERATE ***

```

```

2500 T3 = PC: GOSUB 670: IF PC = 4 OR PC = 0 THEN PC = T3: HCOLOR = PC: HOME: PRINT: HTAB 9: PRINT "NO SEPARATION ON BLACKS. ": GOSUB 1300: GOSUB 1410: GOSUB 1130: GOTO 170
2510 IF PC = 8 THEN PC = T3: GOTO 2580
2520 PRINT D$: "PR#": SL: PRINT "H2, N": GOSUB 1330: HCOLOR = BC: GOSUB 1040: IF PC = 3 OR PC = 7 THEN POKE 767, 176: CALL 24576: GOTO 2570
2530 POKE 767, 144: CALL 24576: T1 = 128: T2 = 213: IF PC = 2 THEN T2 = 170
2540 IF PC = 5 THEN T1 = 0: T2 = 213
2550 IF PC = 6 THEN T1 = 0: T2 = 170
2560 POKE 766, T1: POKE 767, T2: CALL 24911
2570 BC = 0: HCOLOR = 3: GOSUB 1040: GOSUB 1330
2580 HCOLOR = PC: GOSUB 1130: GOTO 170
2590 PRINT: PRINT D$: "PR#": SL
2600 PRINT "D, S": SF: "H2, X": XF: "Y": YF: "R, N": RETURN
2610 TEXT: HOME: PRINT: HTAB 7: PRINT "TABLET INFORMATION FILE DOES": PRINT: HTAB 16: PRINT "NOT EXIST"
2620 VTAB 7: HTAB 8: PRINT "MAKE SURE THE MASTER DISK": PRINT: HTAB 11: PRINT "IS NOT PROTECTED AND": PRINT: HTAB 12: PRINT "THEN PRESS RETURN"
2630 VTAB 14: HTAB 5: PRINT "THE MENU ALIGNMENT ROUTINE WILL": PRINT: HTAB 17: PRINT "BE RUN. ": GET A$: IF ASC (A$) < 0 THEN 2630
2635 POKE 104, 8: POKE 103, 1
2640 PRINT: PRINT D$: "RUN MENU ALIGNMENT, D1": STOP
2650 REM + ERROR HANDLER +
2660 TEXT: HOME: T7 = PEEK (222): PRINT D$: "PR#0": IF T7 = 8 THEN VTAB 12: HTAB 16: PRINT "I/O ERROR. ": GOTO 2700
2670 IF T7 = 6 THEN VTAB 12: HTAB 11: PRINT "PICTURE NOT ON DISK. ": GOTO 2700
2680 IF T7 = 4 OR T7 = 9 OR T7 = 10 THEN VTAB 12: HTAB 8: PRINT "THE PICTURE IS LOCKED, OR": HTAB 5: PRINT "THE DISK IS FULL, OR PROTECTED. ": GOTO 2700
2685 IF T7 = 13 THEN VTAB 12: PRINT "FILE REQUESTED IS NOT A PICTURE FILE. ": GOTO 2700
2690 VTAB 12: HTAB 9: PRINT "PROBLEM --> PEEK(222) = ": T7
2700 VTAB 20: HTAB 8: PRINT "PRESS SPACE BAR TO RETRY. ": PRINT: HTAB 11: PRINT "PRESS <CR> TO ABORT"
2710 VTAB 24: HTAB 20: GET A$: IF A$ = " " THEN VTAB 20: HTAB 1: CALL - 959: HTAB 15: PRINT "RETRYING. ": IF T7 = 6 THEN GOTO 349
2715 IF A$ = " " THEN RESUME
2720 IF ASC (A$) = 13 THEN PRINT: PRINT D$: "CLOSE ": B$: GOTO 290
2730 GOTO 2710

```

VARIABLE ATLAS

Name	Description
A\$	General-purpose input string
AR	Calculated area for AREA command
B\$	Input string for picture name in LOAD and SAVE
B1-B6	Temporary variables for WINDOW
BC	Background Color (defaults to 0)
BX	Pointer into the QUICK-DRAW subroutines
C\$	String for slot number
CD	Termination code of QUICK-DRAW subroutines
CM	Current Command mode: 0 = DRAW 1 = LINES 2 = DOTS 3 = FRAME 4 = BOX
D\$	CTRL-D (CHR\$(4)) for DOS commands
DX	DELTA setting (0-127; negative if Audio Feedback is off)
DF	Default drive number for LOAD, SAVE, CATALOG

DT Calculated distance for DISTANCE command

DX,DY Temporary variables used in AREA and DISTANCE: the vertical and horizontal distance between a point and the next one.

E\$ Temporary input string for SAVE

EP% The beginning address of the QUICK-DRAW subroutines

GF X screen offset values for WINDOW

H Widely used as a temporary variable.

HF Y screen offset values for WINDOW

LT Length of menu, in Tablet units

M% Maximum number of points for DISTANCE or AREA calculation

MD Height and width of each menu command square, in Tablet units

N% Index into arrays X% and Y%, used by QUICK-DRAW

PC Pen color (0-7), defaults to 3 (white)

PI Number of points per inch on the Tablet

RD Flag for REDUCER mode: 1=on, 0=off.

RT A return flag for LINES, DOTS, FRAME, and BOX modes whose value indicates the phase of the operation:

0 = Operation was just initialized.

1 = Menu selected; operation cancelled.

2 = Operation in progress.

S0 Scale setting for menu

S2 Scale setting for WINDOW after LOAD

SF Scale Factor -- see XF,YF

SL Slot number of Tablet Interface card (read from info file)

T1-T9 Temporary variables

TX,TY Temporarily holds an X,Y position (for BOX, LINES, FRAME, SLIDE)

W User CALIBRATE units

W\$ Name of user CALIBRATE units

WM CALIBRATE multiplier (WM= Tablet units / W)

X,Y General-purpose coordinate pair for high-resolution screen

X%,Y% Arrays (of length M%) which hold coordinates of points plotted in DRAW, AREA, and DISTANCE. They are filled by the QUICK-DRAW subroutines.

X1,Y1 Coordinates for upper-left corner of WINDOW on Tablet

X2,Y2 Coordinates for lower-right corner of WINDOW on Tablet

X3,Y3 Coordinates for upper-left corner of VIEWPORT on screen

X4,Y4 Coordinates for lower-right corner of VIEWPORT on screen

X5,Y5 Default values for X1,Y1

X6,Y6 Default values for X2,Y2

X8,Y8 Temporary X,Y coordinates (for VIEWPORT and color menu)

X9,Y9 " " " "

XA,YA Width and height of menu overlay

XB,YB Coordinates for lower-right corner of WINDOW on screen

XF,YF Current Tablet offset factors

XH,YH Coordinates for upper-left corner of overlay on Tablet

XL,YL Coordinates for lower-right corner of overlay on Tablet

XM,YM Coordinates for upper-left corner of working area on Tablet

XT,YT Coordinates for upper-left corner of WINDOW on screen

Z Pen up/pen down value:

0 = pen is down, and has been down.

1 = pen is up

2 = pen newly down

10 = pen is off-scale

Negative numbers indicate that a key has been pressed.

ZZ Temporary variable used in delay loops.

SUBROUTINES

Entry	Description
530	Inputs drive number from keyboard
670	Displays color menu; returns chosen color in PC
880	Draws a single box of the color C9 on the low-resolution graphics screen. The box will be X8 blocks tall, and its upper-left corner will be at (X9, Y9).
1040	Draws the WINDOW on the high-resolution screen in the current HCOLOR.
1070	Sets scaling information for Tablet; falls into subroutine at 1090
1090	Turns off REDUCER, removes WINDOW frame and sets WINDOW to its default values, resets CALIBRATE setting, and falls into subroutine at 1120
1120	Stores VIEWPORT setting in memory for QUICK-DRAW
1130	Resets Tablet scaling information (with REDUCER, if active)
1280	Prints prompt "LOWER-RIGHT?"
1290	Prints prompt "UPPER-LEFT?"
1300	Delay 1.1 seconds
1310	Wait for the pen to be down or a keypress. If pen is down, return with coordinates in X,Y; if keypress, return with Z<0.
1330	Draws or undraws the four VIEWPORT corner marks.
1350	Draws or undraws a single VIEWPORT corner mark. The corner's coordinates are in X8,Y8 and the rotation factor is in H.
1400	Turns on the REDUCER.
1940	Returns with RT=1 if the last pen press was in the menu area; otherwise displays "POINT OUTSIDE VIEWPORT. RESPECIFY"
1990	Performs an AREA calculation on the polygon whose vertices are in the arrays X%,Y%. Returns with the area in AR.
2090	Performs a DISTANCE calculation on the closed curve whose points are in the arrays X%,Y%. Returns with the distance in DT.
2120	Adds the value of DT to the end of string B\$, and prints it centered on the screen.
2300	Clears out the bottom four lines of the Page 2 Text screen.
2310	Displays the prompt "BEGINNING POINT?"
2320	Displays the prompt "ENDING POINT?"
2590	Reinitializes the Tablet with the scaling factor in SF, the X-offset in XF, and the Y-offset in YF.

SPECIAL LOCATIONS

These special memory locations are used by the TABLET-CODE APPLESOFT program. The decimal addresses are given on the left; hexadecimal equivalents are in parentheses and preceded by a dollar sign (\$):

Location	Use
41 (\$29)	This location contains the high part of the memory address of the beginning of the current line on the Text screen. A POKE 41, PEEK(41)+4 operation will cause the next printed line to appear on Page 2, rather than Page 1, of Text mode.
103,104 (\$67,\$68)	This pair of locations holds the address of the beginning of the current Applesoft program in memory.
222 (\$DE)	This location holds the ON ERR GOTO code of the last error generated.
232,233 (\$E8,\$E9)	This pair of locations holds the address of the beginning of the current shape table for the Applesoft DRAW and XDRAW commands.
700 (\$2BC)	Holds the termination code from the QUICK-DRAW subroutines.
752,753 (\$2F0,\$2F1)	After the QUICK-DRAW program is RUN, this pair of locations will hold the memory address of the beginning of the QUICK-DRAW subroutine.
766,767 (\$2FE,\$2FF)	These locations are used to pass the selected color to the SEPARATE subroutine.
3089-3094 (\$C11-\$C16)	These locations are used to pass VIEWPORT information to the QUICK-DRAW subroutine.
16632,16633 (\$40F8,\$40F9)	These locations are in the memory range used by the high-resolution graphics Page 2, but their contents are neither displayed on the screen or affected by normal screen operations. These two locations are used to store the value of S2 during a SAVE.
16504-16511 (\$4078-\$407F)	These are also locations in the high-resolution Page 2 which are not displayed. These eight locations are used to store the values of X1, X2, Y1, and Y2 during a SAVE.
24576 (\$6000)	This is the entry point for the machine language subroutine which performs a SEPARATE.

24911 (\$614F)	This is another entry point for SEPARATE.
25175 (\$6257)	Entry point for a one-dot SLIDE down.
25218 (\$6282)	Entry point for a one-dot SLIDE up.
25261 (\$62AD)	Entry point for a 14-dot SLIDE right.
25308 (\$62DC)	Entry point for a 14-dot SLIDE left.
-16368 (\$C010)	A PEEK or POKE to this location will clear the Apple's keyboard strobe, causing any recent keypress to be ignored.
62454 (\$F3F6)	This subroutine in the Applesoft ROM fills the entire high-resolution screen with the most recent HCOLOR plotted.
-958 (\$FC42)	This subroutine in the Apple's Monitor ROM clears the text screen from the current cursor position to the end of the screen.
-868 (\$FC9C)	This subroutine in the Apple's Monitor ROM clears the text screen from the current cursor position to the end of the line.

ROM CODE

```

SOURCE FILE: BITPAD35.1P
SOURCE FILE: BITPAD35.2P
0000: 1 *****
0000: 2 *
0000: 3 *
0000: 4 * BIT PAD FIRMWARE
0000: 5 *
0000: 6 * COPYRIGHT APPLE COMPUTER
0000: 7 * 7/30/79
0000: 8 * W SANDER
0000: 9 *
0000: 10 *
0000: 11 *****
0024: 12 CH EQU $24 ; SCREEN HORIZONTAL POSITION
002A: 13 HBASL EQU $2A ; BASE ADDRESS FOR BITPAD CURSOR
002B: 14 HBASH EQU $2B
002B: 15 BASL EQU $2B ; TEXT BASE ADDRESS
0036: 16 COUTL EQU $36 ; LOW BYTE OF COUT POINTER
0037: 17 COUTH EQU $37 ; HIGH BYTE OF COUT POINTER
0200: 18 IN0 EQU $200 ; INPUT BUFFER ADDRESSES
0201: 19 IN1 EQU $201
0202: 20 IN2 EQU $202
0203: 21 IN3 EQU $203
0280: 22 TEM EQU $280 ; RETURN FLAG LOCATION
0000: 23 * ; HIGH NIBBLE - 1=RETURN SCALED VALUE
0000: 24 * ; LOW NIBBLE - 0=PEN DOWN, 1=PEN LEFT, 2=PEN FALL, 3=PEN UP
0281: 25 XFLL EQU $281 ; X-COORD LOW BYTE, FULL SCALE
0282: 26 XFLH EQU $282 ; X-COORD HIGH BYTE, FULL SCALE
0283: 27 YFLL EQU $283 ; Y-COORD LOW BYTE, FULL SCALE
0284: 28 YFLH EQU $284 ; Y-COORD HIGH BYTE, FULL SCALE
0285: 29 TEMXL EQU $285 ; X-COORD LOW BYTE, SCALED
0286: 30 TEMX EQU $286 ; X-COORD HIGH BYTE, SCALED

```



```

0287: 31 TEMYL EQU $287 ;Y-COORD LOW BYTE, SCALED
0288: 32 TEMY EQU $288 ;Y-COORD HIGH BYTE, SCALED
0289: 33 REGL EQU $287 ;DIVIDE REGISTERS
0288: 34 REGH EQU $288
0290: 35 INA EQU $290 ;BUFFER REGISTER FOR PRM SYNTAX
0298: 36 INX EQU $298 ;PRM BUFFER POINTER
0299: 37 NFLAG EQU $299 ;PRM BUFFER STATUS FLAG
0298: 38 SAVSLOT EQU $298
02A0: 39 MIFLAG EQU $2A0
02A1: 40 GREGL EQU $2A1
02A2: 41 GREGH EQU $2A2
02A3: 42 DIVL EQU $2A3
02A4: 43 DIVH EQU $2A4
02A5: 44 C1HAR EQU $2A5
0368: 45 PAGE EQU $368 ;PAGE CODE:
0000: 46 *
0000: 47 * HIGH BIT = 1 MEANS SCALE DATA
0000: 48 * 40 = HIRES PAGE2
0000: 49 * 20 = HIRES PAGE1
0000: 50 * 08 = TEXT PAGE2
0000: 51 * 04 = TEXT PAGE1
0000: 52 * 02 = LORES PAGE2
0000: 53 * 01 = LORES PAGE1
0000: 54 * 42 = HIRES MIXED PAGE2
0000: 55 * 21 = HIRES MIXED PAGE1
0000: 56 * 0A = LORES MIXED PAGE2
0000: 57 * 05 = LORES MIXED PAGE1
0000: 58 *
0438: 59 MPAGE EQU $438
0000: 60 *
0000: 61 * LAST SIX BITS OF MPAGE CORRESPOND TO PAGE
0000: 62 * BIT 7 MEANS STREAM MODE IF 1
0000: 63 * BIT 6 MEANS OFFSET AFTER SCALE IF 1
0000: 64 *
0488: 65 SCALL EQU $488 ;LOW BYTE OF SCALE FACTOR
0538: 66 SCALH EQU $538 ;HIGH BYTE OF SCALE FACTOR
0588: 67 OFFXL EQU $588 ;LOW BYTE OF X-OFFSET
0638: 68 OFFXH EQU $638 ;HIGH BYTE OF X-OFFSET
0688: 69 OFFYL EQU $688 ;LOW BYTE OF Y-OFFSET
0738: 70 OFFYH EQU $738 ;HIGH BYTE OF Y OFFSET
0678: 71 HNDX EQU $678 ;TEMP INDEX FOR CURSOR PLOT
0578: 72 TEMPL EQU $578
05F8: 73 TEMPH EQU $5F8
02A5: 74 COUNT EQU $2A5 ;UTILITY COUNT REG
06F8: 75 CHAR EQU $6F8 ;TEMPORARY CHARACTER STORE
07F8: 76 MSLOT EQU $7F8 ;CURRENT SLOT POINTER %CN
0000: 77 KBD EQU $C000 ;KEYBOARD STROBE
0010: 78 KBDSTRB EQU $C010 ;KEYBOARD STROBE RESET
0050: 79 SGR EQU $C050 ;DISPLAY MODE REFERENCES
0051: 80 STXT EQU $C051
0052: 81 SNMIX EQU $C052
0053: 82 SMIX EQU $C053
0054: 83 SPAG1 EQU $C054
0055: 84 SPA02 EQU $C055
0056: 85 SLORES EQU $C056
0057: 86 SHIRES EQU $C057
0081: 87 DEVO EQU $C081 ;BITPAD DEVICE ADDRESSES
0080: 88 DEV1 EQU $C080
0083: 89 DEV2 EQU $C083
0082: 90 DEV3 EQU $C082
CFFF: 91 ROMSW EQU $CFFF ;REFERENCE ADDRESS TO FREE $C800
FE93: 92 SETVID EQU $FE93 ;SET CHARACTER OUTPUT TO NORMAL
FD6D: 93 COUT EQU $FD6D ;CHARACTER OUTPUT
FF58: 94 IORTS EQU $FF58 ;UTILITY LOCATION CONTAINING RTS
0000: 96 *****
0000: 97 *
0000: 98 * CNOO ROM ENTRY
0000: 99 * FLAG SET-UP: C CLEAR FOR IN# ENTRY
0000: 100 * C SET FOR POINT RETURN (CURSOR)
0000: 101 *
0000: 102 * CNOO ENTRY CODE REPLICATED FOR EACH
0000: 103 * N FROM 9 TO F (CORRESPONDING TO 1 TO 7)
0000: 104 *
0000: 105 *****

```

```

0000: 107 *****
0000: 108 *
0000: 109 * C800 SPACE ENTRY
0000: 110 *
0000: 111 * GET SLOT NO. SAVE MSLOT,
0000: 112 * AND SET DEFAULTS
0000: 113 *
0000: 114 *****
----- NEXT OBJECT FILE NAME IS XX
C800: 115 ORG $C800
0000: 116 OBJ $6000
C800: BD A5 02 117 OTHROM STA C1HAR ;SAVE ACCUM FOR PR# ROUTINE
C803: 68 118 PLA ;PULL RETURN VECTOR TO
C804: 68 119 PLA ;GET SLOT NO.
C805: 28 120 PLP
C806: 50 01 121 DVC AOTHROM
C808: 60 122 RTS
C809: BD FB 07 123 AOTHROM STA MSLOT ;SAVE SLOT NO.
C80C: BD 9B 02 124 STA SAVSLOT
C80F: AD A5 02 125 LDA C1HAR
C812: BD FB 06 126 STA CHAR
C815: 48 127 PHA ;SAVE ACCUM
C816: BA 128 TXA ;SAVE X-REG AND Y-REG
C817: 48 129 PHA
C818: 98 130 TYA
C819: 48 131 PHA
C81A: 08 132 PHP ;SAVE STATUS
C81B: AE FB 07 133 LDX MSLOT ;LOAD X FOR SLOT DEP VARS
C81E: BD 38 04 134 LDA MPAGE, X
C821: 49 25 135 EOR #25
C823: 5D 38 03 136 EOR PAGE, X
C826: 29 3F 137 AND #3F
C828: F0 03 138 BEQ PRCHK ;IF 3D THEN NO DEFAULT
C82A: 20 90 CE 139 JSR DEFAULT ;CHECK IF FROM PR#
C82D: E4 37 140 PRCHK CPX COUTH
C82F: D0 03 141 BNE NOPR
C831: 4C AD CC 142 JMP SYNTAX ;IF 3D, THEN TAKE IN COMMANDS
C834: 28 143 NOPR PLP ;RECOVER STATUS
C835: 08 144 PHP ;AND SAVE
C836: B0 07 145 BCS EPOINT
C838: AD FB 06 146 LDA CHAR
C83B: A4 24 147 LDY CH
C83D: 91 28 148 STA (BASL),Y ;ELIM FLASHING CURSOR
C83F: 150 *****
C83F: 151 *****
C83F: 152 *
C83F: 153 * MAIN LOOP ENTRY
C83F: 154 *
C83F: 155 *****
C83F: 156 *****
C83F: 20 89 CB 157 EPOINT JSR MREAD ;READ BITPAD
C842: 2C 00 C0 158 BIT KBD
C845: 30 26 159 BMI END
C847: AD 80 02 160 LDA TEM ;CHECK IF PEN DOWN
C84A: 29 03 161 AND #3
C84C: C9 03 162 CMP #3
C84E: D0 1D 163 BNE END ;EXIT IF PEN DOWN
C850: AC FB 07 164 LDY MSLOT
C853: B9 88 03 165 LDA PAGE, Y
C856: 29 7F 166 AND #7F
C858: F0 0E 167 BEQ E1PNT
C85A: 20 F0 CB 168 JSR CURSOUT ;DRAW CURSOR
C85D: A9 60 169 LDA #60
C85F: 20 A1 CC 170 JSR GWAIT ;LEAVE CURSOR ON FOR AWHILE
C862: 20 F0 CB 171 JSR CURSOUT ;THEN DELETE CURSOR
C865: AC FB 07 172 LDY MSLOT
C868: B9 38 04 173 E1PNT LDA MPAGE, Y
C86B: 10 D2 174 BPL EPOINT

```

```

C86D: 176 *****
C86D: 177 *****
C86D: 178 *
C86D: 179 * EXIT ROUTINES
C86D: 180 *
C86D: 181 *****
C86D: 182 *****
C86D: A2 03 183 END LDX #3
C86F: BD 81 02 184 INEX1 LDA XFL, X ; COPY RESULTS TO TEM REGISTERS
C872: 9D 85 02 185 STA TEMXL, X
C875: CA 186 DEX
C876: 10 F7 187 BPL INEX1
C878: AE F8 07 188 LDX MSL0T ; TEST HIGH BIT OF 'PAGE' TO
C87B: BD 88 03 189 LDA PAGE, X ; SEE IF DATA IS TO BE SCALED
C87E: 10 03 190 BPL INEX2
C880: 20 70 C8 191 JSR SCALE ; SCALE AND OFFSET DATA INTO TEM-R
C883: 28 192 INEX2 PLP
C884: 90 05 193 BCC INEXIT ; SKIP TO FURTHER PROCESSING
C886: 68 194 EXIT PLA
C887: A8 195 TAY
C888: 68 196 PLA ; RESTORE REGISTERS AND EXIT
C889: AA 197 TAX ; IF NOT FROM IN#
C88A: 68 198 PLA
C88B: 60 199 RTS
C88C: 200 *
C88C: 201 * SET INPUT BUFFER TO +0000, +0000, +00
C88C: 202 *
C88C: 203 *****
C88C: A9 80 204 INEXIT LDA #180
C88E: A0 0E 205 LDY #E
C890: 99 00 02 206 GLOOP STA IN0, Y
C893: 88 207 DEY
C894: 10 FA 208 BPL GLOOP
C896: A9 A8 209 LDA #A8
C898: BD 00 02 210 STA $200
C89B: BD 06 02 211 STA $206
C89E: BD 0C 02 212 STA $20C
C8A1: A9 AC 213 LDA #AC
C8A3: BD 05 02 214 STA $205
C8A6: BD 08 02 215 STA $208
C8A9: AD 80 02 216 LDA TEM
C8AC: 29 10 217 AND #10
C8AE: D0 16 218 BNE ASCEX
C8B0: AD 85 02 219 LDA TEMXL
C8B3: AC 86 02 220 LDY TEMX ; CONVERT X TO ASCII
C8B6: A2 00 221 LDX #0 ; IN INPUT BUFFER
C8B8: 20 6A CA 222 JSR ASCON
C8BB: AD 87 02 223 LDA TEMYL
C8BE: AC 88 02 224 LDY TEMY
C8C1: A2 06 225 LDX #6 ; CONVERT Y TO ASCII
C8C3: 20 6A CA 226 JSR ASCON ; IN INPUT BUFFER
C8C6: 2C 00 C0 227 ASCEX BIT KBD
C8C9: 10 09 228 BPL ASC1EX
C8CB: A9 AD 229 LDA #AD
C8CD: BD 0C 02 230 STA $20C
C8D0: AD 80 02 231 ASC1EX LDA TEM
C8D3: 48 232 PHA
C8D4: 29 0F 233 AND #0F ; SET UP RETURN FLAG IN INPUT BUFF
C8D6: 09 80 234 ORA #80
C8D8: BD 0E 02 235 STA $20E
C8DB: 68 236 PLA
C8DC: 4A 237 LSR A
C8DD: 4A 238 LSR A
C8DE: 4A 239 LSR A
C8DF: 4A 240 LSR A
C8E0: 29 0F 241 AND #0F
C8E2: 09 80 242 ORA #80
C8E4: BD 0D 02 243 STA $20D
C8E7: A8 244 TAY
C8E8: 68 245 PLA ; PULL STACK AND SET UP
C8E9: 68 246 PLA ; REGISTERS FOR END OF LINE
C8EA: 68 247 PLA
C8EB: A2 0F 248 LDX #0F
C8ED: A9 8D 249 LDA #8D
C8EF: 60 250 RTS

```

```

C8F0: 252 *****
C8F0: 253 *****
C8F0: 254 *
C8F0: 255 * CURSOR ROUTINE
C8F0: 256 *
C8F0: 257 *****
C8F0: 258 *****
C8F0: 20 70 C8 259 CURSQUT JSR SCALE
C8F3: 4C 0C C9 260 JMP C1SKP
C900: 261 ORG $100+OTHROM
C900: 18 262 INPUTXY CLC ; CARRY SET FOR IN# ENTRY
C901: 80 263 DFB #80 ; SKIP NEXT BYTE
C902: 38 264 POINT SEC ; SET CARRY FOR ENTRY TO GET A POINT
C903: 88 265 CLV
C904: 08 266 PHP ; SAVE FLAGS FOR LATER
C905: 78 267 SEI ; DISABLE INTERRUPT UNTIL MSL0T SE
C906: 2C FF CF 268 BIT ROMSW ; SWITCH OFF ALL $C800 ROMS
C909: 20 00 C8 269 JSR OTHROM ; SWITCH TO $C800 SPACE
C90C: A5 2A 270 C1SKP LDA HBASL
C90E: 48 271 PHA
C90F: A5 2B 272 LDA HBASH
C911: 48 273 PHA
C912: AD 87 02 274 LDA TEMYL
C915: AE 85 02 275 LDX TEMXL
C918: 20 4C CA 276 CALLCURS JSR WINCHK
C91B: 48 277 PHA
C91C: B0 30 278 BCS OUT1
C91E: 20 F0 C9 279 JSR BASCLC
C921: 280 *****
C921: 281 *
C921: 282 * MODE EVALUATION
C921: 283 *
C921: 284 *****
C921: B9 88 03 285 LDA PAGE, Y
C924: 29 7F 286 AND #7F
C926: A8 287 TAY
C927: 29 0C 288 AND #0C
C929: F0 26 289 BEQ GR
C92B: 98 290 TYA
C92C: 29 63 291 AND #63
C92E: F0 06 292 BEQ TEXT
C930: 68 293 MIX PLA ; MIXED GRAPHICS BOUNDARY TEST
C931: 48 294 PHA
C932: C9 A0 295 CMP #160
C934: 90 18 296 BCC GR
C936: 297 *****
C936: 298 *
C936: 299 * TEXT MODE CURSOR GENERATION
C936: 300 *
C936: 301 *****
C936: 98 302 TEXT TYA
C937: 20 DE C9 303 JSR LOCLC
C93A: B1 2A 304 LDA (HBASL), Y
C93C: 48 305 PHA
C93D: A9 DF 306 LDA #DF
C93F: 91 2A 307 STA (HBASL), Y
C941: A9 80 308 LDA #80
C943: 20 A1 CC 309 JSR GWAIT
C946: 68 310 PLA
C947: 91 2A 311 STA (HBASL), Y
C949: A9 60 312 LDA #60
C94B: 20 A1 CC 313 JSR GWAIT
C94E: 4C D0 C9 314 OUT1 JMP OUT
C951: 98 315 GR TYA ; TEST FOR HIRES VS LORES GRAPHICS
C952: C9 0F 316 CMP #0F
C954: B0 18 317 BCS HIRES
C956: A5 2B 318 LDA HBASH
C958: 29 10 319 AND #10
C95A: 320 *****
C95A: 321 *
C95A: 322 * LD RESOLUTION GRAPHICS
C95A: 323 * CURSOR ROUTINE
C95A: 324 *
C95A: 325 *****

```



```

C95A:08 326 LORES PHP
C95B:A9 F0 327 LDA #F0
C95D:28 328 PLP
C95E:D0 02 329 BNE LOR1
C960:49 FF 330 EOR #FF
C962:48 331 LOR1 PHA
C963:98 332 TYA
C964:0A 333 ASL A
C965:0A 334 ASL A
C966:20 DE C9 335 JSR LOCLC
C969:68 336 PLA
C96A:51 2A 337 EOR (HBASL),Y
C96C:91 2A 338 STA (HBASL),Y
C96E:4C D0 C9 339 JMP OUT
C971: 340 *****
C971: 341 *
C971: 342 * HIRES CURSOR ROUTINE
C971: 343 *
C971: 344 *****
C971:A9 16 345 HIRES LDA #16
C973:8D A5 02 346 STA COUNT
C976:8A 347 TXA
C977:38 348 SEC
C978:E9 05 349 SBC #5
C97A:AA 350 TAX
C97B:B0 03 351 BCS LOOP
C97D:CE 86 02 352 DEC TEMX
C980:A0 05 353 LOOP LDY #5
C982:AD A5 02 354 LDA COUNT
C985:D9 D8 C9 355 CTRLLOOP CMP CTRCHK,Y
C988:F0 14 356 BEQ OUTSIDE
C98A:88 357 DEY
C98B:10 F8 358 BPL CTRLLOOP
C98D:68 359 PLA
C98E:20 4C CA 360 JSR WINCHK
C991:48 361 PHA
C992:80 0A 362 BCS OUTSIDE
C994:20 F0 C9 363 JSR BASCLC
C997:AC 78 06 364 LDY HNDX
C99A:51 2A 365 EOR (HBASL),Y
C99C:91 2A 366 STA (HBASL),Y
C99E:A9 0C 367 OUTSIDE LDA #C
C9A0:CD A5 02 368 CMP COUNT
C9A3:F0 0E 369 BEQ A
C9A5:80 1D 370 BCS B
C9A7:EB 371 INX
C9A8:D0 03 372 BNE C
C9AA:EE 86 02 373 INC TEMX
C9AD:CE A5 02 374 C DEC COUNT
C9B0:4C 80 C9 375 JMP LOOP
C9B3:8A 376 A TXA
C9B4:E9 05 377 SBC #5
C9B6:AA 378 TAX
C9B7:AD 86 02 379 LDA TEMX
C9BA:E9 00 380 SBC #0
C9BC:8D 86 02 381 STA TEMX
C9BF:68 382 PLA
C9C0:38 383 SEC
C9C1:E9 06 384 SBC #6
C9C3:48 385 PHA
C9C4:68 386 B PLA
C9C5:18 387 CLC
C9C6:69 01 388 ADC #1
C9C8:48 389 PHA
C9C9:CE A5 02 390 DEC COUNT
C9CC:F0 02 391 BEQ OUT
C9CE:D0 80 392 BNE LOOP
C9D0:68 393 OUT PLA
C9D1:68 394 PLA
C9D2:85 28 395 STA HBASH
C9D4:68 396 PLA
C9D5:85 2A 397 STA HBASL
C9D7:60 398 RTS

```

```

C9DB:12 399 CTRCHK DFB #12
C9DD:11 400 DFB #11
C9DA:10 401 DFB #10
C9DB:07 402 DFB #7
C9DC:06 403 DFB #6
C9DD:05 404 DFB #5
C9DE: 405 *****
C9DE: 406 * TEXT BASE CALC
C9DE: 407 *
C9DE: 408 * THIS SUBROUTINE SETS UP BASE REGISTER
C9DE: 409 * FOR LORES OR TEXT
C9DE: 410 * ENTER WITH 'PAGE' IN A --
C9DE: 411 * EXIT WITH HNDX IN Y, READY FOR SCREEN PROCESSING
C9DE: 412 *
C9DE: 413 *****
C9DE:48 414 LOCLC PHA
C9DF:A5 28 415 LDA HBASH
C9E1:29 03 416 AND #3
C9E3:85 28 417 STA HBASH
C9E5:68 418 PLA
C9E6:29 0C 419 AND #0C
C9E8:05 28 420 ORA HBASH
C9EA:85 28 421 STA HBASH
C9EC:AC 78 06 422 LDY HNDX
C9EF:60 423 RTS
C9F0: 425 *****
C9F0: 426 *
C9F0: 427 * SCREEN BASE ADDRESS CALC
C9F0: 428 *
C9F0: 429 * ENTER WITH LO BYTE OF Y IN ACCUM
C9F0: 430 * AND WITH LO BYTE OF X IN X-REG
C9F0: 431 *
C9F0: 432 * BASE ADDRESS WILL BE COMPUTED INTO
C9F0: 433 * HBASL,HBASH, AND HNDX: HIRES BIT ADRESSED
C9F0: 434 * IS RETURNED AS A 1 IN A BIT IN THE ACCUM
C9F0: 435 *
C9F0: 436 *****
C9F0:48 437 BASCLC PHA
C9F1:29 C0 438 AND #C0
C9F3:85 2A 439 STA HBASL
C9F5:4A 440 LSR A
C9F6:4A 441 LSR A
C9F7:05 2A 442 ORA HBASL
C9F9:85 2A 443 STA HBASL
C9FB:68 444 PLA
C9FC:4C 0C CA 445 JMP C2SKP
CA00: 446 ORG #200+QTHROM
CA00:18 447 CLC
CA01:80 448 DFB #80
CA02:38 449 SEC
CA03:88 450 CLV
CA04:08 451 PHP
CA05:78 452 SEI
CA06:2C FF CF 453 BIT ROMSW
CA09:20 00 CB 454 JSR QTHROM
CA0C:85 28 455 C2SKP STA HBASH
CA0E:0A 456 ASL A
CA0F:0A 457 ASL A
CA10:0A 458 ASL A
CA11:26 28 459 ROL HBASH
CA13:0A 460 ASL A
CA14:26 28 461 ROL HBASH
CA16:0A 462 ASL A
CA17:66 2A 463 ROR HBASL
CA19:A5 28 464 LDA HBASH
CA1B:29 1F 465 AND #1F
CA1D:85 28 466 STA HBASH
CA1F:8A 467 TXA
CA20:AC 86 02 468 LDY TEMX
CA23:C0 00 469 CPY #0
CA25:F0 05 470 BEQ HPOSN2
CA27:A0 23 471 LDY #23
CA29:69 04 472 ADC #4

```

```

CA23: C8      473 HPOSN1  INY
CA2C: E9 07   474 HPOSN2  SBC  #17
CA2E: B0 FB   475        BCS  HPOSN1
CA30: A9 08   476        ADC  #18
CA32: BC 78 06 477        STY  HNDX
CA35: A8      478        TAY
CA36: A9 00   479        LDA  #10
CA3B: 3B      480        SEC
CA39: 2A      481 CLOOP    ROL  A
CA3A: 8B      482        DEY
CA3B: D0 FC   483        BNE  CLOOP
CA3D: AC FB 07 484        LDY  MSLOT
CA40: 4B      485        PHA
CA41: B9 BB 03 486        LDA  PAGE, Y
CA44: 29 60   487        AND  #160
CA46: 05 2B   488        ORA  HBASH
CA48: B5 2B   489        STA  HBASH
CA4A: 6B      490        PLA
CA4B: 60      491        RTS
CA4C:      492        CHN  BITPAD35, 2P
CA4C:      2 *****
CA4C:      3 *
CA4C:      4 * WINDOW CHECK SUBROUTINE
CA4C:      5 *
CA4C:      6 * ENTER WITH LO BYTE OF Y IN ACCUM
CA4C:      7 * AND LO BYTE OF X IN X-REG
CA4C:      8 *
CA4C:      9 * RETURN WILL BE CARRY CLEAR IF
CA4C:     10 * WITHIN WINDOW AND CARRY SET IF
CA4C:     11 * OUTSIDE.
CA4C:     12 *
CA4C:     13 *****
CA4C: 4B      14 WINCHK    PHA
CA4D: C9 C0   15        CMP  #192
CA4F: B0 16   16        BCS  NO
CA51: AD 86 02 17        LDA  TEMX
CA54: F0 09   18        BEQ  YES
CA56: C9 02   19        CMP  #12
CA5B: B0 0D   20        BCS  NO
CA5A: BA      21        TXA
CA5B: C9 1B   22        CMP  #24
CA5D: B0 0B   23        BCS  NO
CA5F: AD 8B 02 24 YES    LDA  TEMY
CA62: D0 03   25        BNE  NO
CA64: 1B      26        CLC
CA65: 6B      27        PLA
CA66: 60      28        RTS
CA67: 3B      29 NO      SEC
CA6B: 6B      30        PLA
CA69: 60      31        RTS
CA6A:      32 *****
CA6A:      33 *
CA6A:      34 *
CA6A:      35 * ASCII CONVERSION
CA6A:      36 * ENTER WITH HIGH BYTE
CA6A:      37 * IN Y-REG, LOW BYTE IN ACCUM
CA6A:      38 * AND INPUT BUFFER OFFSET
CA6A:      39 * IN X-REG
CA6A:      40 *
CA6A:      41 *****
CA6A: 4B      42 ASCON     PHA
CA6B: 9B      43        TYA
CA6C: 10 12   44        BPL  POSIT
CA6E: 4B      45        PHA
CA6F: A9 AD   46        LDA  #1AD
CA71: 9D 00 02 47        STA  INO, X
CA74: 6B      48        PLA
CA75: B6 2A   49        STX  HBASL
CA77: AA      50        TAX
CA7B: 6B      51        PLA
CA79: 20 5B CB 52        JSR  TWOCON
CA7C: 4B      53        PHA
CA7D: BA      54        TXA
CA7E: A6 2A   55        LDX  HBASL

```

```

CAB0: A8      56 POSIT    TAY
CAB1: EB      57        INX
CAB2: 6B      58        PLA
CAB3: 3B      59        SEC
CAB4: B0 03   60        BCS  ASKIP
CAB6: FE 00 02 61 FLOOP    INC  INO, X
CAB9: E9 EB   62 ASKIP    SBC  #EB
CABB: 4B      63        PHA
CABC: 9B      64        TYA
CABD: E9 03   65        SBC  #3
CABF: AB      66        TAY
CA90: 6B      67        PLA
CA91: B0 F3   68        BCS  FLOOP
CA93: 69 EB   69        ADC  #EB
CA95: 4B      70        PHA
CA96: 9B      71        TYA
CA97: 69 03   72        ADC  #3
CA99: AB      73        TAY
CA9A: 6B      74        PLA
CA9B: B0 03   75        BCS  BSKIP
CA9D: FE 01 02 76 HLOOP    INC  IN1, X
CAA0: 3B      77 BSKIP    SEC
CAA1: E9 64   78        SBC  #64
CAA3: B0 FB   79        BCS  HLOOP
CAA5: 8B      80        DEY
CAA6: 10 F5   81        BPL  HLOOP
CAAB: 1B      82        CLC
CAA9: CB      83        INY
CAAA: 69 64   84        ADC  #64
CAAC: 3B      85        SEC
CAAD: B0 03   86        BCS  CSKIP
CAAF: FE 02 02 87 JLOOP    INC  IN2, X
CAB2: E9 0A   88 CSKIP    SBC  #A
CAB4: B0 F9   89        BCS  JLOOP
CAB6: 69 0A   90        ADC  #A
CAB8: B0 03   91        BCS  DSKIP
CABA: FE 03 02 92 KLOOP    INC  IN3, X
CABD: E9 01   93 DSKIP    SBC  #1
CABF: B0 F9   94        BCS  KLOOP
CAC1: 60      95 RTN      RTS
CAC2:      96 *****
CAC2:      97 *
CAC2:      98 *
CAC2:      99 * OFFSET AND DIVIDE ROUTINE
CAC2:     100 *
CAC2:     101 * ENTER WITH OFFSET IN REGH
CAC2:     102 * AND REGL, VALUE TO SCALE IN
CAC2:     103 * X (HIGH BYTE) AND A (LOW BYTE)
CAC2:     104 * SCALE (INTEGER DIVISOR) IN
CAC2:     105 * DIVH AND DIVL
CAC2:     106 *
CAC2:     107 * RESULT IN REGH AND REGL
CAC2:     108 * VALUE MAY BE +OR-32767
CAC2:     109 * SCALE 0 TO +32767
CAC2:     110 * RESULT IS TWOS COMPLEMENT
CAC2:     111 * REMAINDER IS LOST
CAC2:     112 *
CAC2:     113 *****
CAC2: AC FB 07 114 OFFDIV    LDY  MSLOT
CAC5: 4B      115        PHA
CAC6: B9 3B 04 116        LDA  MPAGE, Y
CAC9: 0A      117        ASL  A
CACA: 30 05   118        BMI  DIVIDE
CACC: 6B      119        PLA
CACD: 20 64 CB 120        JSR  OFFSET
CADO: 4B      121        PHA
CAD1: B8      122 DIVIDE    CLV
CAD2: A0 00   123        LDY  #0
CAD4: AD A4 02 124        LDA  DIVH
CAD7: CB      125 LOOP1    INY
CADB: 0E A3 02 126        ASL  DIVL
CADB: 2A      127        ROL  A
CADC: 10 F9   128        BPL  LOOP1
CADE: BD A4 02 129        STA  DIVH

```


CAE1: A9 00	130	LDA	##0
CAE3: 8D 8B 02	131	STA	REGH
CAE6: 8D 87 02	132	STA	REGL
CAE9: 68	133	PLA	
CAEA: E8	134	INX	
CAEB: CA	135	DEX	
CAEC: 08	136	PHP	
CAED: 10 03	137	BPL	POS
CAEF: 20 58 CB	138	JSR	TWOCOM
CAF2: 38	139	SEC	
CAF3: ED A3 02	140	SBC	DIVL
CAF6: 48	141	PHA	
CAF7: 8A	142	TXA	
CAF8: ED A4 02	143	SBC	DIVH
CAF8: AA	144	TAX	
CAFC: 68	145	PLA	
CAFD: 4C 0C CB	146	JMP	LOOP3
CB00:	147	ORG	*300+OTHRM
CB00: 18	148	CLC	
CB01: 80	149	DFB	*80
CB02: 38	150	SEC	
CB03: 88	151	CLV	
CB04: 08	152	PHP	
CB05: 78	153	SEI	
CB06: 2C FF CF	154	BIT	ROMSW
CB09: 20 00 CB	155	JSR	OTHRM
CB0C: 08	156	PHP	
CB0D: 2E 87 02	157	ROL	REGL
CB10: 2E 88 02	158	ROL	REGH
CB13: 88	159	DEY	
CB14: 30 16	160	BMI	FEXIT
CB16: 4E A4 02	161	LSR	DIVH
CB19: 6E A3 02	162	ROR	DIVL
CB1C: 28	163	PLP	
CB1D: 80 D4	164	BCS	LOOP2
CB1F: 6D A3 02	165	ADC	DIVL
CB22: 48	166	PHA	
CB23: 8A	167	TXA	
CB24: 6D A4 02	168	ADC	DIVH
CB27: AA	169	TAX	
CB28: 68	170	PLA	
CB29: 4C 0C CB	171	JMP	LOOP3
CB2C: 28	172	PLP	
CB2D: 28	173	PLP	
CB2E: 10 0F	174	BPL	EEXIT
CB30: AD 87 02	175	LDA	REGL
CB33: AE 88 02	176	LDX	REGH
CB36: 20 58 CB	177	JSR	TWOCOM
CB39: 8E 88 02	178	STX	REGH
CB3C: 8D 87 02	179	STA	REGL
CB3F: AC F8 07	180	LDY	MSLOT
CB42: B9 38 04	181	LDA	MPAGE, Y
CB45: 0A	182	ASL	A
CB46: 10 0F	183	BPL	EEXIT
CB48: AD 87 02	184	LDA	REGL
CB4B: AE 88 02	185	LDX	REGH
CB4E: 20 64 CB	186	JSR	OFFSET
CB51: 8D 87 02	187	STA	REGL
CB54: 8E 88 02	188	STX	REGH
CB57: 60	189	RTS	
CB58: 49 FF	190	EOR	##FF
CB5A: 18	191	CLC	
CB5B: 69 01	192	ADC	##1
CB5D: 48	193	PHA	
CB5E: 8A	194	TXA	
CB5F: 49 FF	195	EOR	##FF
CB61: AA	196	TAX	
CB62: 68	197	PLA	
CB63: 60	198	RTS	
CB64: 38	199	SEC	
CB65: ED A1 02	200	SBC	DIVL
CB68: 48	201	PHA	
CB69: 8A	202	TXA	

*C300 SPACE ENTRY

CB6A: ED A2 02	203	SBC	DIVH
CB6D: AA	204	TAX	
CB6E: 68	205	PLA	
CB6F: 60	206	RTS	
CB70:	208	*****	
CB70:	209	*	
CB70:	210	* SCALE ROUTINE	
CB70:	211	*	
CB70:	212	* VALUES IN -FL- REGISTERS CONVERTED	
CB70:	213	* TO SCALED VALUES IN TEM- REGISTERS	
CB70:	214	*	
CB70:	215	*****	
CB70: AC F8 07	216	SCALE	LDY
CB73: B9 88 04	217		MSLOT
CB76: 8D A3 02	218		LDA
CB79: B9 38 05	219		SCALL, Y
CB7C: 8D A4 02	220		STA
CB7F: B9 88 05	221		DIVL
CB82: 8D A1 02	222		LDA
CB85: B9 38 06	223		SCALL, Y
CB88: 8D A2 02	224		STA
CB8B: AD 91 02	225		DIVH
CB8E: AE 82 02	226		LDA
CB91: 20 C2 CA	227		OFFXL, Y
CB94: AC F8 07	228		STA
CB97: AD 87 02	229		DIVH
CB9A: 8D 85 02	230		LDA
CB9D: AD 88 02	231		OFFXL, Y
CB9F: 8D 86 02	232		STA
CB9A: B9 88 06	233		DIVH
CB96: 8D A1 02	234		LDA
CB99: B9 38 07	235		OFFXL, Y
CB9C: 8D A2 02	236		STA
CB9F: AD 83 02	237		DIVH
CB82: AE 84 02	238		LDA
CB85: 20 C2 CA	239		OFFXL, Y
CB88: 60	240		STA
CB89:	242		DIVH
CB89:	243		LDX
CB89:	244		YFLH
CB89:	245		JSR
CB89:	246		OFFDIV
CB89:	247		LDY
CB89:	248		MSLOT
CB89:	249		LDA
CB89:	250		TEMYL
CB89:	251		STA
CB89: 20 F4 CB	252		TEMYL
CB8C: 90 12	253		STA
CB8E: 2C 00 C0	254		TEMY
CB81: 30 03	255		STA
CB83: 4C B9 CB	256		TEMX
CB86: 48	257		LDA
CB87: AD 80 02	258		OFFYL, Y
CB8A: 09 08	259		STA
CB8C: 8D 80 02	260		DIVH
CB8F: 68	261		LDA
CB8D: 48	262		OFFYL, Y
CB81: 4D 80 02	263		STA
CB84: 6A	264		DIVH
CB85: 90 05	265		LDA
CB87: A9 50	266		OFFYL, Y
CB89: 20 A1 CC	267		STA
CB8C: 68	268		DIVH
CB8D: 6A	269		LDA
CB8E: AD 80 02	270		OFFYL, Y
CB81: 2A	271		STA
CB82: 29 13	272		DIVH
CB84: 8D 80 02	273		LDA
CB87: 4E 84 02	274		OFFYL, Y
CB8A: 6E 83 02	275		STA
CB8D: 4E 82 02	276		DIVH
CB8F: 6E 81 02	277		LDA

CBF3: 60	278	RTS	
CBF4: AD F8 07	279	LDA	MSLOT
CBF7: 0A	280	ASL	A
CBF8: 0A	281	ASL	A
CBF9: 0A	282	ASL	A
CBFA: 0A	283	ASL	A
CBFB: AA	284	TAX	
CBFC: A0 03	285	LDY	#53
CBFE: D0 0C	286	BNE	C4SKP
CC00:	287	ORG	\$400+QTHROM
CC00: 18	288	CLC	
CC01: B0	289	DFB	\$B0 ; \$C400 SPACE ENTRY
CC02: 38	290	SEC	
CC03: 88	291	CLV	
CC04: 08	292	PHP	
CC05: 78	293	SEI	
CC06: 2C FF CF	294	BIT	RDMSW
CC09: 20 00 C8	295	JSR	QTHROM
CC0C: A9 00	296	LDA	#50
CC0E: 99 81 02	297	STA	XFLH, Y
CC11: 88	298	DEY	
CC12: 10 FA	299	BPL	ZDLOOP
CC14: A0 06	300	LDY	#56
CC16: 8C 78 06	301	STY	HNDX
CC19: 20 83 CC	302	JSR	RESLP
CC1C: 8D 81 C0	303	LDA	DEVO, X
CC1F: 20 42 CC	304	JSR	READTAB
CC22: 80 1D	305	BCS	OFFSC
CC24: A0 02	306	LDY	#52
CC26: 20 8E CC	307	JSR	AMOVE
CC29: 20 83 CC	308	JSR	RESLP
CC2C: 8D 80 C0	309	LDA	DEV1, X
CC2F: 20 42 CC	310	JSR	READTAB
CC32: 80 0D	311	BCS	OFFSC
CC34: 48	312	PHA	
CC35: A0 00	313	LDY	#50
CC37: 20 8E CC	314	JSR	AMOVE
CC3A: 68	315	PLA	
CC3B: CE 78 06	316	DEC	HNDX
CC3E: D0 D9	317	BNE	RDLOOP
CC40: 18	318	CLC	
CC41: 60	319	RTS	
CC42: A9 12	320	LDA	#512
CC44: E9 01	321	SBC	#51
CC46: D0 FC	322	BNE	ALDOP
CC48: 8D 82 C0	323	LDA	DEV3, X
CC4B: 0A	324	ASL	A
CC4C: 0A	325	ASL	A
CC4D: 0A	326	ASL	A
CC4E: 0A	327	ASL	A
CC4F: A9 70	328	EOR	#570
CC51: 29 F0	329	AND	#5F0
CC53: 8D 87 02	330	STA	TEMYL
CC56: 8D 83 C0	331	LDA	DEV2, X
CC59: 8D 88 02	332	STA	TEMY
CC5C: A9 60	333	LDA	#560
CC5E: E9 01	334	SBC	#51
CC60: D0 FC	335	BNE	AILOOP
CC62: A0 04	336	LDY	#54
CC64: 4E 88 02	337	LSR	TEMY
CC67: 6E 87 02	338	ROR	TEMYL
CC6A: 88	339	DEY	
CC6B: D0 F7	340	BNE	DLOOP
CC6D: AD 88 02	341	LDA	TEMY
CC70: D0 07	342	BNE	ATST
CC72: A9 60	343	LDA	#560
CC74: CD 87 02	344	CMP	TEMYL
CC77: 90 02	345	BCC	BTST
CC79: C9 0A	346	CMP	#50A
CC7B: 8D 82 C0	347	LDA	DEV3, X
CC7E: A9 01	348	EOR	#51
CC80: 29 01	349	AND	#51
CC82: 60	350	RTS	

CC83: AD FB 07	351	RESLP	LDA	MSLOT
CC86: 48	352		PHA	
CC87: A9 03	353		LDA#53	
CC89: 48	354		PHA	
CC8A: 2C 41 CC	355		BIT	OFFSC
CC8D: 60	356		RTS	
CC8E: AD 87 02	357	AMOVE	LDA	TEMYL
CC91: 79 81 02	358		ADC	XFLH, Y
CC94: 99 81 02	359		STA	XFLH, Y
CC97: AD 88 02	360		LDA	TEMY
CC9A: 79 82 02	361		ADC	XFLH, Y
CC9D: 99 82 02	362		STA	XFLH, Y
CCAD: 60	363		RTS	
CCA1: 38	364	QWAIT	SEC	
CCA2: 48	365	Q2WAIT	PHA	
CCA3: E9 01	366	Q3WAIT	SBC	#51
CCA5: D0 FC	367		BNE	Q3WAIT
CCA7: 68	368		PLA	
CCAB: E9 01	369		SBC	#51
CCAA: D0 F6	370		BNE	Q2WAIT
CCAC: 60	371		RTS	
CCAD:	373	*****		
CCAD:	374	*		
CCAD:	375	* CHARACTER ENTRY SEQUENCE		
CCAD:	376	*		
CCAD:	377	* CHARACTER STRING ANALYSIS		
CCAD:	378	* S... NNNN SET SCALE FACTOR TO NNNN		
CCAD:	379	* X... NNNN SET X OFFSET TO NNNN		
CCAD:	380	* Y... NNNN SET Y OFFSET TO NNNN		
CCAD:	381	* M... (1 OR 2) SET MIXED HIRES MODE		
CCAD:	382	* H... (1 OR 2) SET HIRES MODE		
CCAD:	383	* G... (1 OR 2) SET MIXED LORES MODE		
CCAD:	384	* L... (1 OR 2) SET LORES MODE		
CCAD:	385	* T... (1 OR 2) SET TEXT MODE		
CCAD:	386	* N... SUPPRESS ALL PRINTING		
CCAD:	387	* D... RESTORE DEFAULT PARAMETERS		
CCAD:	388	* C... NO CURSOR		
CCAD:	389	* F... DATA RETURNED UNSCALED		
CCAD:	390	* R... DATA RETURNED SCALED		
CCAD:	391	* P... STREAM MODE ON		
CCAD:	392	* G... STREAM MODE OFF (DEFAULT)		
CCAD:	393	* A... OFFSET AFTER SCALE		
CCAD:	394	* B... OFFSET BEFORE SCALE (DEFAULT)		
CCAD:	395	*		
CCAD:	396	*****		
CCAD: 28	397	SYNTAX	PLP	
CCAE: 80 0C	398		BCS	SYNT1
CCB0: A9 00	399		LDA	#50
CCB2: 8D 98 02	400		STA	INX
CCB5: 8D 99 02	401		STA	NFLAG
CCB8: A9 02	402		LDA	#52
CCBA: 85 36	403		STA	COUTL
CCBC: AD FB 06	404	SYNT1	LDA	CHAR
CCBF: C9 AD	405		CMP	#5AD
CCC1: D0 03	406		BNE	SYNT2
CCC3: 8D A0 02	407		STA	NIFLAG
CCC6: C9 A0	408	SYNT2	CMP	#5A0
CCC8: F0 29	409		BEQ	EXIT4
CCCA: C9 AC	410		CMP	#5AC
CCC0: F0 28	411		BEQ	PROC1
CCCE: C9 8D	412		CMP	#5BD
CCD0: F0 26	413		BEQ	PROC2
CCD2: 08	414		PHP	
CCD3: AE 98 02	415		LDX	INX
CCD6: F0 0C	416		BEQ	CHOUT
CCD8: 49 80	417		EOR	#580
CCDA: C9 0A	418		CMP	#5A
CCDC: 90 06	419		BCC	CHOUT
CCDE: E0 01	420		CPX	#51
CCEO: F0 10	421		BEQ	EXIT3
CCER: D0 6C	422		BNE	ERR1
CEE4: E0 06	423	CHOUT	CPX	#56
CEE6: 80 68	424		BCS	ERR1

CCB:AD	F8 06	425	LDA	CHAR	
CCB:9D	90 02	426	STA	INA, X	:SAVE THE CHAR IN THE BUFFER
CEE:EB		427	INX		:UPDATE THE BUFFER INDEX
CEF:BE	98 02	428	STX	INX	
CF2:28		429	PLP		:RESTORE STATUS
CF3:4C	86 CB	430	JMP	EXIT	:GOTO EXIT
CF6:38		431	SEC		:SET CARRY IF A COMMA
CF7:90		432	DFB	#90	:BCS ALWAYS
CF8:18		433	CLC		:CLEAR CARRY IF A CR
CF9:08		434	PHP		:SAVE THE CARRY
CCA:AD	90 02	435	LDA	INA	
CCD:4C	0C CD	436	JMP	C5SKP	
CD00:		437	ORG	#500+OTHRM	
CD00:18		438	CLC		:%C500 SPACE ENTRY
CD01:80		439	DFB	#80	
CD02:38		440	SEC		
CD03:88		441	CLV		
CD04:08		442	PHP		
CD05:78		443	SEI		
CD06:2C	FF CF	444	BIT	ROMSW	
CD09:20	00 CB	445	JSR	OTHRM	
CD0C:A0	12	446	LDY	#12	
CD0E:88		447	DEY		
CD0F:F0	3F	448	BEG	ERR1	
CD11:D9	5C CE	449	CMP	TABL-1, Y	
CD14:D0	F8	450	BNE	ALPH1	
CD16:A9	CD	451	LDA	#CROUTIN	
CD18:48		452	PHA		
CD19:B9	6D CE	453	LDA	ADR-1, Y	
CD1C:48		454	PHA		
CD1D:B9	7E CE	455	LDA	PARAM-1, Y	
CD20:AC	98 02	456	LDY	INX	
CD23:60		457	RTS		:JUMP TO ROUTINE WITH RTS
CD24:C0	01	458	CPY	#1	
CD26:D0	28	459	BNE	ERR1	
CD28:C9	CE	460	CMP	#CE	
CD2A:D0	05	461	BNE	ROUT1	
CD2C:BD	99 02	462	STA	NFLAG	
CD2F:F0	18	463	BEG	EXIT5	
CD31:AE	F8 07	464	LDX	MSLOT	
CD34:C9	C4	465	CMP	#C4	
CD36:D0	05	466	BNE	ROUT2	
CD38:20	90 CE	467	JSR	DEFAULT	
CD3B:D0	0F	468	BNE	EXIT5	
CD3D:1E	88 03	469	ASL	PAGE, X	
CD40:48		470	PHA		
CD41:68		471	PLA		
CD42:F0	04	472	DEG	NDCRS	
CD44:0A		473	ASL	A	
CD45:BD	88 03	474	LDA	PAGE, X	
CD48:6A		475	ROR	A	
CD49:9D	88 03	476	STA	PAGE, X	
CD4C:4C	0C CE	477	JMP	EXIT1	
CD4F:68		478	PLA		
CD50:20	93 FE	479	JSR	SETVID	
CD53:A0	19	480	LDY	#19	
CD55:B9	43 CE	481	LDA	STRIN-1, Y	
CD58:20	ED FD	482	JSR	COUT	
CD5B:88		483	DEY		
CD5C:D0	F7	484	BNE	MSG1	
CD5E:A0	51 C0	485	LDA	STEXT	
CD61:AD	54 C0	486	LDA	SPAQ1	
CD64:4C	0C CE	487	JMP	EXIT1	
CD67:C0	02	488	CPY	#2	
CD69:D0	E5	489	BNE	ERR1	
CD6B:48		490	PHA		
CD6C:AD	91 02	491	LDA	INA+1	
CD6F:49	80	492	EOR	#80	
CD71:F0	DC	493	BEG	ERR3	
CD73:C9	03	494	CMP	#3	
CD75:80	D8	495	BCS	ERR3	
CD77:6A		496	ROR	A	
CD78:68		497	PLA		



CD79:80	01	498	BCS	NOROL	
CD7B:2A		499	ROL	A	
CD7C:AE	F8 07	500	NOROL	LDX	MSLOT
CD7F:1E	88 03	501	ASL	PAGE, X	
CD82:6A		502	ROR	A	
CD83:20	BE CE	503	JSR	STMODE	
CD86:4C	0C CE	504	JMP	EXIT1	
CD89:85	28	505	STA	HBASH	
CD8B:A9	88	506	LDA	#88	
CD8D:85	2A	507	STA	HBASL	
CD8F:88		508	DEY		
CD90:B9	90 02	509	LDX	INA, Y	
CD93:49	80	510	EOR	#80	
CD95:C9	0A	511	CMP	#A	
CD97:80	87	512	BCS	ERR1	
CD99:99	90 02	513	STA	INA, Y	
CD9C:88		514	DEY		
CD9D:D0	F1	515	BNE	DIGLP	
CD9F:A2	00	516	LDX	#0	
CDA1:C8		517	INX		
CDA2:8D	78 05	518	STA	TEMPL	
CDA5:8E	F8 03	519	STX	TEMPH	
CDA8:C8		520	INX		
CDA9:CC	98 02	521	CPY	INX	
CDAC:F0	1D	522	BEG	DIG3	
CDAE:A9	0A	523	LDA	#A	
CD80:BD	A5 02	524	STA	COUNT	
CD83:A2	00	525	LDX	#0	
CD85:B9	90 02	526	LDA	INA, Y	
CD88:6D	78 05	527	ADC	TEMPL	
CD8B:48		528	PHA		
CD8C:8A		529	TXA		
CD8D:6D	F8 05	530	ADC	TEMPH	
CD8F:30	8E	531	BMI	ERR1	
CDC2:AA		532	TAX		
CDC3:68		533	PLA		
CDC4:CE	A5 02	534	DEC	COUNT	
CDC7:D0	EF	535	BNE	DIG1	
CDC9:F0	D7	536	BEG	DIG2	
CDCB:A4	28	537	LDY	HBASH	
CDCD:C0	04	538	CPY	#4	
CDCF:F0	08	539	BEG	DIG4	
CDD1:AC	A0 02	540	LDY	MIFLAG	
CDD4:F0	03	541	BEGDIG4		
CDD6:20	58 CB	542	JSR	TWOCOM	
CDD9:AC	F8 07	543	LDY	MSLOT	
CDDC:91	2A	544	STA	(HBASL), Y	
CDDE:A9	38	545	LDA	#38	
CDE0:85	2A	546	STA	HBASL	
CDE2:E6	28	547	INC	HBASH	
CDE4:8A		548	TXA		
CDE5:91	2A	549	STA	(HBASL), Y	
CDE7:4C	0C CE	550	JMP	EXIT1	
CDEA:AC	F8 07	551	LDY	MSLOT	
CDED:48		552	PHA		
CDEE:6A		553	ROR	A	
CDEF:68		554	PLA		
CDFO:90	05	555	BCC	CROUT2	
CDF2:39	38 04	556	AND	MPAGE, Y	
CDF5:80	03	557	BCS	CROUT3	
CDF7:19	38 04	558	ORA	MPAGE, Y	
CDFA:99	38 04	559	STA	MPAGE, Y	
CDFD:4C	0C CE	560	JMP	EXIT1	
CE00:		561	ORG	#600+OTHRM	
CE00:18		562	CLC		:%C600 SPACE ENTRY
CE01:80		563	DFB	#80	
CE02:38		564	SEC		
CE03:88		565	CLV		
CE04:08		566	PHP		
CE05:78		567	SEI		
CE06:2C	FF CF	568	BIT	ROMSW	
CE09:20	00 CB	569	JSR	OTHRM	
CE0C:A9	00	570	LDA	#0	

CE0E: 8D A0 02	571	STA	MIFLAG
CE11: 8D 98 02	572	STA	INX
CE14: AC F8 07	573	LDY	MSLOT
CE17: 89 38 04	574	LDA	MPAGE, Y
CE1A: 29 C0	575	AND	#C0
CE1C: 99 38 04	576	STA	MPAGE, Y
CE1F: 89 88 03	577	LDA	PAGE, Y
CE22: 29 3F	578	AND	#3F
CE24: 49 25	579	EOR	#25
CE26: 19 38 04	580	ORA	MPAGE, Y
CE29: 99 38 04	581	STA	MPAGE, Y
CE2C: 28	582	PLP	
CE2D: 80 12	583	BCS	EXIT2
CE2F: AD 99 02	584	LDA	NFLAG
CE32: F0 0A	585	BEG	PRINT
CE34: A9 58	586	LDA	#IORTS
CE36: 85 36	587	STA	COUTL
CE38: A9 FF	588	LDA	#IORTS/256
CE3A: 85 37	589	STA	COUTH
CE3C: D0 03	590	DNE	EXIT2
CE3E: 20 93 FE	591	JSR	SETVID
CE41: 4C 86 C8	592	JMP	EXIT
CE44: 8D	593	DFB	#8D
CE45: D2 CF D2	594	ASC	"RORRE
CE48: D2 C5 A0			XATNYS TELBAT ***"
CE4B: D8 C1 D4			
CE4E: CE D9 D3			
CE51: A0 D4 C5			
CE54: C0 C2 C1			
CE57: D4 A0 AA			
CE5A: AA AA 87			
CE5D: D0 D1 C1	595	TABL	ASC
CE60: C2 D3 D8			"PGABXVTMHLGCFRND"
CE63: D9 D4 CD			
CE66: C8 CC C7			
CE69: C3 C6 D2			
CE6C: CE C4			
CE6E: E9	596	ADR	DFB
CE6F: E9	597		CROUT-1
CE70: E9	598		DFB
CE71: E9	599		CROUT-1
CE72: 88	600		DFB
CE73: 88	601		BROUT-1
CE74: 88	602		DFB
CE75: 66	603		BROUT-1
CE76: 66	604		DFB
CE77: 66	605		AROUT-1
CE78: 66	606		DFB
CE79: 66	607		AROUT-1
CE7A: 23	608		DFB
CE7B: 23	609		ROUTIN-1
CE7C: 23	610		DFB
CE7D: 23	611		ROUTIN-1
CE7E: 23	612		DFB
CE7F: 80	613	PARAM	ROUTIN-1
CE80: 7F	614		DFB
CE81: 40	615		#80
CE82: 8F	616		DFB
CE83: 04	617		#7F
CE84: 05	618		DFB
CE85: 06	619		#40
CE86: 08	620		DFB
CE87: 48	621		#8F
CE88: 40	622		DFB
CE89: 02	623		#04
CE8A: 0A	624		DFB
CE8B: 00	625		#05
CE8C: 01	626		DFB
CE8D: 80	627		#06
CE8E: CE	628		DFB
CE8F: C4	629		#08
			DFB
			#48
			DFB
			#40
			DFB
			#02
			DFB
			#0A
			DFB
			#0
			DFB
			#01
			DFB
			#80
			DFB
			#CE
			DFB
			#C4

CE90:	631	*****
CE90:	632	*****
CE90:	633	*
CE90:	634	* DEFAULT
CE90:	635	*
CE90:	636	* SCALE = 16
CE90:	637	* X OFFSET = 1536
CE90:	638	* Y OFFSET = 1536
CE90:	639	* HIRES PAGE 2
CE90:	640	* PRINT ON
CE90:	641	* CURSOR ON
CE90:	642	* STREAM MODE OFF
CE90:	643	* DATA RETURNED UNSCALED
CE90:	644	* OFFSET BEFORE SCALE
CE90:	645	*
CE90:	646	*****
CE90:	647	*****
CE90: A9 10	648	DEFAULT LDA #10
CE92: 9D 88 04	649	STA SCALL, X
CE95: A9 00	650	LDA #0
CE97: 9D 38 05	651	STA SCALH, X
CE9A: 9D 88 05	652	STA OFFXL, X
CE9D: 9D 88 06	653	STA OFFYL, X
CEA0: 8D 98 02	654	STA INX
CEA3: A9 03	655	LDA #3
CEA5: 8D 80 02	656	STA TEM
CEA8: A9 06	657	LDA #6
CEAA: 9D 38 06	658	STA OFFXH, X
CEAD: 9D 38 07	659	STA OFFYH, X
CEB0: 2C 10 C0	660	BIT KBDSTRB
CEB3: 20 F4 C8	661	JSR MIREAD
CEB6: 20 D0 C8	662	JSR SWCHK
CEB9: AE F8 07	663	LDX MSLOT
CEBC: A9 40	664	LDA #40
CEBE: AB	665	STMODE TAY
CEBF: 8D 92 C0	666	STA SNMIX
CEC2: 8D 57 C0	667	STA SHIRES
CEC5: 8D 51 C0	668	STA STEXT
CEC8: 8D 54 C0	669	STA SPAG1
CECB: 29 0C	670	AND #0C
CECD: F0 03	671	BEG DEF1
CECF: 8D 33 C0	672	STA SMIX
CE02: 98	673	DEF1 TYA
CE03: 29 63	674	AND #63
CE05: F0 03	675	BEG DEF2
CE07: AD 30 C0	676	LDA SGR
CE0A: 98	677	DEF2 TYA
CE0B: 29 4A	678	AND #4A
CE0D: F0 03	679	BEG DEF3
CE0F: AD 55 C0	680	LDA SPAG2
CEE2: 98	681	DEF3 TYA
CEE3: 29 03	682	AND #03
CEE5: F0 03	683	BEG DEF4
CEE7: 8D 56 C0	684	STA SLORES
CEEA: 98	685	DEF4 TYA
CEEB: 9D 88 03	686	STA PAGE, X
CEEE: 29 3F	687	AND #3F
CEFO: 49 25	688	EOR #25
CEF2: 9D 38 04	689	STA MPAGE, X
CEF5: 60	690	RTS
CEF6:	691	*****
CEF6:	692	*
CEF6:	693	* JUMP TABLE
CEF6:	694	*
CEF6:	695	*****
CEF6:	696	ORG \$6F6+QTHROM
CEF6: 4C 4C CA	697	JWINCHK JMP WINCHK
CEF9: 4C 89 C8	698	JMREAD JMP MREAD
CEFC: 4C 70 C8	699	JSCALE JMP SCALE

*** SUCCESSFUL ASSEMBLY: NO ERRORS

CC8E AIL00P
 CB09 ADTHROM
 CB00 ASC1EX
 CC79 ATST
 CB89 BROUT
 C90C C1SKP
 ?C918 CALLCURS
 CA39 CLOOP
 3A COUTL
 C9AD C
 C989 CTRL00P
 CEEA DEF4
 C0B3 DEV2
 CDA2 DIQ2
 CDA4 DIVH
 CABD DSKIP
 CD55 EMSQ1
 CD50 ERR1
 CD4C EXIT5
 CB2C FEXIT
 CB90 GLOOP
 2A HBASL
 CA2B HPOSN1
 C202 IN2
 CB83 INEX2
 FF5B IORTS
 ?CEFC JWINCHK
 C9DE LOCLC
 CB0C L00P3
 CBF4 M1READ
 CB89 MREAD
 CD4B NDCRS
 CAC2 OFFDIV
 C63B OFFXH
 C2A2 OREGH
 C99E OUTSIDE
 ?C902 POINT
 CE3E PRINT
 CC42 READTAB
 CFFF ROMSW
 ?CAC1 RTN
 C43B SCALL
 C056 SLORES
 C055 SPAG2
 CBDO SWCHK
 CE5D TABL
 C2B6 TEMX
 C936 TEXT
 C2B1 XFLL
 C00E ZDLOOP
 24 CH
 36 COUTL
 C202 IN2
 C2B2 XFLH
 C2B6 TEMX
 C2B9 REGH
 C29B SAVSLOT
 C2A3 DIVL
 C3B8 PAGE
 C57B TEMPL
 C67B HNDX
 C7F8 MSLOT
 C051 STXT
 C055 SPAG2
 C0B1 DEVO
 CB09 ADTHROM
 CB6B E1PNT
 CB86 EXIT
 CBDO ASC1EX
 C90C C1SKP
 C94E OUT1
 C971 HIRES
 C9AD C

CE6E ADR
 CD67 AROUT
 CB66 ASCEX
 C9C4 B
 CAA0 BSKIP
 CA0C C2SKP
 CCE4 CHOUT
 C2A5 COUNT
 CDF7 CROUT2
 CDEA CROUT
 CED2 DEF1
 CE90 DEFAULT
 C0B2 DEV3
 CDCB DIQ3
 CAD1 DIVIDE
 CB57 E1EXIT
 ?CD53 EMSQ
 CD4F ERR3
 CB86 EXIT
 CAB6 FLOOP
 C951 GR
 C971 HIRES
 CA2C HPOSN2
 C203 IN3
 CB8C INEXIT
 CAAF JL00P
 C000 KBD
 C980 LOOP
 ?CB1F LOOP4
 C2A0 MIFLAG
 C7F8 MSLOT
 CB34 NDCRS
 CB66 OFFS1
 C5B8 OFFXL
 C2A1 OREGH
 C9DO OUT
 CAB0 PG3IT
 CCF6 PROC1
 C2B8 REGH
 CD31 ROUT1
 C29B SAVSLOT
 FE93 SETVID
 C053 SMIX
 C051 STXT
 CB8C SYNT1
 C57B TEMPL
 C2B7 TEMYL
 CB5B TWOCOM
 CA5F YES
 2B BASL
 37 COUTH
 C203 IN3
 C2B3 YFLH
 C2B7 TEMYL
 C290 INA
 C2A0 MIFLAG
 C2A3 DIVL
 C43B MPAGE
 C5B8 OFFXL
 C6B8 OFFYL
 C000 KBD
 C053 SMIX
 C056 SLORES
 C0B2 DEV3
 CB2D PRCHK
 CB6D END
 CB8C INEXIT
 CBFO CURSOUT
 ?C918 CALLCURS
 C951 GR
 C980 LOOP
 C9B3 A

CDOE ALPH1
 C9B3 A
 CA6A ASCON
 C9F0 BASCLC
 CC7B BTST
 CCOC C4SKP
 24 CH
 FDED COUT
 CDFA CROUT3
 CAB2 CSKIP
 CEDA DEF2
 C0B1 DEVO
 ?CB2D DEXIT
 CDD9 DIQ4
 C2A3 DIVL
 CB6B E1PNT
 CB6D END
 CE0C EXIT1
 CE41 EXIT2
 CCA2 G2WAIT
 CCA1 GWAIT
 CA9D HLOOP
 C200 INO
 C290 INA
 ?C900 INPUTXY
 ?CEFC JMREAD
 C010 K3DSTRB
 CAD7 LOOP1
 C962 LOR1
 ?C930 MIX
 C299 NFLAG
 CD7C NOROL
 CC41 OFFSC
 C73B OFFYH
 CB00 OTHROM
 C3B8 PAGE
 CAF2 POS
 CCFB PROC2
 C2B7 REGH
 CD3D ROUT2
 CB70 SCALE
 C050 SGR
 C052 SNMIX
 CE8E STMODE
 CCC6 SYNT2
 C57B TEMPL
 C2B8 TEMY
 CA4C WINCHK
 C2B4 YFLH
 2A HBASL
 C200 INO
 C2B0 TEM
 C2B4 YFLH
 C2B7 REGH
 C29B INX
 C2A1 OREGH
 C2A5 C1HAR
 C43B SCALL
 C57B TEMPL
 C67B CHAR
 C010 K3DSTRB
 C053 SMIX
 C057 SHIRES
 C0B3 DEV2
 CB34 NDCRS
 CB6F INEX1
 CB90 GLOOP
 ?C900 INPUTXY
 ?C930 MIX
 ?C95A LORES
 C9B5 CTRL00P
 C9C4 B

CC8E AMOVE
 CC44 AL00P
 CAB9 ASKIP
 2B BASL
 C2A5 C1HAR
 CD0C C5SKP
 C67B CHAR
 37 COUTH
 CBFO CURSOUT
 C9DB CTRCHK
 CEE2 DEF3
 C0B0 DEV1
 CDBB DIQ1
 CD90 DIGLP
 CC64 DLOOP
 CB3F EEXIT
 CB3F EPOINT
 CCF2 EXIT3
 CCF3 EXIT4
 CCA3 G3WAIT
 2B HBASH
 C67B HNDX
 C201 IN1
 CB6F INEX1
 C29B INX
 ?CEFC JSCALE
 CAB8 KLOOP
 CAF3 LOOP2
 ?C95A LORES
 C43B MPAGE
 CA67 NO
 CBDC NOSWITCH
 CB64 OFFSET
 C6B8 OFFYL
 C94E OUT1
 CE7F PARAM
 CB2D PRCHK
 CC19 RDLOOP
 CB83 RESLP
 CD24 ROUTIN
 C53B SCALH
 C057 SHIRES
 C054 SPAG1
 CE44 STRIN
 CCAD SYNTAX
 C2B5 TEMXL
 C2B0 TEM
 C2B2 XFLH
 C2B3 YFLH
 2B HBASH
 C201 IN1
 C2B1 XFLL
 C2B5 TEMXL
 C2B8 TEMY
 C299 NFLAG
 C2A2 OREGH
 C2A5 COUNT
 C53B SCALH
 C63B OFFXH
 C73B OFFYH
 C050 SGR
 C054 SPAG1
 C0B0 DEV1
 CB00 OTHROM
 CB3F EPOINT
 CB83 INEX2
 CB66 ASCEX
 ?C902 POINT
 C936 TEXT
 C962 LOR1
 C99E OUTSIDE
 C9DO OUT

C9DB CTRCHK
 CA2B HPOSN1
 CA5F YES
 CAB6 FLOOP
 CAAF JL00P
 ?CAC1 RTN
 CAF2 POS
 CB2C FEXIT
 CB5B TWOCOM
 CB66 OFFS1
 CCOC C4SKP
 CC42 READTAB
 CC79 ATST
 CCA1 GWAIT
 CB8C SYNT1
 CCF3 EXIT4
 CDOE ALPH1
 CD4B NDCRS
 ?CD53 EMSQ
 CD89 BROUT
 CDCB DIQ3
 CDFA CROUT3
 CE44 STRIN
 CE90 DEFAULT
 CEE2 DEF3
 ?CEFC JSCALE
 FF5B IORTS

C9DE LOCLC
 CA2C HPOSN2
 CA67 NO
 CAB9 ASKIP
 CAB2 CSKIP
 CAL2 OFFDIV
 CAF3 LOOP2
 ?CB2D DEXIT
 CB64 OFFSET
 CBDO SWCHK
 CCOE ZDLOOP
 CC44 AL00P
 CC7B BTST
 CCA2 G2WAIT
 CCC6 SYNT2
 CCF6 PROC1
 CD24 ROUTIN
 CD4C EXIT5
 CD55 EMSQ1
 CD90 DIGLP
 CDD9 DIQ4
 CE0C EXIT1
 CE5D TABL
 CE8E STMODE
 CEEA DEF4
 CFFF ROMSW

C9F0 BASCLC
 CA39 CLOOP
 CA6A ASCON
 CA9D HLOOP
 CAB8 KLOOP
 CAD1 DIVIDE
 CB0C LOOP3
 CB3F EEXIT
 CB70 SCALE
 CBDC NOSWITCH
 CC19 RDLOOP
 CC5E AIL00P
 CB83 RESLP
 CCA3 G3WAIT
 CCE4 CHOUT
 CCFB PROC2
 CD31 ROUT1
 CD4F ERR3
 CD67 AROUT
 CDA2 DIQ2
 CDEA CROUT
 CE3E PRINT
 CE6E ADR
 CED2 DEF1
 ?CEFC JWINCHK
 FDED COUT

CA0C C2SKP
 CA4C WINCHK
 CAB0 POSIT
 CAA0 BSKIP
 CABD DSKIP
 CAD7 LOOP1
 ?CB1F LOOP4
 CB57 E1EXIT
 CB89 MREAD
 CBF4 M1READ
 CC41 OFFSC
 CC64 DLOOP
 CC8E AMOVE
 CCAD SYNTAX
 CCF2 EXIT3
 CD0C C5SKP
 CD3D ROUT2
 CD50 ERR1
 CD7C NOROL
 CD8B DIQ1
 CDF7 CROUT2
 CE41 EXIT2
 CE7F PARAM
 CEDA DEF2
 ?CEFC JMREAD
 FE93 SETVID

QUICK-DRAW

```

0000: 1 PAGE
0000: 2 *****
0000: 3 *
0000: 4 * COPYRIGHT 1979
0000: 5 *
0000: 6 * APPLE COMPUTER INC.
0000: 7 *
0000: 8 * CUPERTINO CALIFORNIA
0000: 9 *
0000: 10 * ALL RIGHTS RESERVED
0000: 11 *
0000: 12 *****
0000: 13 * WRITTEN JAN 1979
0000: 14 * BY JOHN A.
0000: 15 * APPLE COMPUTER
0000: 16 * SYSTEMS SOFTWARE
0000: 17 *****
0000: 18 * WINDOCK CORRECTED APR 25, 1979
0000: 19 * BY JOHN A.
0000: 20 PAGE
0000: 21 *****
0000: 22 *
0000: 23 * BITPAD TO APPLESOFT II *
0000: 24 * INTERFACE ROUTINE *
0000: 25 * THIS ROUTINE MAKES *
0000: 26 * IT POSSIBLE TO CALL *
0000: 27 * THE BITPAD AT HIGH *
0000: 28 * SPEED AND FETCH THE *
0000: 29 * POINTS DRAWN DIRECTLY *
0000: 30 * INTO APPLESOFT DATA *
0000: 31 * ARRAYS AT MAXIMUM *
0000: 32 * SPEED. ARRAYS MUST BE *
0000: 33 * DIMENSIONED BEFORE *
0000: 34 * CALLING THIS ROUTINE *
0000: 35 * THEY ARE X% AND Y% *
0000: 36 * IN ADDITION N% AND D% *
0000: 37 * MUST ALSO BE ALLOCATED *
0000: 38 *****
0000: 39 ORG $C00
0000: 40 OBJ $2000
0000: 41 *****
0000: 42 *PAGE ZERO USAGE *
0000: 43 VARPNT EQU $83
0000: 44 VARNAM EQU $81
0000: 45 LOWTR EQU $98
0000: 46 TTTAB EQU $67
0000: 47 VARTAB EQU $69
0000: 48 ARYTAB EQU $68
0000: 49 STREND EQU $6D
0000: 50 ARYPNT EQU $94
0000: 51 *FAC EQU $9D TO A3
0000: 52 DELTA EQU $9D
0000: 53 INDX EQU $9E
0000: 54 NADRS EQU $A0
0000: 55 MAXN EQU $A2
0000: 56 *ARG EQU $A5 TO A8
0000: 57 TICFLG EQU $A5
0000: 58 XVPTR EQU $A6
0000: 59 YVPTR EQU $A8
0000: 60 TMAXY EQU $AA ;TEMP MAX Y COORD LIMIT
0000: 61 * ;TMAXY =MIN(MIXED MODE*160,MAXY)
0000: 62 XOL EQU $E0 ;PRIOR X-COORD SAVE
0000: 63 XOH EQU $E1 ;PRIOR X-COORD SAVE HI
0000: 64 YO EQU $E2 ;PRIOR Y-COORD SAVE
0000: 65 ERRFLG EQU $DB
0000: 66 REMSTK EQU $FB
0000: 67 ERRNUM EQU $DE
0000: 68 *****
0000: 69 *ENTRY POINTS USED *

```

```

0C00: 70 HILIN EQU $F53A ; REAL HILIN ENTRY
0C00: 71 HPL0T EQU $F457 ; REAL HPL0T ENTRY
0C00: 72 CHRGET EQU $00B1 ; NEXT PGM CHAR
0C00: 73 CHRGT EQU $00B7
0C00: 74 CRDO EQU $DAFB
0C00: 75 OUTGST EQU $DB5A
0C00: 76 OUTDO EQU $DB5C
0C00: 77 ISLETC EQU $E07D
0C00: 78 TYPERR EQU $D42A
0C00: 79 HNDLERX EQU $F2EF
0C00: 80 WAIT EQU $FCAB ;MON A WAIT
0C00: 81 PAGE
0C00: 82 *****
0C00: 83 * DEVICE ADDRESSES
0C00: 84 SPKR EQU $C030 ; TOGGLES APPLE SPKR
0C00: 85 STXT EQU $C051 ; SET TEXT MODE!
0C00: 86 SPAG1 EQU $C054
0C00: 87 *****
0C00: 88 * BITPAD INTERFACE EQU *
0C00: 89 *****
0C00: 90 TEM EQU $280 ; RETURN FLAG LDC
0C00: 91 * HI NIBBLE =1 FOR SCALED RESULTS
0C00: 92 * LO NIBBLE 0=PEN DOWN
0C00: 93 * 1=PEN LIFT
0C00: 94 * 2 PEN FALL
0C00: 95 * 3=PEN UP
0C00: 96 XFLL EQU $281 ; X-COORD LO UNSCALED
0C00: 97 XFLH EQU $282 ; X-COORD HI UNSCALED
0C00: 98 YFLL EQU $283 ; Y-COORD LOW UNSCALED
0C00: 99 YFLH EQU $284 ; Y-COORD HI UNSCALED
0C00: 100 TEMXL EQU $285 ; X-COORD LO SCALED
0C00: 101 TEMX EQU $286 ; X-COORD HI SCALED
0C00: 102 TEMYL EQU $287 ; Y-COORD LO SCALED
0C00: 103 TEMY EQU $288 ; Y-COORD HI SCALED
0C00: 104 SSM1 EQU $29A ;LO INDIRECT ADRS
0C00: 105 SAVSLOT EQU $298
0C00: 106 RTNCD EQU $28C ;=700 BITSOFT RTN CODE
0C00: 107 PAGE EQU $388 ;+CN : SCREEN MODE
0C00: 108 * HI BIT=1 MEANS SCALE DATA
0C00: 109 * 40 = HIRES PG2
0C00: 110 * 20 = HIRES PG1
0C00: 111 HIRES1 EQU $20
0C00: 112 * 08 = TEXT PG2
0C00: 113 * 04 = TEXT PG1
0C00: 114 * 02 = LORES PG2
0C00: 115 * 01 = LORES PG1
0C00: 116 * 42 = HIRES PG2 MIXED
0C00: 117 * 21 = HIRES PG1 MIXED
0C00: 118 * 0A = LORES PG2 MIXED
0C00: 119 * 05 = LORES PG1 MIXED
0C00: 120 MXYVALU EQU 160 ; FOR NORMAL APPLE
0C00: 121 MSLOT EQU $7FB
0C00: 122 *****
0C00: 123 * BITPAD ENTRY POINTS *
0C00: 124 *****
0C00: 125 POINT EQU $C102
0C00: 126 MREAD EQU $CEF9
0C00: 127 WINCHK EQU $CEFC
0C00: 128 SCALE EQU $CEFC
0C00: 129 PAGE
0C00: 130 *****
0C00: 131 JMP BITSOFT
0C00: 132 JMP FINDVAR ;FIND VARIABLE UTILITY ENTR
0C00: 133 JMP FINDARY ;FIND ARRAY UTILITY ENTRY
0C00: 134 *****
0C00: 135 VNAMTAB EQU *
0C00: 136 DLTANAM DFB $C4,$80 ; DX
0C00: 137 NDXNAM DFB $CE,$80 ; NX
0C00: 138 XVNAM DFB $DB,$80 ; XX
0C00: 139 YVNAM DFB $D9,$80 ; YZ
0C00: 140 DNAME EQU DLTANAM-VNAMTAB
0C00: 141 NNAME EQU NDXNAM-VNAMTAB
0C00: 142 XNAME EQU XVNAM-VNAMTAB

```



```

OC11: 00 143 YNAME EGU YVNAME-VNAMTAB
OC12: 00 144 MINXL DFB $00
OC13: 18 145 MINX DFB $00
OC14: 01 146 MAXXL DFB 24
OC15: 00 147 MAXX DFB 1 ; MAX X=256+24
OC16: C0 148 MINY DFB $0
OC17: 03 4F D0 149 MAXY DFB 192
OC1A: 19 52 C9 150 CTABLE DFB $03, $4F, $D0
OC1D: 07 48 D4 151 DFB $19, $52, $C9
OC20: 20 41 D0 152 DFB $07, $48, $D4
OC23: 10 4C C5 153 DFB $20, $41, $D0
OC26: 20 43 CF 154 DFB $10, $4C, $C5
OC29: 0D 50 D5 155 DFB $20, $43, $CF
OC2C: 14 45 D2 156 DFB $0D, $50, $D5
OC2F: 37 79 157 DFB $14, $45, $D2
OC31: 158 DFB $37, $79
OC31: 159 PAGE
OC31: 160 *****
OC31: 161 * BITPAD MESSAGES
OC31: 20 44 41
OC34: 50 54 49
OC37: C2 162 BITMSG DCI " DAPTIB"
OC38: 44 45 4C
OC3B: 54 41 20
OC3E: 53 49 5A
OC41: C5 163 DLTASIZ DCI "DELTA SIZE"
OC42: 44 45 4C
OC45: 54 41 20
OC48: 55 4E 44
OC4B: 45 46 49
OC4E: 4E 45 C4 164 DLTADef DCI "DELTA UNDEFINED"
OC51: 49 4E 44
OC54: 45 58 20
OC57: 55 4E 44
OC5A: 45 46 49
OC5D: 4E 45 C4 165 INDXDEF DCI "INDEX UNDEFINED"
OC60: 41 52 52
OC63: 41 59 20
OC66: 44 49 4D
OC69: 45 4E 53
OC6C: 49 4F CE 166 ARYDEF DCI "ARRAY DIMENSION"
OC6F: 42 41 44
OC72: 20 53 55
OC75: 42 53 43
OC78: 52 49 50
OC7B: D4 167 NGTMAXN DCI "BAD SUBSCRIPT"
OC7C: 4E 4F 54
OC7F: 20 49 4E
OC82: 20 53 43
OC85: 41 4C 45
OC88: 44 20 48
OC8B: 49 52 45
OC8E: 53 20 4D
OC91: 4F 44 C5 168 NOTHGR DCI "NOT IN SCALED HIRES MODE"
OC94: 169 XDLTASIZ EGU DLTASIZ-BITMSG+40 ; THIS BIASES RTN CDS BY 4
OC94: 170 XDLTADef EGU DLTADef-BITMSG+40 ; THIS BIASES RTN CDS BY 4
OC94: 171 XINDXDEF EGU INDXDEF-BITMSG+40 ; THIS BIASES RTN CDS BY 4
OC94: 172 XARYDEF EGU ARYDEF-BITMSG+40 ; THIS BIASES RTN CDS BY 4
OC94: 173 XNRANGE EGU NGTMAXN-BITMSG+40 ; THIS BIASES RTN CDS BY 4
OC94: 174 XNOTHGR EGU NOTHGR-BITMSG+40 ; THIS BIASES RTN CDS BY 4
OC94: 175 PAGE
OC94: 176 *****
OC94: 177 * BEGIN CODE *
OC94: 178 *****
OC94: 179 BITSOFT EGU *
OC94: 20 95 OF 180 JSR USRNAMS
OC97: A2 00 181 NONAMES LDX #NAME ;=0
OC99: 20 E4 OE 182 JSR SETNAME ; SET UP VARNA
OC9C: 20 58 OF 183 JSR FINDVAR ; GO FIND DELTA
OC9F: D0 33 184 BCS DLTAOK ; HE DID ALLOCATE IT!
OCA1: A2 39 185 LDX #XDLTADef
OCA3: 186 BITPERR EGU *
OCA3: 24 D0 187 BIT ERRFLG ; IS ON ERR DN?

```

```

OCA5: 10 0B 188 BPL DOERR ; NO
OCA7: 86 DE 189 STX ERRNUM
OCA9: A6 FB 190 LDX REMSTK ; GET STACK PTR
OCAB: 9A 191 TXS ; RESTORE STACK
OCAC: 4C EF F2 192 JMP HNDLERX
OCAE: AD 34 C0 193 DOERR EGU *
OCB2: AD 31 C0 194 LDA SPAG1 ; BACK TO PAGE 1 TOO
OCB5: 20 F3 DA 195 LDA STXT ; BACK TO TEXT MODE!
OCB8: 20 5A DB 196 JSR CRDO
OCBB: A0 06 197 JSR OUTGST
OCBD: B9 31 OC 198 LDY #6
OCCE: 20 5C DB 199 BITPD LDA BITMSG, Y
OCCE: 88 200 JSR OUTDO
OCCE: 10 F7 201 DEY
OCCE: B0 09 OC 202 BPL BITPD
OCCE: 48 203 BMSGPL LDA BITMSG-40, X
OCCE: 20 5C DB 204 PHA
OCCE: E8 205 JSR OUTDO
OCCE: 68 206 INX
OCCE: 10 F5 207 PLA
OCCE: 4C 2A D4 208 BPL BMSGPL ; LOOP FOR NXT
OCCE: A0 00 209 JMP TYPERR ; ADD LINE # & QUIT
OCCE: B1 B3 210 DLTAOK EGU *
OCCE: B4 A5 211 LDY #0
OCCE: 18 212 LDA (VARPNT), Y
OCCE: 10 0B 213 STY TICFLG ; ASSUME TICK
OCCE: 38 214 CLC ; ASSUME NOT NEGATIVE
OCCE: B5 A5 215 BPL CHKDVALU
OCCE: 49 FF 216 SEC ; SAY NEGATIVE
OCCE: F0 04 217 STA TICFLG ; SET NOTICK
OCCE: A2 2F 218 EOR #FF ; IS DX < 256
OCCE: D0 B0 219 BEQ CHKDVALU ; IT'S OK
OCCE: C8 220 DSIZERR LDX #XDLTASIZ
OCCE: B1 B3 221 BNE BITPERR
OCCE: 90 04 222 CHKDVALU EGU *
OCCE: 49 FF 223 INY ; Y=1
OCCE: 69 00 224 LDA (VARPNT), Y ; GET DELTA LOW
OCCE: 30 F1 225 BCC NOCOMPL ; DONT COMPLEMENT
OCCE: F0 EF 226 EOR #FF
OCCE: 85 9D 227 ADC #0 ; DO TWOS COMP
OCCE: A2 02 228 NOCOMPL BMI DSIZERR ; !DELTA!>127 ERR
OCCE: 20 E4 OE 229 BEQ DSIZERR
OCCE: 20 58 OF 230 STA DELTA ; SAVE WINDOW SIZE
OCCE: B0 04 231 LDX #NAME ; =2
OCCE: A2 48 232 JSR SETNAME
OCCE: D0 9E 233 JSR FINDVAR ; IS NX THERE
OCCE: A0 00 234 BCS NTHERR ; YES HE DID
OCCE: B1 B3 235 PAGE
OCCE: B4 A5 236 LDX #XINDXDEF
OCCE: 18 237 BNE BITPERR
OCCE: 10 0B 238 EGU *
OCCE: 38 239 LDY #0
OCCE: B5 A5 240 LDA (VARPNT), Y
OCCE: 49 FF 241 BMI NTHERR ; INDX<0 ERR
OCCE: 30 F1 242 IXOK STA INDX+1 ; SAVE VALUE
OCCE: F0 EF 243 INY ; Y=1
OCCE: 85 9D 244 LDA (VARPNT), Y
OCCE: A2 02 245 STA INDX
OCCE: 20 E4 OE 246 LDA VARPNT
OCCE: B0 04 247 STA NADRS ; SAVE IT ADDRESS
OCCE: A2 48 248 LDA VARPNT+1
OCCE: D0 9E 249 STA NADRS+1 ; FOR UPDATEING N
OCCE: A0 00 250 LDX #NAME ; =4
OCCE: B1 B3 251 JSR SETNAME
OCCE: B4 A5 252 JSR FINDARY ; IS X%?
OCCE: 18 253 BCS XTHERR ; YES SMART USER
OCCE: 10 0B 254 ARYERR LDX #XARYDEF
OCCE: 38 255 ERRJMP JMP BITPERR
OCCE: B5 A5 256 XTHERR EGU *
OCCE: 49 FF 257 LDY #4 ; POINT AT # OF DIMS
OCCE: F0 04 258 LDA (VARPNT), Y ; IS DIMS 1?
OCCE: A2 2F 259 CMP #1 ; IS IT A VECTOR ?
OCCE: D0 B0 260 BNE ARYERR

```

0031	C8	261	XDIM50K	INY	: Y=5
0032	C9	262		INY	: Y=6
0033	08	263		SEC	
0034	B1 83	264		LDA (VARPNT),Y	
0036	E5 9F	265		SBC INDY	
0038	AA	266		TAX	: SAVE LOW RESULT
0039	88	267		DEY	: Y=5
003A	B1 83	268		LDA (VARPNT),Y	
003C	E5 9F	269		SBC INDY+1	
003E	B0 04	270		BCS NOTXROWS	
0040	A2 6A	271	NRNGERR	LDX #XNRANGE	
0042	D0 E2	272		BNE ERRJMP	
0044	30 FA	273	NOTXROWS	BMI NRNGERR	
0046	D0 04	274		BNE NISOK	
0048	E0 02	275		CPX #2	
004A	90 F4	276		BCC NRNGERR	
004C	B1 83	277	NISOK	LDA (VARPNT),Y	: GET MAX
004E	B5 A3	278		STA MAXN+1	
0050	C8	279		INY	: Y=6
0051	B1 83	280		LDA (VARPNT),Y	: GET LO
0053	B5 A2	281		STA MAXN	
0055	A5 B3	282		LDA VARPNT	
0057	18	283		CLC	
0058	69 07	284		ADC #7	: CALC BASE ADDRESS
005A	B5 A6	285		STA XVPTR	: SET X BASE
005C	A6 B4	286		LDX VARPNT+1	: GET HI BASE
005E	90 01	287		BCC #+3	: NO CARRY FROM ADD
0060	E8	288		INX	
0061	B6 A7	289		STX XVPTR+1	: X BASE COMPLETE
0063		290		PAGE	
0063	A2 06	291		LDX #YNAME	+ #6
0065	20 E4 0E	292		JSR SETNAME	
0068	20 27 0F	293		JSR FINDARY	
006B	90 B7	294		BCC ARYERR	
006D	A0 04	295	YTHRE	LDY #4	
006F	B1 83	296		LDA (VARPNT),Y	
0071	C9 01	297		CMF #1	
0073	D0 AF	298		BNE ARYERR	
0075	C8	299		INY	
0076	C8	300		INY	: POINT TO NROWSL
0077	B1 83	301		LDA (VARPNT),Y	
0079	AA	302		TAX	
007A	C5 A2	303		CMF MAXN	
007C	88	304		DEY	
007D	B1 83	305		LDA (VARPNT),Y	
007F	E5 A3	306		SBC MAXN+1	: IS YSIZE>XSIZE?
0081	B0 1C	307		BCS YSIZEOK	: YSIZE>XSIZE
0083	B6 A2	308		STX MAXN	
0085	B1 83	309		LDA (VARPNT),Y	: GET HI BACK
0087	B5 A3	310		STA MAXN+1	
0089	38	311		SEC	
008A	A5 A2	312		LDA MAXN	
008C	E5 9E	313		SBC INDY	
008E	AA	314		TAX	
008F	A5 A3	315		LDA MAXN+1	
0091	E5 9F	316		SBC INDY+1	
0093	B0 02	317		BCS YROWSGTN	
0095	90 A9	318		BCC NRNGERR	
0097	30 A7	319	YROWSGTN	BMI NRNGERR	
0099	D0 04	320		BNE YSIZEOK	
009B	E0 02	321		CPX #2	: AT LEAST TWO MORE ARRAY E
009D	90 A1	322		BCC NRNGERR	: YSIZE<N
009F		323	YSIZEOK	EQU *	
009F	A5 B3	324		LDA VARPNT	
00A1	18	325		CLC	
00A2	69 07	326		ADC #7	
00A4	B5 A8	327		STA YVPTR	
00A6	A6 B4	328		LDX VARPNT+1	
00A8	90 01	329		BCC #+3	
00AA	E8	330		INX	
00AB	B6 A9	331		STX YVPTR+1	
00AD	06 9E	332		ASL INDY	
00AF	26 9F	333		ROL INDY+1	INDX=INDX*2

00B1	A5 A8	334		LDA YVPTR	
00B3	A6 A9	335		LDX YVPTR+1	
00B5	20 F0 0E	336		JSR ADDINX	
00B8	B4 A8	337		STY YVPTR	
00BA	B5 A9	338		STA YVPTR+1	
00BC	A5 A6	339		LDA XVPTR	
00BE	A6 A7	340		LDX XVPTR+1	
00C0	20 F0 0E	341		JSR ADDINX	
00C3	B4 A6	342		STY XVPTR	
00C5	B5 A7	343		STA XVPTR+1	
00C7	46 9F	344		LSR INDY+1	
00C9	66 9E	345		ROR INDY	: INDX=INDX/2
00CB		346		PAGE	
00CB	A9 00	347		LDA #0	
00CD	BD BC 02	348		STA RTNCD	
00D0	AC 9B 02	349		LDY SAVSLOT	
00D3	98	350		TYA	: PUT IN A
00D4	38	351		SEC	: FOR SUBTRACT
00D5	E9 C1	352		SBC #C1	: IT VALID SLOT?
00D7	C9 07	353		CMF #7	
00D9	B0 08	354		BCS BADMODE	: SLOT NOT INITED!!!
00DB	B9 B8 03	355		LDA PAGE,Y	
00DE	10 06	356		BPL BADMODE	
00E0	29 7F	357		AND #67F	
00E2	C9 20	358		CMF #HIRES1	
00E4	B0 05	359		BCS MODEOK	
00E6	A2 73	360	BADMODE	LDX #XNOTHGR	
00E8	4C A3 0C	361		JMP DITPERR	
00EB	29 03	362	MODEOK	AND #3	
00ED	AC 16 0C	363		LDY MAXY	
00F0	AA	364		TAX	: IS IT MIXED MODE?
00F1	F0 06	365		BEG NOTMIXD	
00F3	C0 A0	366		CPY #MAXYVALU	
00F5	90 02	367		BCC NOTMIXD	
00F7	A0 A0	368		LDY #MAXYVALU	
00F9	B4 AA	369	NOTMIXD	STY TMAXY	
00FB	A2 02	370		LDX #POINT	
00FD	8E 9A 02	371		STX SAVSLOT-1	
00E0	20 E1 0E	372		JSR JSRINDRCT	
00E3	AD B0 02	373		LDA TEM	
00E6	29 03	374		AND #3	
00E8	C9 03	375		CMF #3	: IS PEN UP?
00EA	F0 0A	376		BEG KYBDXIT	: YES, HE HIT KEYBD
00EC	20 F8 0E	377		JSR WINDOCHK	: IS IT ON SCREEN?
00EF	B0 06	378		BCS ONSCRN	: YEP
00E11	A9 01	379	YTOOBIG	LDA #1	: PEN OFF SCREEN EXIT
00E13	BD BC 02	380	STRTNC	STA RTNCD	
00E16	60	381	KYBDXIT	RTS	
00E17		382	ONSCRN	EQU *	
00E17	AD B7 02	383		LDA TEMYL	
00E1A	AE B5 02	384		LDX TEMXL	
00E1D	AC B6 02	385		LDY TEMX	
00E20	20 57 F4	386		JSR HPLDT	
00E23		387	MAINLP	EQU *	
00E23	24 A5	388		BIT TICFLQ	
00E25	30 08	389		BMI NOTICK	
00E27		390	TICKLE	EQU *	
00E27	AD 30 C0	391		LDA SPKR	
00E2A	A9 0F	392		LDA #0F	
00E2C	20 A8 FC	393		JSR WAIT	
00E2F	AD 30 C0	394		LDA SPKR	: TICK IT
00E32		395	NOTICK	EQU *	
00E32	AD B6 02	396		LDA TEMX	
00E35	A0 00	397		LDY #0	
00E37	91 A6	398		STA (XVPTR),Y	
00E39	AD B8 02	399		LDA TEMY	
00E3C	91 A8	400		STA (YVPTR),Y	: STORE Y VALU
00E3E	C8	401		INY	
00E3F	AD B5 02	402		LDA TEMXL	: STORE X VALUE
00E42	91 A6	403		STA (XVPTR),Y	
00E44	AD B7 02	404		LDA TEMYL	
00E47	91 A8	405		STA (YVPTR),Y	


```

0E49: 406 PAGE
0E49: A2 01 407 LDX #1
0E4B: E6 A6 408 XVINI INC XVPTR
0E4D: D0 02 409 BNE **4
0E4F: E6 A7 410 INC XVPTR+1
0E51: CA 411 DEX
0E52: F0 F7 412 BEQ XVINI
0E54: A2 01 413 LDX #1
0E56: E6 A6 414 YVINI INC YVPTR
0E58: D0 02 415 BNE **4
0E5A: E6 A7 416 INC YVPTR+1
0E5C: CA 417 DEX
0E5D: F0 F7 418 BEQ YVINI
0E5F: E6 9E 419 INC INDX
0E61: D0 02 420 BNE **4
0E63: E6 9F 421 INC INDX+1
0E65: 422 * Y=1 FROM ABOVE!
0E65: A3 9E 423 LDA INDX
0E67: 91 A0 424 STA (NADRS),Y
0E69: 89 425 DEY
0E6A: A5 9F 426 LDA INDX+1
0E6C: 91 A0 427 STA (NADRS),Y
0E6E: A5 9E 428 LDA INDX
0E70: C5 A2 429 CMP MAXN
0E72: A5 9F 430 LDA INDX+1
0E74: E5 A3 431 SBC MAXN+1
0E76: 90 05 432 BCC MORPTS
0E78: A9 03 433 LDA #3
0E7A: 4C 13 0E 434 JMP STRNCD
0E7D: AE 9B 02 435 LDX SAVSLOT
0E80: BE FB 07 436 STX MSLDT
0E83: 437 WAITLP EQU *
0E83: 20 F9 0E 438 JSR MREAD
0E86: AD 80 02 439 LDA TEM
0E89: 29 03 440 AND #3
0E8B: F0 05 441 BEQ PENDOWN
0E8D: A9 02 442 LDA #2
0E8F: 4C 13 0E 443 JMP STRNCD
0E92: A2 03 444 PENDOWN LDX #3
0E94: 8D 81 02 445 MVLP LDA XFLX,X
0E97: 9D 85 02 446 STA TEMXL,X
0E9A: CA 447 DEX
0E9B: 10 F7 448 BPL MVLP
0E9D: AE 9B 02 449 LDX SAVSLOT
0EA0: 20 FC 0E 450 JSR SCALE
0EA3: 20 FB 0E 451 JSR WINDCHK
0EA6: 80 03 452 BCS CKDLTA
0EAB: 4C 11 0E 453 JMP YTOOBIG
0EAB: AD 87 02 454 CKDLTA EQU *
0EAB: 3B 455 LDA TEMYL
0EAF: E5 E2 456 SEC
0EB1: 80 04 457 SBC YD
0EB3: 49 FF 458 BCS CKYDLTA
0EB5: 69 01 459 EOR #FF
0EB7: C5 9D 460 ADC #1
0EB9: 80 17 461 CKYDLTA CMP DELTA
0EBB: 3B 462 BCS PLOTSEQ
0EBC: AD 85 02 463 SEC
0EBF: E5 E0 464 LDA TEMXL
0EC1: AA 465 SBC XOL
0EC2: AD 86 02 466 TAX
0EC5: E5 E1 467 LDA TEMX
0EC7: 8A 468 SBC XOH
0ECB: 80 04 469 TXA
0ECA: 49 FF 470 BCS CKXDLTA
0ECC: 69 01 471 EOR #FF
0ECE: 472 ADC #1
0ECE: C5 9D 473 CKXDLTA EQU *
0ED0: 90 B1 474 CMP DELTA
0ED2: AD 85 02 475 BCC WAITLP
0ED5: AE 86 02 476 PLOTSEQ LDA TEMXL
0ED8: AC 87 02 477 LDX TEMX
478 LDY TEMYL

```

```

0ED8: 20 3A F5 479 JSR HILIN
0EDE: 4C 23 0E 480 JMP MAINLP
0EE1: 481 *****
0EE1: 482 * MY SUBROUTINES
0EE1: 483 *****
0EE1: 6C 9A 02 484 JSRINDRCT JMP (SAVSLOT-1)
0EE4: 485 *****
0EE4: 8D 09 0C 486 SETNAME LDA VNAMTAB,X
0EE7: 85 81 487 STA VARNAM
0EE9: E8 488 INX
0EEA: 8D 09 0C 489 LDA VNAMTAB,X
0EED: 85 82 490 STA VARNAM+1
0EEF: 60 491 RTS
0EFO: 492 *****
0EFO: 18 493 ADDINX CLC
0EF1: 65 9E 494 ADC INDX
0EF3: A8 495 TAY
0EF4: BA 496 TXA
0EF5: 65 9F 497 ADC INDX+1
0EF7: 60 498 RTS
0EF8: 499 *****
0EF8: AD 85 02 500 WINDCHK LDA TEMXL
0EF8: AA 501 TAX
0EFC: CD 11 0C 502 CMP MINXL
0EFF: AD 86 02 503 LDA TEMX
0F02: A8 504 TAY
0F03: ED 12 0C 505 SBC MINX
0F06: 90 0B 506 BCC WCHKRTS
0F08: BA 507 TXA
0F09: CD 13 0C 508 CMP MAXXL
0F0C: 98 509 TYA
0F0D: ED 14 0C 510 SBC MAXX
0F10: 90 02 511 BCC XINSIDE
0F12: 18 512 OUTSIDE CLC
0F13: 60 513 WCHKRTS RTS
0F14: AD 88 02 514 XINSIDE LDA TEMY
0F17: D0 F9 515 BNE OUTSIDE
0F19: AD 87 02 516 LDA TEMYL
0F1C: CD 15 0C 517 CMP MINY
0F1F: 90 F2 518 BCC WCHKRTS
0F21: C5 AA 519 CMP TMAXY
0F23: 80 ED 520 BCS OUTSIDE
0F25: 38 521 SEC
0F26: 60 522 INSIDE RTS
0F27: 523 PAGE
0F27: 524 *****
0F27: A6 6B 525 FINDARY LDX ARYTAB
0F29: A5 6C 526 LDA ARYTAB+1
0F2B: 86 9B 527 FNDLPA STX LOWTR
0F2D: 85 9C 528 STA LOWTR+1
0F2F: C5 6E 529 CMP STREND+1
0F31: D0 04 530 BNE FNDFDV
0F33: E4 6D 531 CPX STREND
0F35: F0 5C 532 BEQ NOTFND
0F37: A0 00 533 FNDFDV LDY #0
0F39: B1 9B 534 LDA (LOWTR),Y
0F3B: CB 535 INY
0F3C: C5 81 536 CMP VARNAM
0F3E: D0 06 537 BNE NXTARY
0F40: A5 82 538 LDA VARNAM+1
0F42: D1 9B 539 CMP (LOWTR),Y
0F44: F0 0E 540 BEQ GOTARY
0F46: CB 541 INY
0F47: B1 9B 542 LDA (LOWTR),Y
0F49: 18 543 CLC
0F4A: 65 9B 544 ADC LOWTR
0F4C: AA 545 TAX
0F4D: CB 546 INY
0F4E: B1 9B 547 LDA (LOWTR),Y
0F50: 65 9C 548 ADC LOWTR+1
0F52: 90 D7 549 BCC FNDLPA
0F54: A9 00 550 GOTARY LDA #0
0F56: F0 2D 551 BEQ ADJVPTR

```

```

OF5B: 552 PAGE
OF5B: 553 *****
OF5B: A3 69 554 FINDVAR LDA VARTAB
OF5A: A6 6A 555 LDY VARTAB+1
OF5C: A0 00 556 LDY #0
OF5E: B6 9C 557 FNDLPX STX LOWTR+1
OF60: B9 9B 558 FINDLP STA LOWTR
OF62: E4 6C 559 CPX ARYTAB+1
OF64: D0 04 560 BNE LOPFN
OF66: C5 6B 561 CMP ARYTAB
OF68: F0 29 562 BEQ NOTFND
OF6A: A5 81 563 LOPFN LDA VARNAM
OF6C: D1 90 564 CMP (LOWTR),Y
OF6E: D0 0B 565 BNE NOTIT
OF70: A5 82 566 LDA VARNAM+1
OF72: C8 567 INY
OF73: D1 9B 568 CMP (LOWTR),Y
OF75: F0 0C 569 BEQ FOUNDS
OF77: B8 570 DEY
OF79: 18 571 NOTIT CLC
OF7A: A5 9B 572 LDA LOWTR
OF7B: 69 07 573 ADC #7
OF7D: 90 E1 574 BCC FINDLP
OF7F: E8 575 INX
OF80: D0 DC 576 BNE FNDLPX
OF82: 00 577 BRK
OF83: A9 02 578 FOUNDS LDA #2
OF85: 18 579 ADJVPTR CLC
OF86: 65 9B 580 ADC LOWTR
OF88: A4 9C 581 LDY LOWTR+1
OF8A: 90 01 582 BCC ADJDONE
OF8C: C8 583 INY
OF8D: B5 83 584 ADJDONE STA VARPNT
OF8F: 84 84 585 STY VARPNT+1
OF91: 38 586 SEC
OF92: 60 587 RTS
OF93: 18 588 NOTFND CLC
OF94: 60 589 RTS
OF95: 590 *****
OF95: 591 * GET USR NAMES FROM*
OF95: 592 * HIS CALL LINE AND *
OF95: 593 * USE THEM INSTEAD *
OF95: 594 * OF THE DEFAULTS *
OF95: 595 * THE USER ENTERS *
OF95: 596 * THE NAMES IN FIXED*
OF95: 597 * POSITIONAL ORDER *
OF95: 598 * AS FOLLOWS *
OF95: 599 * D%,N%,X%,Y% *
OF95: 600 *****
OF95: 601 PAGE
OF95: 602 USRNAS EGU *
OF95: A2 07 603 LDY #7
OF97: B0 F8 0F 604 DFLTS LDA DEFALT,X
OF9A: 90 09 0C 605 STA VNAMTAB,X
OF9D: CA 606 DEX
OF9E: 10 F7 607 BPL DFLTS
OFA0: 20 B7 00 608 JSR CHRGET
OFA3: D0 01 609 BNE ++3
OFA5: 60 610 RTS
OFA6: 20 7D E0 611 JSR ISLETC
OFA9: 90 18 612 BCC GETLTR
OFAB: 20 E7 0F 613 SET1ST JSR STORIT
OFAE: F0 31 614 BEQ UNAMRTS
OFB0: 20 F0 0F 615 ISTALL JSR MYCHGET
OFB3: 90 1E 616 BCC SET2ND
OFB5: 20 7D E0 617 JSR ISLETC
OFB8: B0 19 618 BCS SET2ND
OFBA: C9 2C 619 CMP #2C
OFBC: D0 F2 620 BNE ISTALL
OFBE: E8 621 NXTX INX
OFBF: E0 07 622 CPX #7
OFC1: B0 1E 623 BCS UNAMRTS
OFC3: 20 F0 0F 624 GETLTR JSR MYCHGET

```

```

; X,A SET UP
; DO CARRY TO HI
; X,A SET NOW
; INSURANCE!

```

```

; GET NEXT CHR
; EXIT, END OF STMT
; A LETTER?
; NO, IGNORE IT
; YES, USE
; GET NEXT
; DIGIT OK
; A LETTER?
; YES, USE
; NO, A COMMA ?
; NOT COMMA, IGNORE
; A COMMA SAYS NO 2ND
; AM I DONE?
; YEP
; FIND A LTR

```

```

OFC6: 20 7D E0 625 JSR ISLETC
OFC9: B0 E0 626 BCS SET1ST
OFCB: C9 2C 627 CMP #2C
OFCD: D0 F4 628 BNE GETLTR
OFCF: E8 629 INX
OFD0: B8 630 CLV
OFD1: 30 EB 631 BVC NXTX
OFD3: 20 E7 0F 632 SET2ND JSR STORIT
OFD6: F0 09 633 BEQ UNAMRTS
OFD8: 20 F0 0F 634 SCANC JSR MYCHGET
OFDB: C9 2C 635 CMP #2C
OFDD: D0 F9 636 BNE SCANC
OFDF: F0 E2 637 BEQ GETLTR
OFE1: 20 F0 0F 638 UNAMRTS JSR MYCHGET
OFE4: D0 FD 639 BNE UNAMRTS
OFE6: 60 640 RTS
OFE7: E8 641 STORIT INX
OFE8: 09 B0 642 ORA #B0
OFEA: 90 09 0C 643 STA VNAMTAB,X
OFED: E0 07 644 CPX #7
OFEF: 60 645 RTS
OFF0: 20 B1 00 646 MYCHGET JSR CHRGET
OFF3: D0 02 647 BNE ++4
OFF5: 68 648 PLA
OFF6: 68 649 PLA
OFF7: 60 650 RTS
OFFB: C4 B0 651 DEFALT DFB #C4, $B0
OFFA: CE B0 652 DFB #CE, $B0
OFFC: D8 B0 653 DFB #D8, $B0
OFFE: D9 B0 654 DFB #D9, $B0

```

*** SUCCESSFUL ASSEMBLY: NO ERRORS

```

; A LETTER?
; YES DO NEXT ONE
; A COMMA ?
; NO, IGNORE !
; YES SKIP THIS NAME
; ALWAYS
; TAKEN !
; IS IT A COMMA?
; NO, KEEP LOOKING
; YES, BEGIN AGAIN
; GET NEXT
; FIND END OF STMT
; JUST IN CASE
; MUST BE ON
; GET CHR
; NOT END OF TEXT
; CLEAR 1ST LEVEL RTS
; RTN TO CALLER OR HIS CALL

```


UTILITIES

```

0000: 1 *
0000: 2 *VARIOUS BIT PAD HI-RES ROUTINES
0000: 3 *BY DAVE M. LINCER
0000: 4 *COPYRIGHT APPLE COMPUTER CO.
0000: 5 * JUNE 1979
0000: 6 *
0000: 7 DRG $6000
0000: 8 DBJ $2000
0000: 9 HBASL EQU $00
0000: 10 HBASH EQU $01
0000: 11 HMASK EQU $02
0000: 12 ZTEM EQU $03
0000: 13 XOL EQU $2FF
0000: 14 XOH EQU $2FE
0000: 15 YQ EQU $2FD
0000: 16 FLGL EQU $2FC
0000: 17 FLQH EQU $2FB
0000: 18 XL EQU FLGL
0000: 19 XH EQU FLQH
0000: 20 *
0000: 21 *WHITE PICK OFF
0000: 22 *
0000: 23 WHITE TXA SAVE X,Y AND ZPG
0001: 48 PHA
0002: 98 TYA
0003: 48 PHA
0004: A2 03 LDX $03
0006: B5 00 LDA $00,X
0008: 48 PHA
0009: CA DEX
000A: 10 FA BPL SLP,ZPG
000C: AD FF 02 LDA XOL
000F: BD 55 60 STA PKE1
0012: BD 91 60 STA PKE2
0015: A9 00 LDA $00
0017: BD FD 02 STA YQ
001A: BD FF 02 STA XOL
001D: BD FE 02 STA XOH
0020: BD FC 02 STA FLGL
0023: BD FB 02 STA FLQH
0026: 20 C3 60 JSR HPOSN
0029: AE FF 02 LDX XOL
002C: AC FE 02 LDY XOH
002F: 20 ED 60 JSR XPOS
0032: B1 00 LDA (HBASL),Y
0034: 25 02 AND HMASK
0036: B5 03 STA ZTEM
0038: F0 02 BEQ ITZOFF
003A: A9 01 LDA $01
003C: 18 CLC
003D: 6D FC 02 ADC FLGL
0040: BD FC 02 STA FLGL
0043: 29 00 AND $00
0045: 6D FB 02 ADC FLQH
0048: BD FB 02 STA FLQH
004B: AD FC 02 LDA FLGL
004E: C9 02 CMP $02
0050: AD FB 02 LDA FLQH
0053: E9 00 SBC $00
0055: 90 0A BCC LN130
0057: A5 03 LDA ZTEM
0059: D0 06 BNE LN130
005B: 20 02 61 JSR CLER
005E: 4C 73 60 JMP NXTX
0061: AD FC 02 LDA FLGL
0064: 0D FB 02 ORA FLQH
0067: F0 04 BEQ ZFG
0069: A5 03 LDA ZTEM
006B: D0 06 BNE NXTX

```

SAVE X,Y AND ZPG

SAVED
SELF MODIFY
BCC INTO BCS

INIT MY REGS
TO UPPER LEFT
W/NO BITS ON

FIRST TIME
NEXT TIME ONLY
CHANGE Y &
HMASK
DO AN
HSCRN @ X,Y
SAVE BIT
??
NOPE
YUP
INC FLG CNTR
BY BIT ON
CARRY FROM LOW ADD
IS ADDED TO FLQH

IS THERE MORE
THAN 2 BITS ON
2 BYTE TEST

CS FOR DEL WHITE
BIT?
ON?
NO,OFF
NEXT HORIZ POS
IS ANY ON?

NO
YES AND IF
Z=1 THEN OK

```

606D: 8D FC 02
6070: 8D FB 02
6073: EE FF 02
6076: D0 03
6078: EE FE 02
607B: AD FF 02
607E: C9 18
6080: AD FE 02
6083: E9 01
6085: 90 A2
6087: AD FC 02
608A: C9 02
608C: AD FB 02
608F: E9 00
6091: 90 03
6093: 20 02 61
6096: A9 00
6098: 8D FC 02
609B: 8D FB 02
609E: 8D FF 02
60A1: 8D FE 02
60A4: EE FD 02
60A7: 20 C3 60
60AA: AD FD 02
60AD: C9 C0
60AF: B0 03
60B1: 4C 29 60
60B4: A2 00
60B6: 68
60B7: 93 00
60B9: E8
60BA: E0 04
60BC: D0 FB
60BE: 68
60BF: A8
60C0: 68
60C1: AA
60C2: 60
60C3:
60C3: AD FD 02
60C6: AE FF 02
60C9: AC FE 02
60CC: 48
60CD: 29 C0
60CF: B5 00
60D1: 4A
60D2: 4A
60D3: 05 00
60D5: B5 00
60D7: 68
60D8: B5 01
60DA: 0A
60DB: 0A
60DC: 0A
60DD: 26 01
60DF: 0A
60E0: 26 01
60E2: 0A
60E3: 66 00
60E5: A9 01
60E7: 29 1F
60E9: 09 40
60EB: B5 01
60ED: BA
60EE: C0 00
60F0: F0 05
60F2: A0 23
60F4: 69 04
60F6: C8

```

```

70 ZFG
71
72 NXTX
73
74
75 TESTX
76
77
78
79
80
81
82
83
84 PKE2
85
86 NXTY
87
88
89
90
91
92
93
94
95
96
97 RET1
98 RLP
99
100
101
102
103
104
105
106
107
108 *
109 *HPOSN HRES BIT POSN ROUT
110 *READ ABOUT THIS CODE IN UTILITY ROM MANUAL
111 *
112 HPOSN LDA YQ
113 LDY XOL
114 LDY XOH
115 HPOS PHA
116 AND $00
117 STA HBASL
118 LSR A
119 LSR A
120 ORA HBASL
121 STA HBASL
122 PLA
123 STA HBASH
124 ASL A
125 ASL A
126 ASL A
127 ROL HBASH
128 ASL A
129 ROL HBASH
130 ASL A
131 ROR HBASL
132 LDA HBASH
133 AND $01F
134 ORA $040
135 STA HBASH
136 XPOS TXA
137 CPY $00
138 BEQ HPOSN2
139 LDY $023
140 ADC $04
141 HPOSN1 INY

```

```

ELSE ZERO
FLAG
INC CNT FIRST
THEN TEST
X HIGH
2 BYTE TEST
FOR XPOS=
279 OR
$118
IF OK ELSE
END OF X LOOP
MAKE SURE TO
CATCH LAST
WHITE OR COLOR
CS FOR DEL CLR
CLEAR OUT
RESET X AND
FLAG

THEN INC YQ
REPOSN
AND TEST
FOR Y=191
WE'RE DONE
NO CONTINUE (LONG BRANCH)
BRING BACK ALL
ZPAGE
AND X,Y


```


THIS ENTRY ONLY
COMPUTES Y & HMASK

60F7	E9 07	142	HPOSN2	SBC #*7	
60F9	80 F0	143		BCS HPOSN1	
60FB	AA	144		TAX	
60FC	8D 4F 60	145		LDA MSKTBL-249, X	
60FF	85 02	146		STA HMASK	
6101	60	147		RTS	
6102		148	*		
6102		149	*CLER CLEAR	BACK FLQ+1 BITS	
6102		150	*		
6102	38	151	CLER	SEC	FIND XO-FLG
6103	AD FF 02	152		LDA XOL	DOUBLE BYTE
6106	ED FC 02	153		SBC FLGL	
6109	8D FC 02	154		STA XL	
610C	AD FE 02	155		LDA XOM	
610F	ED FB 02	156		SBC FLGH	
6112	8D FB 02	157		STA XH	WITH RESULT IN XL, XH
6115	AE FC 02	158	CLOP	LDX XL	SETUP FOR XPOSN
6118	AC FB 02	159		LDY XH	
611B	20 ED 60	160		JSR XPOS	
611E	A5 02	161		LDA HMASK	DELETE THE BIT
6120	49 FF	162		EOR #*FF	@ Y, HMASK
6122	31 00	163		AND (HBASL), Y	ON LINE HBASL
6124	91 00	164		STA (HBASL), Y	
6126	1B	165		CLC	
6127	AD FC 02	166		LDA XL	FAKE OUT TEST SO
612A	69 01	167		ADC #*01	THAT
612C	CD FF 02	168		CMP XOL	WE ONLY GO TO
612F	AD FB 02	169		LDA XH	XO-1
6132	ED FE 02	170		SBC XOM	
6135	EE FC 02	171		INC XL	
6138	D0 03	172		BNE XOK	NOW INC XL, XH
613A	EE FB 02	173		INC XH	
613D	90 D6	174	XOK	BCC CLOP	CONTINUE
613F	A9 00	175		LDA #*00	DONE CLEAR
6141	8D FC 02	176		STA FLGL	FLAG
6144	8D FB 02	177		STA FLGH	
6147	60	178		RTS	AND RETURN
6148		179	*		
6148		180	*MSKTBL HMASK LOOKUP TABLE		
6148		181	*		
6148	01 02 04	182	MSKTBL	DFB #01, #02, #04, #08	
6148	08	183		DFB #10, #20, #40	
614C	10 20 40	184		PAGE	
614F		185	*		
614F		186	*HIRES PICK STUPID PICK ROUTINE		
614F		187	*		
614F		188	*ALTM = #80 FOR COLOR SET 1		
614F		189	*ALTM = #00 FOR COLOR SET 2		
614F		190	*COLR = #AA FOR PUR&BLU		
614F		191	*COLR = #D5 FOR GRN&ORG		
614F		192	*		
614F		193	ALTM	EGU #2FE	
614F		194	COLR	EGU #2FF	
614F		195	A1L	EGU #00	
614F		196	A1H	EGU #01	
614F		197	*		
614F		198	*HIRES PICK OFF		
614F		199	*		
614F	98	200	HPICK	TYA	SAVE Y, X AND ZPG
6150	48	201		PHA	
6151	A5 00	202		LDA A1L	#00
6153	48	203		PHA	
6154	A5 01	204		LDA A1H	#01
6156	48	205		PHA	
6157	A0 00	206		LDY #*00	SET INDEX
6159	B4 00	207		STY A1L	SET ZPG CTRS
615B	A9 40	208		LDA #*40	
615D	B5 01	209		STA A1H	TO BEGINNING OF
615F	B1 00	210	LOOP	LDA (A1L), Y	PICK UP BYTE
6161	4D FE 02	211		EOR ALTM	CHANGE SETBIT
6164	30 04	212		BMI OKBYT	IF RIGHT SET

6166	A9 00	213		LDA #00	WRONG SET CLR BYT
6168	F0 0C	214		BEG STOR1	ALWAYS TAKEN
616A	A5 00	215	OKBYT	LDA A1L	ARE ON ODD OR EVEN
616C	4A	216		LSR A	BYTE? THE CARRY KNOWS
616D	AD FF 02	217		LDA COLR	IF EVEN THEN
6170	80 02	218		BCS STOR	SHIFT ELSE STOR
6172	49 7F	219		EOR #*7F	SHIFT MASK
6174	31 00	220	STOR	AND (A1L), Y	WIPE OUT EXTRA
6176	91 00	221	STOR1	STA (A1L), Y	AND STORE IT
6178	A5 00	222		LDA A1L	GOTO NEXT BYTE
617A	C9 FF	223		CMP #*FF	WITH TEST FOR
617C	A5 01	224		LDA A1H	END OF HSCRN
617E	E9 5F	225		SBC #*5F	(#5FFF)
6180	E6 00	226		INC A1L	
6182	D0 02	227		BNE CHLOP	
6184	E6 01	228		INC A1H	
6186	90 D7	229	CHLOP	BCC LOOP	
6188	68	230		PLA	CC ON NOT END
6189	85 01	231		STA A1H	RETURN Y AND ZPG
618B	68	232		PLA	
618C	85 00	233		STA A1L	
618E	68	234		PLA	
618F	A8	235		TAY	
6190	60	236		RTS	
6191		237		PAGE	

*** SUCCESSFUL ASSEMBLY: NO ERRORS





10260 Bandley Drive
Cupertino, California 95014
408 996-1010